

# AXIS TQ.1952-E Cable Gland Ex e Non-Armored

## Cable gland for non-armored cables

For hazardous area compliance, the Ex e cable gland maintains a secure entry where the non-armored cable connects to the camera or junction box. The cable gland is certified for increased safety. It fits cable entries with M20x1.5 threads.

- > **Certified for ATEX and IECEx**
- > **Outdoor use**
- > **For hazardous areas**



## AXIS TQ1952-E Cable Gland Ex e Non-Armored

Approvals		Operating conditions
Product markings	ATEX, CE, IECEx	-40 °C to 85 °C (-40 °F to 185 °F)
Supply chain	TAA compliant	Dimensions
Explosion	IEC/EN 60079-0, IEC/EN 60079-7, IEC/EN 60079-31	Cable diameter: 8–13 mm
Certifications	Model key: K100-1020-00-EX ATEX: II 2 G Ex eb IIC Gb II 2 D Ex tb IIIC Db Certificate: BVS 17 ATEX E 118 X IECEx: Ex eb IIC Gb Ex tb IIIC Db Certificate: IECEx BVS 17.0101X	Weight
General		42 g (0.09 lb)
Casing	IP66-, IP67-, and IP68-rated Nickel plated brass	Warranty
		5-year warranty, see <a href="https://www.axis.com/warranty">axis.com/warranty</a>
		Sustainability
		Substance control
		PVC free, BFR/CFR free in accordance with JEDEC/ECA Standard JS709 RoHS in accordance with EU RoHS Directive 2011/65/EU and 2015/863 and EN IEC 63000:2018 REACH in accordance with (EC) No 1907/2006. For SCIP UUIID, see <a href="https://echa.europa.eu">echa.europa.eu</a>
		Environmental responsibility
		<a href="https://www.axis.com/environmental-responsibility">axis.com/environmental-responsibility</a> Axis Communications is a signatory of the UN Global Compact, read more at <a href="https://www.unglobalcompact.org">unglobalcompact.org</a>