

# ExCam XF P1377 Explosion-Protected Camera

## Zone-certified fixed camera with excellent image quality

Certified (ATEX, IECEx, EAC Ex, IA, INMETRO and PESO) for use in potentially combustible environments, this lightweight camera offers high quality, high resolution images of people and objects. Featuring Axis Lightfinder and Axis Forensic WDR, it delivers true colors and great details in challenging light or near darkness. It includes electronic image stabilization for stable images despite vibration. And, intelligent i-CS lens technology facilitates fast and easy installation with remote zoom. Built-in cybersecurity features such as signed firmware and secure boot ensure the integrity and authenticity of the firmware. Furthermore, Axis Zipstream with support for H.264/H.265 significantly lowers bandwidth and storage requirements.

- > 30 fps in 5 MP or up to 180 fps in HDTV 720p
- > Lightfinder and Forensic WDR
- > Zipstream supporting H.264 and H.265
- > Signed firmware and secure boot
- > ATEX, IECEx, EAC Ex, IA, INMETRO and PESO



# ExCam XF P1377 Explosion-Protected Camera

<b>Camera</b>		<b>Event actions</b>	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap PTZ: PTZ preset, start/stop guard tour Overlay text, external output activation, play audio clip, WDR mode, day/night mode MQTT publish
<b>Image sensor</b>	1/2.7" progressive scan RGB CMOS	<b>Data streaming</b>	Event data
<b>Lens</b>	IR-corrected i-CS lens Varifocal 3.9–10 mm, F1.5 4:3 aspect ratio: Horizontal field of view: 75°–31° Vertical field of view: 55°–23° 16:9 aspect ratio: Horizontal field of view: 75°–31° Vertical field of view: 41°–17° Remote zoom, remote focus	<b>Built-in installation aids</b>	Focus assistant, pixel counter, remote back focus, autorotation
<b>Day and night</b>	Automatically removable infrared-cut filter	<b>Analytics</b>	
<b>Minimum illumination</b>	5 MP 25/30 fps with Forensic WDR and Lightfinder: Color: 0.15 lux, at 50 IRE F1.5 B/W: 0.03 lux, at 50 IRE F1.5	<b>Applications</b>	<b>Included</b> AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard AXIS Video Motion Detection, active tampering alarm, gatekeeper <b>Supported</b> AXIS Live Privacy Shield, AXIS Perimeter Defender Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="https://axis.com/acap">axis.com/acap</a>
<b>Shutter speed</b>	WDR: 1/33500 s to 1/5 s No WDR: 1/5000 s to 1/5 s	<b>Cybersecurity</b>	
<b>System on chip (SoC)</b>		<b>Edge security</b>	<b>Software:</b> Signed firmware, brute force delay protection, digest authentication and OAuth 2.0 RFC6749 OpenID Authorization Code Flow for centralized ADFS account management, password protection, AES-XTS-Plain64 256bit SD card encryption <b>Hardware:</b> Secure boot
<b>Model</b>	ARTPEC-7	<b>Network security</b>	IEEE 802.1X (EAP-TLS, PEAP-MSCHAPv2), IEEE 802.1AE (MACsec PSK/EAP-TLS), HTTPS/HSTS, TLS v1.2/v1.3, Network Time Security (NTS), X.509 Certificate PKI, host-based firewall
<b>Memory</b>	1 GB RAM, 512 MB Flash	<b>Documentation</b>	<i>AXIS OS Hardening Guide</i> <i>Axis Vulnerability Management Policy</i> <i>Axis Security Development Model</i> AXIS OS Software Bill of Material (SBOM) AXIS OS Software Bill of Material (SBOM) To download documents, go to <a href="https://axis.com/support/cybersecurity/resources">axis.com/support/cybersecurity/resources</a> To read more about Axis cybersecurity support, go to <a href="https://axis.com/cybersecurity">axis.com/cybersecurity</a>
<b>Video</b>		<b>General</b>	
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Motion JPEG	<b>Casing</b>	IP68-rated, EN 1.4404 (ASTM 316L) stainless steel casing for maximum corrosion protection Casing manufactured and certified by Samcon Prozessleittechnik GmbH, <a href="https://www.samcon.eu">www.samcon.eu</a>
<b>Resolution</b>	2592x1944 (5 MP) to 160x90 2688x1512 (4 MP) to 160x90 1280x720 (HDTV 720p) to 160x90	<b>Power</b>	<b>Camera:</b> Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3, max 10.7 W, typical 5.4 W <b>Heater:</b> 24 V DC, max 40 W 24 V DC is required for operating at temperatures below 0 °C (32 °F).
<b>Frame rate</b>	Capture mode 5 MP: 25/30 fps (50/60 Hz) Capture mode 4 MP: 25/30 fps (50/60 Hz) Capture mode HDTV 720p: 180 fps	<b>Connectors</b>	5 m (16 ft) pigtail cable for network (Cat 6, RJ45 connector) and power
<b>Video streaming</b>	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 Video streaming indicator	<b>Storage</b>	Pre-installed AXIS Surveillance microSDXC Card 128 GB Support for SD card encryption (AES-XTS-Plain64 256bit) Recording to network-attached storage (NAS) For SD card and NAS recommendations see <a href="https://axis.com">axis.com</a>
<b>Multi-view streaming</b>	Up to 8 individually cropped out view areas	<b>Operating conditions</b>	-60 °C to 60°C (-76 °F to 140 °F) Maximum temperature according to NEMA TS 2 (2.2.7): 74 °C (165 °F) Humidity 10-100% RH (condensing)
<b>Image settings</b>	Saturation, contrast, brightness, sharpness, Forensic WDR: Up to 120 dB depending on scene, white balance, day/night threshold, exposure mode, exposure zones, local contrast, tone mapping, compression, rotation: auto, 0°, 90°, 180°, 270° including Corridor Format, mirroring of images, dynamic text and image overlay, privacy masks, defogging, electronic image stabilization, barrel distortion correction, scene profiles: forensic, vivid, traffic overview	<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5-95% RH (non-condensing)
<b>Pan/Tilt/Zoom</b>	Digital PTZ	<b>Approvals</b>	<b>EMC</b> EN 55035, EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2 <b>Environment</b> IEC/EN 60529 IP68 <b>Network</b> NIST SP500-267 <b>Explosion</b> EN/IEC 60079-0, EN/IEC 60079-1, EN/IEC 60079-31,
<b>Network</b>			
<b>Network protocols</b>	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS, HTTP/2, TLS, QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SRTP/RTSPS, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCPv4/v6, ARP, SSH, LLDP, CDP, MQTT v3.1.1, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf)		
<b>System integration</b>			
<b>Application Programming Interface</b>	Open API for software integration, including VAPIX® and AXIS Camera Application Platform, specifications at <a href="https://axis.com">axis.com</a> One-Click Cloud Connection ONVIF® Profile G, ONVIF® Profile S, and ONVIF® Profile T, specification at <a href="https://onvif.org">onvif.org</a>		
<b>Onscreen controls</b>	Electronic image stabilization Day/night shift Defogging Wide dynamic range		
<b>Event conditions</b>	Analytics, shock detection, edge storage events, supervised external input, audio level, time scheduled, MQTT subscribe		

	TR CU 012/2011, GOST R IEC 60079-0, GOST IEC 60079-1, GOST R IEC 60079-31	Armored cables ExCam, 10, 25, 95 m (33, 82, 312 ft), Ex Connection Rail 4-port PoE PS 24, Ex Connection Rail 8-port PoE PS 24, Weathershield ExCam XF For more accessories, see <a href="https://axis.com">axis.com</a>
<b>Certifications</b>	<p>Model key: T08-VA2.3.K3.BOR2-LL.H-005.N-P ATEX: II 2 G Ex db IIC T5 Gb, II 2 D Ex tb IIIC T95°C Db Certificate: TÜV 18 ATEX 8218X IECEX: Ex db IIC T5 Gb, Ex tb IIIC T95°C Db Certificate: IECEX TUR 18.0023X IA: Ex db IIC T5 Gb, Ex tb IIIC T95°C Db Certificate: MASC MS/18-3256X EAC Ex: 1Ex db IIC T5 Gb, Ex tb IIIC T 95°C Db Series: T8, Model: T08-VA2.3. Certificate: RU C-DE.HA65.B.01652/22 INMETRO: Ex db IIC T5 Gb, Ex tb IIIC T95°C Db Certificate: TÜV 23.0363X PESO: Ex db IIC T5 Gb Certificate: A/P/HQ/KA/104/5735 UKCA: II 2 G Ex db IIC T5 Gb, II 2 D Ex tb IIIC T95 °C Db Certificate: TÜV 22 UKEX 7137 X</p>	
<b>Dimensions</b>	<p>ø 113 mm (4.4 in) Height: 160.5 mm (6.3 in ) Length: 334 mm (13.1 in )</p>	
<b>Weight</b>	7.8 kg (17.2 lb)	
<b>Included accessories</b>	Installation Guide, Windows® decoder 1-user license, SKDP03-T Cable ExCam 5 meter, AXIS Surveillance microSDXC Card 128 GB	
<b>Optional accessories</b>	Wall Mount ExCam XF, Pole Mount ExCam XF, EXTB-3 Junction Box ExCam, Non-armored cables ExCam, 10, 25, 95 m (33, 82, 312 ft),	
		<b>Video management software</b> AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at <a href="https://axis.com/vms">axis.com/vms</a>
		<b>Languages</b> English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese, Dutch, Czech, Swedish, Finnish, Turkish, Thai, Vietnamese, Polish
		<b>Warranty</b> 5-year warranty, see <a href="https://axis.com/warranty">axis.com/warranty</a>
		<b>Sustainability</b>
		<b>Substance control</b> PVC free Free of hazardous brominated and chlorinated flame retardants (BFR/CFR free) RoHS in accordance with EU RoHS Directive 2011/65/EU/ and EN 63000:2018 REACH in accordance with (EC) No 1907/2006. For SCIP UUID, see <a href="https://echa.europa.eu">echa.europa.eu</a>
		<b>Environmental responsibility</b> <a href="https://axis.com/environmental-responsibility">axis.com/environmental-responsibility</a> Axis Communications is a signatory of the UN Global Compact, read more at <a href="https://unglobalcompact.org">unglobalcompact.org</a>