

# AXIS A4120-E Reader with Keypad

## Secure RFID reader with keypad

Designed to perfectly match Axis network door controllers and Axis credentials, AXIS A4120-E Reader with Keypad offers secure and seamless entry. Ideal for use in harsh environments both indoors and outdoors, this keypad reader is easy to install on single-gang boxes, or mounted on the wall. It supports most types of smart RFID card standards with 13.56MHz credential technologies and includes out-of-the-box support for Open Supervised Device Protocol (OSDP) for secure bidirectional communication. Packed with built-in cybersecurity features, it helps prevent unauthorized access and safeguards your system. Furthermore, this smart reader supports Secure Channel Protocol (SCP) enabling secure communications and connections.

- > **Designed to perfectly match Axis door controllers and credentials**
- > **Support for most RFID cards with 13.56MHz**
- > **IP66, IK07 ratings for use in harsh environments**
- > **EAL6+ Certified Secure Element for added protection**
- > **Intuitive keypad offers unlimited touches**



## AXIS A4120-E Reader with Keypad

<b>RFID reader</b>		<b>Power</b>	Input: 12 V DC Current consumption: Typical 85 mA@ 12 V, peak 120 mA@ 12 V H-field strength = 17.5 dBµA/m @3m
<b>Reader technology</b>	13.56 MHz ISO14443A and ISO14443B (MIFARE Classic®, MIFARE Plus® (Level 1), MIFARE DESFire® EV1 and EV2).	<b>Connectors</b>	4-pin 26–18 AWG terminal block for RS485 (A/B) and power (+/-)
<b>Network protocols</b>	Open supervised device protocol (OSDP)	<b>Cable requirements</b>	Power: 26–18 AWG (0.13–0.82 mm <sup>2</sup> ) Reader data: 1 twisted pair with shield, 26–18 AWG (0.13–0.82 mm <sup>2</sup> ), 120 ohm impedance, for A and B. Qualified for up to 1000 m (3281 ft) – 24 AWG.
<b>Alarm status indication</b>	RGB LED for user feedback, buzzer	<b>Operating conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 10–100% RH (condensing)
<b>Tampering</b>		<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
<b>Detection type</b>	Built-in tamper switch for detecting both open casing and removal from wall	<b>Approvals</b>	EMC EN 55032 Class B, EN 61000-6-1, EN 61000-6-3, FCC Part 15 Subpart B Class B Wireless EN 300330, EN 301489-1, EN 301489-3, EN 50364, EN 62311, FCC Part 15 Subpart C Safety CAN/CSA-C22.2 No. 60950-22, CAN/CSA C22.2 No. 62368-1, IEC/EN/UL 60950-22, IEC/EN/UL 62368-1, UL 294 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP66, IEC/EN 62262 IK07, NEMA 250 Type 4X
<b>Cybersecurity</b>		<b>Dimensions</b>	121 x 85 x 27 mm (4.76 x 3.35 x 1.06 in)
<b>Edge security</b>	Hardware: Axis Edge Vault cybersecurity platform Secure element (CC EAL 6+), secure keystore, secure boot	<b>Weight</b>	258 g (9.10 oz)
<b>Documentation</b>	<i>AXIS OS Hardening Guide</i> <i>Axis Vulnerability Management Policy</i> <i>Axis Security Development Model</i> To download documents, go to <a href="https://axis.com/support/cybersecurity/resources">axis.com/support/cybersecurity/resources</a> To read more about Axis cybersecurity support, go to <a href="https://axis.com/cybersecurity">axis.com/cybersecurity</a>	<b>Warranty</b>	5-year warranty, see <a href="https://axis.com/warranty">axis.com/warranty</a>
<b>General</b>			
<b>Keypad</b>	Capacitive touch, 3x4 layout		
<b>Casing</b>	IP66 and NEMA 4X-rated, IK07 plastic casing, hard-coated scratch- and impact-resistant front Color: black NCS S 9000-N		
<b>Mounting</b>	Suitable for single-gang box door installations or any flat surface mounting		
<b>Security</b>	EAL 6+ Certified Secure Element Hardware		