

AXIS M1135-E Network Camera

Outdoor-ready 2 MP premium affordable surveillance.

AXIS M1135-E is a compact, outdoor-ready network camera that's easy to install and operate. It supports PoE and redundant DC power, so your data is safeguarded in the event of a power outage. Featuring Axis Lightfinder and Axis Forensic WDR it delivers true colors and great details in challenging light or near darkness. It includes a CS-mount allowing you to easily change lens to meet your specific requirements. Plus, audio input lets you record video with sound. Furthermore, Axis Zipstream with H.264/H.265 significantly lowers bandwidth and storage requirements and enhanced security features ensures the integrity and authenticity of the firmware.

- > **2 MP / HDTV 1080p at 30 fps**
- > **Lightfinder and Forensic WDR**
- > **Audio input**
- > **Exchangeable CS mount lens**
- > **Zipstream supporting H.264 and H.265**



AXIS M1135-E Network Camera

Camera	
Image sensor	Progressive scan RGB CMOS 1/2.9"
Lens	Varifocal, IR corrected, CS-mount, DC-iris, 3–10.5 mm Horizontal field of view: 90°–33° Vertical field of view: 49°–19°
Day and night	Automatically removable infrared-cut filter
Minimum illumination	HDTV 1080p 25/30 fps with Forensic WDR and Lightfinder: Color: 0.15 lux at 50 IRE, F1.4 B/W: 0.03 lux at 50 IRE, F1.4 HDTV 1080p 25/30 fps with Forensic WDR and Lightfinder: Color: 0.1 lux at 30 IRE, F1.4 B/W: 0.02 lux at 30 IRE, F1.4
Shutter speed	1/33500 to 2 s
System on chip (SoC)	
Model	ARTPEC-7
Memory	512 MB RAM, 512 MB Flash
Video	
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG
Resolution	1920x1080 to 160x90
Frame rate	Up to 25/30 fps in all resolutions
Video streaming	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265
Image settings	Axis Forensic WDR: up to 120 dB depending on scene, manual shutter time, compression, color, brightness, sharpness, contrast, white balance, exposure control (including automatic gain control), exposure zones, fine tuning of behavior at low light, aspect ratio correction, text and image overlay, privacy mask, mirroring of images
Pan/Tilt/Zoom	Digital PTZ
Audio	
Audio streaming	Audio in, simplex
Audio encoding	24bit LPCM, AAC-LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz Configurable bit rate
Audio input/output	External microphone input or line input, automatic gain control
Network	
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1x (EAP-TLS) ^a network access control, digest authentication, user access log, brute force delay protection, signed firmware, secure boot
Supported protocols	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTP/2, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SOCKS, SSH, LLDP, CDP, MQTT v3.1.1, Syslog, Link-Local address (ZeroConf) IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTP/2, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SOCKS, SSH, LLDP, CDP, MQTT v3.1.1, Syslog, Link-Local address (ZeroConf)
System integration	
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com AXIS Video Hosting System (AVHS) with One-Click Connection One-click cloud connection ONVIF [®] Profile G, and ONVIF [®] Profile S, specification at onvif.org
Event conditions	Audio: audio detection Device status: above operating temperature, above or below operating temperature, below operating temperature, IP address

	removed, network lost, new IP address, storage failure, system ready, within operating temperature Edge storage: recording ongoing, storage disruption I/O: digital input, manual trigger, virtual input MQTT subscribe Scheduled and recurring: scheduled event Video: day/night mode, live stream open, tampering
Event actions	File upload via FTP, HTTP HTTPS, SFTP, network share and email MQTT publish Notification via email, HTTP, HTTPS, TCP Video recording to edge storage, pre- and post-alarm video buffering, PTZ preset, guard tour, send video clip, send SNMP trap, day/night vision mode, WDR mode, status LED indicator, output port
Data streaming	Event data
Built-in installation aids	Pixel counter
Analytics	
Applications	Included AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard AXIS Video Motion Detection, active tampering alarm Supported Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap
General	
Casing	IP66- and NEMA 4X-rated, IK10 impact-resistant polymer enclosure Color: White NCS S 1002-B
Sustainability	PVC free
Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 2, max 6.49 W, typical 4.1 W 8–28 V DC, max 6.49 W, typical 3.8 W
Connectors	RJ45 10BASE-T/100BASE-TX PoE Terminal block for one input and one output (12 V DC output, max load 25 mA) DC input, terminal block 3.5 mm mic/line in
Storage	Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Operating conditions	–25 °C to 50 °C (–13 °F to 122 °F) Maximum temperature (intermittent): 55 °C (131 °F) Maximum temperature according to NEMA TS2 (2.27) 74 °C (165° F) Start-up temperature: –20 °C (–4 °F) Humidity 10–100% RH (condensing)
Storage conditions	–40 °C to 65°C (–40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
Approvals	EMC EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), VCCI Class A, RCM AS/NZS CISPR 32 Class A, KC KN32 Class A, KC KN35 Safety IEC/EN/UL 62368-1, CAN/CSA C22.2 No. 62368-1, IEC/EN/UL 60950-22, CAN/CSA-C22.2 No. 60950-22IS 13252 Environment EN 50581, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP66, NEMA 250 Type 4X, IEC/EN 62262 IK10, NEMA TS 2 (2.2.7-2.2.9) Network NIST SP500-267
Dimensions	240 x 143 x 372 mm (9.5 x 5.6 x 14.7 in) including wall mount
Weight	1.8 kg (4.0 lb) including wall mount
Included accessories	AXIS T94Q01A Wall Mount, Torx [®] T20 screw driver, Torx [®] T30 screw bit, connector kit, installation guide, Windows [®] decoder 1-user license

Optional accessories	AXIS T94R01P Conduit Back Box, AXIS T98A16-VE Surveillance Cabinet Series, AXIS T91B47 Pole Mount, AXIS T90B Illuminators, AXIS T8351 Mk II Microphone 3.5 mm	a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).</i>
Optional lenses	Computar 12.5-50 mm, DC-iris Lens CS 2.8-13 mm F1.4 DC-Iris 5 MP	Environmental responsibility: axis.com/environmental-responsibility
Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at axis.com/vms	
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese	
Warranty	5-year warranty, see axis.com/warranty	