

AXIS Q1647 Network Camera

5 MP video with 1/2" sensor and i-CS lens

With AXIS Q1647 Network Camera it's easier than ever to capture everything. High resolution at full frame rate, i-CS lens, and 1/2" sensor ensures outstanding details and sharp images. Even in challenging or low light, Forensic WDR and Lightfinder ensures details will be discovered. To minimize vibrations, electronic image stabilization (EIS) keeps the image steady. AXIS Q1647 enables proactive surveillance with preinstalled AXIS Motion Guard and AXIS Fence Guard. Orientation aid enables street view and compass rose for quick orientation with multiple monitors, and Zipstream optimizes the video stream to maintain high video quality while saving bandwidth and storage.

- > **5 MP resolution at 25/30 fps**
- > **1/2" sensor**
- > **Forensic WDR and Lightfinder**
- > **Electronic image stabilization (EIS)**
- > **AXIS Motion Guard and AXIS Fence Guard**



AXIS Q1647 Network Camera

Camera	
Image sensor	1/2" progressive scan RGB CMOS
Lens	Varifocal, IR corrected, CS-mount 3.9–10.0 mm, F1.5 5.3 MP (16:9): Horizontal field of view: 110°–44° Vertical field of view: 59°–24° 4 MP (16:9): Horizontal field of view: 95°–38° Vertical field of view: 52°–21° 5 MP (4:3): Horizontal field of view: 92°–37° Vertical field of view: 68°–27° i-CS lens
Day and night	Automatically removable infrared-cut filter
Minimum illumination	5 MP 25/30 fps with WDR and Lightfinder: Color: 0.12 lux at 50 IRE, F1.5; B/W: 0.02 lux at 50 IRE, F1.5 4 MP 50/60 fps: Color: 0.24 lux at 50 IRE, F1.5, B/W; 0.04 lux at 50 IRE, F1.5
Shutter speed	1/100000 to 2 s
Pan/Tilt/Zoom	Digital PTZ, uploadable PTZ driver (Pelco D pre-installed)
System on chip (SoC)	
Model	ARTPEC-6
Memory	1 GB RAM, 512 MB Flash
Video	
Video compression	H.264 (MPEG-4 Part 10/AVC), Main, Baseline and High Profile Motion JPEG
Resolution	3072x1728 to 320x180
Frame rate	5 MP with WDR: 25/30 fps with power line frequency 50/60 Hz 4 MP without WDR: 50/60 fps with power line frequency 50/60 Hz
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/ABR/MBR H.264
Image settings	Saturation, contrast, brightness, sharpness, Forensic WDR – 120 dB, white balance, day/night threshold, exposure mode, exposure zones, compression, orientation: auto, 0°, 90°, 180°, 270° including corridor format, mirroring of images, dynamic text overlay, image overlay, privacy masks, defogging, noise reduction, electronic image stabilization, barrel distortion correction, orientation aid, fine tuning of behavior at low light Scene profiles: forensic, vivid, traffic overview, backlit entrance
Audio	
Audio streaming	Two-way, full duplex
Audio encoding	AAC-LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz Configurable bit rate
Audio input/output	External balanced/unbalanced microphone or line input, line output, built-in microphone, automatic gain control 24 bit AD/DA-conversion
Network	
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1x (EAP-TLS) ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware
Network protocols	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTP/2, HTTPS ^a , TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP TM , SNMPv1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, RTSP, RTP, SFTP, SRTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SSH, LLDP, CDP, MQTT v3.1.1, Syslog, Link-Local address (ZeroConf).
System integration	
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com AXIS Video Hosting System (AVHS) with One-Click Connection One-Click Cloud Connection

	ONVIF [®] Profile G, ONVIF [®] Profile M, ONVIF [®] Profile S, and ONVIF [®] Profile T, specifications at onvif.org
Event conditions	Analytics, external input, edge storage events, virtual inputs through API Audio: audio detection Device status: above operating temperature, above or below operating temperature, below operating temperature, IP address removed, network lost, new IP address, storage failure, system ready, within operating temperature Edge storage: recording ongoing, storage disruption I/O: digital input, manual trigger, virtual input MQTT subscribe PTZ: PTZ malfunctioning, PTZ movement, PTZ preset position reached, PTZ ready Scheduled and recurring: scheduled event Video: average bitrate degradation, day-night mode, live stream open, tampering
Event actions	File upload: FTP, SFTP, HTTP, HTTPS, network share and email, send video clip Notification: email, HTTP, HTTPS and TCP Overlay text, Send SNMP Trap Video and audio recording to edge storage Pre- and post-alarm video buffering External output activation, day/night vision mode, play audio clip, status LED, WDR mode, defog mode, PTZ control MQTT publish
Data streaming	Event data
Built-in installation aids	i-CS: Remote zoom and focus Other lens: Remote back focus Traffic wizard, pixel counter, levelling assistant, autorotation
Analytics	
Applications	Included AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard AXIS Video Motion Detection, active tampering alarm, audio detection Supported AXIS Digital Autotracking Support for additional applications if the device is used with compatible accessories. For more information, contact your Axis partner. Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap
General	
Casing	Metal (zinc) Color lid: Silver - RAL 9006 Color chassi: Black - NCS S 9000-N
Sustainability	PVC free
Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Typical 5.3 W, max 10.8 W 8–28 V DC, typical 6.4 W, max 11.2 W
Connectors	Shielded RJ45 10BASE-T/100BASE-TX PoE I/O: 6-pin 2.5 mm terminal block for four configurable inputs/outputs (12 V DC output, max load 50 mA) RS485/RS422, 2 pcs, 2 pos, full duplex, terminal block 3.5 mm mic/line in, 3.5 mm line out i-CS connector (compatible with P-Iris and DC-iris)
Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Operating conditions	-20 °C to 60 °C (-4 °F to 140 °F) Humidity 10–85% RH (non-condensing)
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
Approvals	EMC EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KCC KN32 Class A, KN35 Safety IEC/EN/UL 62368-1, IS 13252 Environment

	IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78 Network NIST SP500-267	For more accessories, see axis.com
Dimensions	82 x 66 x 210 mm (3.23 x 2.60 x 8.25 in)	Video management software AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at axis.com/vms
Weight	950 g (2.1 lb)	Languages English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Included accessories	Stand, connector kit, resistor ^x T20 tool, installation guide, Windows [®] decoder 1-user license	Warranty 5-year warranty, see axis.com/warranty
Optional lenses	Fujinon Varifocal Lens 8-80 mm, DC-iris Lens CS 12-50 mm F1.4 P-Iris 8 MP Lens i-CS 9-50 mm F1.5 8 MP	a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (openssl.org), and cryptographic software written by Eric Young (eyay@cryptsoft.com).</i>
Optional accessories	AXIS T90B Illuminators, AXIS T92G Housings, AXIS T93F Housings, Axis network cable couplers, AXIS T8129 PoE Extender, AXIS T8415 Wireless Installation Tool, Axis midspans	Environmental responsibility: axis.com/environmental-responsibility