

# AXIS Companion Dome mini LE

## Outdoor full HD IR network camera

AXIS Companion Dome mini LE is an outdoor-ready day-and-night camera. It has built-in IR illumination for surveillance in total darkness and WDR technology that delivers sharp HD 1080p video even in scenes with complex light conditions. The compact design and weather-resistant enclosure enables discreet installations both indoors and out. Power over Ethernet (PoE) allows easy installation with a single cable to provide both network connectivity and electrical power. AXIS Companion Dome mini LE is supported only by the AXIS Companion video management software and mobile app, and requires an AXIS Companion Recorder for system completion.

- > **HD 1080p video quality**
- > **Surveillance in total darkness**
- > **Handles complex light conditions**
- > **Power over Ethernet (PoE)**
- > **Outdoor-ready**



## AXIS Companion Dome mini LE

<b>Camera</b>		<b>Connectors</b>	T/100BASE-TX PoE
<b>Image sensor</b>	1/2.8" progressive scan RGB CMOS	<b>IR illumination</b>	Power-efficient, long-life 850 nm IR LEDs. Range of reach up to 15 m (49 ft) depending on scene
<b>Lens</b>	Horizontal field of view: 100° Vertical field of view: 53° Fixed iris and IR corrected	<b>Storage</b>	AXIS Companion Recorder is required This camera does not support AXIS S3008 Recorder
<b>Day and night</b>	Automatically removable infrared-cut filter	<b>Operating conditions</b>	-20 °C to 50 °C (-4°F to 122°F) Humidity 10–85% RH
<b>Minimum illumination</b>	0 lux with IR illumination on	<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F)
<b>Camera angle adjustment</b>	Pan: 350° Tilt: +/-70° Rotation: +/-95° Can be directed in any direction	<b>Approvals</b>	EMC EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, VCCI Class A, ICES-003 Class A, RCM AS/NZS CISPR 32 Class A Safety IEC/EN/UL 62368-1, IEC/EN/UL 60950-22 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP66
<b>Video</b>		<b>Dimensions</b>	Height: 70 mm (2 3/4 in) ø 120 mm (4 3/4 in)
<b>Video compression</b>	H.265 (MPEG-H Part 2)	<b>Weight</b>	205 g (0.45 lb)
<b>Resolution</b>	1920x1080 HDTV 1080p and 640x360	<b>Included accessories</b>	Installation guide Tool mounting RJ45
<b>Frame rate</b>	Up to 25/30 fps with power line frequency 50/60 Hz	<b>Optional accessories</b>	AXIS T8415 Wireless installation tool AXIS T94B01P Conduit back box AXIS T91A27 Pole mount AXIS T94C01M J-box/gang box plate AXIS T94C01L Recessed mount AXIS T94C01U Universal mount AXIS Companion Weathershield A For more accessories, see <a href="http://axis.com">axis.com</a>
<b>Video streaming</b>	One high resolution and one low resolution, individually configurable streams Controllable frame rate	<b>Video management software</b>	AXIS Companion available on <a href="http://axis.com/vms">axis.com/vms</a>
<b>Image settings</b>	Color, brightness, sharpness, contrast, white balance, exposure control, rotation: 0°, 90°, 180°, 270°, including Corridor Format, privacy masks	<b>Warranty</b>	Axis 3-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a>
<b>Wide dynamic range</b>	WDR	a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).</i>	
<b>Network</b>		Environmental responsibility: <a href="http://axis.com/environmental-responsibility">axis.com/environmental-responsibility</a>	
<b>Security</b>	Password protection, HTTPS <sup>a</sup> encryption, digest authentication, user access log, signed firmware		
<b>Supported protocols</b>	IPv4/v6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , Bonjour, UPnP <sup>®</sup> , DNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP		
<b>System integration</b>			
<b>Event triggers</b>	Video motion detection		
<b>General</b>			
<b>Casing</b>	IP66-rated enclosure. Dome: clear PC. Bottom: PC+GF, black NCS S 9000-N. Cover: ASA, white NCS S 1002-B. For repainting instructions of casing and impact on warranty, contact your Axis partner.		
<b>Sustainability</b>	PVC free		
<b>Power</b>	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 1 Typical 2.1 W, max 3.2 W		