

AXIS P1378 Network Camera

Excellent details in 4K under any circumstances

AXIS P1378 captures excellent detailed images in 4K resolution. Featuring Axis Lightfinder and Axis Forensic WDR it delivers true colors and great details in challenging light or near darkness. It offers P-Iris for images with better contrast, clarity, resolution and depth of field. Designed to act as a deterrent, it includes electronic image stabilization for stable images as well as enhanced security features, barrel distortion correction, shock detection and scene profiles. Axis Zipstream supporting H.264/H.265 provides exceptional savings on bandwidth and storage. Plus, with CS mount and support for motorized i-CS, you can easily change lens to meet your requirements.

- > **4K resolution**
- > **Lightfinder and Forensic WDR**
- > **Signed firmware and secure boot**
- > **Electronic image stabilization**
- > **Zipstream supporting H.264 and H.265**



AXIS P1378 Network Camera

Camera		Onscreen controls	Electronic image stabilization Day/night shift Defogging Wide dynamic range
Image sensor	1/1.8" progressive scan RGB CMOS	Event triggers	Analytics, shock detection, edge storage events, supervised external input, audio level, time scheduled MQTT subscribe
Lens	IR corrected, CS-mount lens, P-Iris Varifocal 3.9–10 mm, F1.5 Horizontal field of view: 119°–45° Vertical field of view: 62°–25°	Event actions	MQTT publish Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap PTZ: PTZ preset, start/stop guard tour Overlay text, external output activation, play audio clip, WDR mode, day/night mode
Day and night	Automatically removable infrared-cut filter	Data streaming	Event data
Minimum illumination	4K 25/30 fps with Forensic WDR and Lightfinder: Color: 0.15 lux, at 50 IRE F1.5 B/W: 0.03 lux, at 50 IRE F1.5	Built-in installation aids	Focus assistant, pixel counter, remote back focus, autorotation
Shutter speed	1/8500 s to 1/5 s	Analytics	
System on chip (SoC)		AXIS Object Analytics	Object classes: humans, vehicles Trigger conditions: line crossing, object in area Up to 10 scenarios Metadata visualized with color-coded bounding boxes Polygon include/exclude areas Perspective configuration ONVIF Motion Alarm event
Model	ARTPEC-7	Applications	Included AXIS Object Analytics AXIS Video Motion Detection, active tampering alarm, audio detection Supported AXIS Live Privacy Shield Support for additional applications if the device is used with compatible accessories. For more information, contact your Axis partner. Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap
Memory	2 GB RAM, 512 MB Flash	General	
Compute capabilities	Machine learning processing unit (MLPU)	Casing	Metal (zinc) Color lid: White NCS S 1002-B Color chassis: Black NCS S 9002-N
Video		Mounting	¼"-20 tripod screw thread Camera stand included
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Motion JPEG	Sustainability	Free of hazardous brominated and chlorinated flame retardants (BFR/CFR free)
Resolution	3840x2160 (4K) to 160x90	Power	12–28 V DC, max 10.5 W, typical 6.1 W Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3, max 10.7 W, typical 6.2 W Power redundancy
Frame rate	25/30 fps (50/60 Hz) in all resolutions	Connectors	RJ45 10BASE-T/100BASE-TX/1000BASE-T I/O: 6-pin 2.5 mm terminal block, for 2 supervised alarm inputs and 2 outputs RS485/RS422, 2 pcs, 2 pos, full duplex, terminal block DC input, terminal block, 3.5 mm mic/line in, 3.5 mm line out i-CS connector (compatible with P-Iris and DC-Iris) Security lock slot AXIS T92G20 connector
Video streaming	Multiple, individually configurable streams in H.264, H.265, and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 Video streaming indicator	Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Multi-view streaming	Up to 8 individually cropped out view areas	Operating conditions	-10 °C to 55 °C (14 °F to 131 °F) Humidity 10–85% RH (non-condensing)
Image settings	Saturation, contrast, brightness, sharpness, Forensic WDR: Up to 120 dB depending on scene, white balance, day/night threshold, exposure mode, exposure zones, local contrast, tone mapping, compression, orientation: auto, 0°, 90°, 180°, 270° including Corridor Format, mirroring of images, dynamic text and image overlay, privacy masks, defogging, electronic image stabilization, barrel distortion correction, scene profiles: forensic, vivid, traffic overview	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
Pan/Tilt/Zoom	Digital PTZ Uploadable PTZ driver (Pelco D pre-installed)	Approvals	EMC EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A,
Audio			
Audio streaming	Two-way, full duplex		
Audio encoding	AAC LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz, LPCM 48 kHz Configurable bit rate		
Audio input/output	External microphone input, line input, digital input with ring power, line output, built-in microphone (can be disabled), automatic gain control		
Network			
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X (EAP-TLS) ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot		
Supported protocols	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS ^a , HTTP/2, TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP [™] , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, RTSP, RTP, SRTP, SFTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SOCKS, SSH, LLDP, CDP, MQTT v3.1.1, Syslog, Link-Local address (ZeroConf)		
System integration			
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform, specifications at axis.com One-Click Cloud Connection ONVIF [®] Profile G, ONVIF [®] Profile M, ONVIF [®] Profile S, and ONVIF [®] Profile T, specification at onvif.org		

	ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KCC KN32 Class A, KN35
	Safety IEC/EN/UL 62368-1, IS 13252
	Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78
	Network NIST SP500-267
Dimensions	214 x 80 x 57 mm (8 7/16 x 3 1/8 x 2 1/4 in)
Weight	750 g (1.7 lb)
Included accessories	Connector kit, Installation Guide, Windows® decoder 1-user license, stand, Resistorx® L-key TR20, Torx® L-key T6
Optional lenses	Lens CS 4-10 mm F0.9 P-Iris Lens i-CS 3.9-10 mm F1.5 8 MP Lens i-CS 9-50 mm F1.5 8 MP

Optional accessories	Axis mounts, Axis lenses, Axis midspans, Axis microphones AXIS TQ1809-LE Housing T92G AXIS T8355 Digital Microphone For more accessories, see axis.com
Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available at axis.com/vms
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese, Polish
Warranty	5-year warranty, see axis.com/warranty

- a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<http://www.openssl.org/>), and cryptographic software written by Eric Young (ey@cryptsoft.com).*

Environmental responsibility:

axis.com/environmental-responsibility