

## AXIS Q6055-S PTZ Network Camera

Outdoor-ready, stainless steel PTZ with HDTV 1080p and Zipstream

AXIS Q6055-S is a pressurized, marine-grade stainless steel PTZ camera with HDTV 1080p and 32x optical zoom. Fast and precise pan/tilt for wide area coverage and detailed surveillance at great distances. The high light sensitivity and day/night functionality ensure high image quality even in low-light conditions, while Axis Zipstream technology reduces bandwidth and storage requirements. The stainless steel casing gives high resistance to corrosion, cleaning chemicals and high-pressure steam. The casing can be filled with nitrogen to prevent internal condensation and create a non-flammable environment. The media converter switch enables daisy chain installation using standard network or fiber optic cables.

- > [Marine-grade stainless steel casing for pressurized nitrogen](#)
- > [HDTV 1080p and 32x optical zoom](#)
- > [SFP slots for fiber, RJ45 connections](#)
- > [I/O for alarm in/out](#)
- > [Axis Zipstream](#)



# AXIS Q6055-S PTZ Network Camera

|  |   |  |
|--|---|--|
| <b>Models</b>                            | AXIS Q6055-S 60 Hz<br>AXIS Q6055-S 50 Hz  | Notification via email, HTTP, HTTPS and TCP<br>External output activation  |
| <b>Camera</b>                            |   | <b>Data streaming</b> Event data   |
| <b>Image sensor</b>                      | 1/2.8" progressive scan CMOS  | <b>Built-in installation aids</b> Pixel counter  |
| <b>Lens</b>                              | 4.44–142.6 mm, F1.6–4.41<br>Horizontal field of view: 62.8°–2.23°<br>Vertical field of view: 36.8°–1.3°<br>Autofocus, auto-iris   | <b>Analytics</b>   |
| <b>Day and night</b>                     | Automatically removable infrared-cut filter   | <b>Applications</b> Included<br>AXIS Video Motion Detection, Autotracking, Active Gatekeeper, AXIS Fence Guard, AXIS Motion Guard<br>Basic Analytics (not to be compared with third-party analytics): object removed, enter/exit detector, fence detector, object counter<br>Highlight compensation<br>Supported<br>Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://www.axis.com/acap">www.axis.com/acap</a>   |
| <b>Minimum illumination</b>              | Color: 0.3 lux at 30 IRE F1.6<br>B/W: 0.03 lux at 30 IRE F1.6<br>Color: 0.5 lux at 50 IRE F1.6<br>B/W: 0.04 lux at 50 IRE F1.6  | <b>General</b>   |
| <b>Shutter speed</b>                     | 1/33000 s to 1/3 s with 50 Hz<br>1/33000 s to 1/4 s with 60 Hz  | <b>Casing</b> IP6K9K-, IP66-, IP67-, NEMA 4X-, NEMA 6P and IK10-rated <sup>b</sup><br>Stainless steel casing (V4A, SAE 316L/UNS S31603/EN 1.4432), nylon clear dome  |
| <b>Pan/Tilt/Zoom</b>                     | Pan: 360° endless, 0.05° - 450°/s<br>Tilt: 220°, 0.05°-450°/s<br>32x optical zoom and 12x digital zoom, total 384x zoom<br>E-flip, 256 preset positions, Tour recording, Guard tour, Control queue, On-screen directional indicator, Set new pan 0°, Adjustable zoom speed  | <b>Memory</b> 512 MB RAM, 256 MB Flash   |
| <b>Video</b>                             |   | <b>Power</b> Camera consumption: min 65 W<br>Min required power supply: 24 V DC, 3.2 A (75 W)<br>Recommended power supply: AXIS T8008 PS24   |
| <b>Video compression</b>                 | H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles<br>Motion JPEG  | <b>Connectors</b> IP66-rated multiconnector for DC power, RJ45<br>10BASE-T/100BASE-TX and I/O, including 7 m (23 ft) cable   |
| <b>Resolution</b>                        | HDTV 1080p 1920x1080 to 320x180<br>HDTV 720p 1280x720 to 320x180  | <b>Storage</b> Support for SD/SDHC/SDXC card<br>Support for SD card encryption<br>Support for recording to network-attached storage (NAS)<br>For SD card and NAS recommendations see <a href="http://www.axis.com">www.axis.com</a>  |
| <b>Frame rate</b>                        | Up to 50/60 fps (50/60 Hz) in HDTV 720p<br>Up to 25/30 fps (50/60 Hz) in HDTV 1080p   | <b>Operating conditions</b> -30 °C to 50 °C (-22 °F to 122 °F)<br>Maximum temperature (intermittent): 60 °C (140 °F)<br>Humidity 10–100% RH (condensing)   |
| <b>Video streaming</b>                   | Multiple, individually configurable streams in H.264 and Motion JPEG<br>Axis Zipstream technology<br>Controllable frame rate and bandwidth<br>VBR/MBR H.264   | <b>Storage conditions</b> -40 °C to 65 °C (-40 °F to 149 °F)   |
| <b>Image settings</b>                    | Manual shutter time, compression, color, brightness, sharpness, white balance, exposure control, exposure zones, fine tuning of behavior at low light, rotation: 0°, 180°, text and image overlay, 32 individual 3D privacy masks, image freeze on PTZ, automatic defog, backlight compensation<br>Wide Dynamic Range (WDR): Up to 120 dB depending on scene, highlight compensation                        | <b>Approvals</b> EMC<br>EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, EN 55024, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KCC KN32 Class A, KN35<br>Safety<br>IEC/EN/UL 60950-1<br>IEC/EN/UL 60950-22<br>Environment<br>EN 50121-4, IEC 62236-4, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, NEMA 250 Type 4X<br>IEC/EN 60529 IP66, IP67, IP6K9K, NEMA 250 Type 6P, MIL-STD 810G 509.5<br>Network<br>NIST SP500-267 |
| <b>Network</b>                           |   | <b>Weight</b> 6.0 kg ( 13 lb)  |
| <b>Security</b>                          | Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1X <sup>a</sup> network access control, Digest authentication, User access log, Centralized Certificate Management, Brute force delay protection   | <b>Dimensions</b> Ø224 x 256 mm (Ø8 13/16 x 10 1/16 in)  |
| <b>Supported protocols</b>               | IPv4, IPv6 USGv6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP <sup>TM</sup> , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, NTCIP, LLDP   | <b>Included accessories</b> AXIS T8607 Media Converter Switch, 7 m (23 ft) IP66-rated multicable<br>Installation Guide, Windows decoder 1-user license   |
| <b>System integration</b>                |   | <b>Optional accessories</b> AXIS T8008 PS24, AXIS T94A02D Pendant Kit, AXIS T91K61 Wall Mount, AXIS Q60-S Smoked Dome<br>AXIS T91 Mounting Accessories, AXIS T8415 Wireless Installation Tool, AXIS T90 Illuminators, AXIS T8310 Video Surveillance Control Board, multi-user decoder license pack   |
| <b>Application Programming Interface</b> | Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="http://www.axis.com">www.axis.com</a><br>AXIS Video Hosting System (AVHS) with One-Click Connection<br>ONVIF <sup>®</sup> Profile S and ONVIF <sup>®</sup> Profile G, specification at <a href="http://onvif.org">onvif.org</a>  | <b>Video management software</b> AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on <a href="http://www.axis.com/vms">www.axis.com/vms</a>  |
| <b>Event triggers</b>                    | Detectors: live stream accessed, video motion detection, shock detection<br>Object removed, enter/exit detector, fence detector, object counter<br>Hardware: fan, network, temperature<br>PTZ: autotracking, error, moving, ready, preset reached<br>Storage: disruption, recording<br>System: system ready<br>Time: recurrence, use schedule<br>Input signal: manual trigger, virtual input, digital input | <b>Languages</b> English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese   |
| <b>Event actions</b>                     | Day/night mode, overlay text, video recording to edge storage, pre- and post-alarm video buffering, send SNMP trap<br>PTZ: PTZ preset, start/stop guard tour<br>File upload via FTP, SFTP, HTTP, HTTPS network share and email  |  |

**Warranty** Axis 3-year warranty and AXIS Extended Warranty option, see [www.axis.com/warranty](http://www.axis.com/warranty)

b. *Except valves on top.*

a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. ([www.openssl.org](http://www.openssl.org)), and cryptographic software written by Eric Young ([ey@cryptsoft.com](mailto:ey@cryptsoft.com)).*

## AXIS T8607 Media Converter Switch

| General                       |   |
|-------------------------------|---|
| <b>Casing</b>                 | Metal<br>Color: White NCS S 1002-B  |
| <b>Power</b>                  | 24 V DC, max 4 W (power supply not included)  |
| <b>Connectors</b>             | 2x RJ45 connectors (10/100 Mbps) (Use shielded cables (STP) CAT5 or higher.)<br>2x SFP connectors (100/1000 Mbps) for SFP fiber optic modules or SFP to copper modules<br>1x power<br>2x configurable alarm input/output ports<br>Camera multicable |
| <b>Display and indicators</b> | Power LED indicator<br>Camera network LED indicator<br>Network LED indicator (4x)   |
| <b>Compliance</b>             | RoHS, REACH, WEEE, CE, EN 50022, IEC 60715, AS 2756   |
| <b>Mounting</b>               | DIN Rail mount  |
| <b>Environment</b>            | Indoor/Cabinet  |
| <b>Operating conditions</b>   | -40 °C to 75 °C (-40 °F to 167 °F)<br>Humidity 10-85% RH (non-condensing)   |
| <b>Storage conditions</b>     | -40 °C to 75 °C (-40 °F to 167 °F)<br>Humidity 10-85% RH (non-condensing)   |
| <b>Approvals</b>              | EMC<br>EN 55022 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, EN 55024, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 22, KCC KN22 Class A, KN24<br>Safety<br>IEC/EN 60950-1                   |
| <b>Dimensions</b>             | 150 x 100 x 30 mm (5 15/16 x 3 15/16 x 1 3/16 in)   |
| <b>Weight</b>                 | 284 g (0.63 lb)   |
| <b>Included accessories</b>   | Bracket Mount DIN Clip  |
| <b>Warranty</b>               | 3-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a>   |

Environmental responsibility:

[axis.com/environmental-responsibility](http://axis.com/environmental-responsibility)