

AXIS Live Privacy Shield

Versatile dynamic privacy masking

AXIS Live Privacy Shield makes it easy to remotely monitor activities while safeguarding privacy. It supports two different methods for real-time dynamic privacy masking. All compatible cameras can use the motion-based functionality to mask all moving objects as compared with the background scene. This functionality supports strict privacy requirements and is suitable for indoor scenes with good, stable lighting. Compatible DLPU cameras can additionally use the application's Al-based human recognition functionality to mask humans or the background in indoor or outdoor scenes in all lighting conditions. Both masking methods support "exclude" zones, and color or mosaic masking.

- > Safeguards privacy
- > Real-time, edge-based dynamic masking
- > Motion-based masking
- > AI-based masking for select deep-learning (DLPU) cameras
- > Free download









T10133920/EN/M7.3/2109 www.axis.com

AXIS Live Privacy Shield

General	
Typical use cases	Monitoring activities while safeguarding privacy by use of real-time dynamic privacy masking. Motion-based method for indoor scenes with good, stable lighting and need of strict privacy protection. Al-based method for masking humans, or the background, in indoor or outdoor scenes in places like manufacturing facilities, hospitals, elderly care homes, schools, hotels, offices and stores.
Supported devices	Available for free download for all compatible cameras. Motion-based method: All compatible cameras. Al-based method: Selected deep-learning (DLPU ^a) cameras. For a complete list of recommended and supported cameras, go to axis.com
Compute platform	Edge
Configuration	Through web browser: Chrome™ or Firefox®
Languages	English

Capabilities	
Image settings	Motion-based or Al-based method Color or mosaic masking Polygon include and exclude zones Al-based method: Masking of humans or background
Frame rate	Motion-based method: Up to full frame rate Al-based method: 10 fps
Limitations	Motion-based method: Limited to indoor environments with good, stable lighting. Scenes with reflective surfaces are not recommended. Al-based method: People partially blocked from view by, for example, a pole may not be masked. Also in the parts of a scene where the pixel density is less than 100 pixels/meter (30 pixels/foot) there is a risk that a person may not be completely masked.
System integration	
A 1: 4:	March 1 P. 11 D. C. Lie L.

Application Programming Interface

Multiple, individually configurable masked streams and maximum one unmasked stream can be fetched from the camera via VAPIX® API. The application can be enabled and disabled via VAPIX® API. Support for Axis Camera Application Platform. Specifications at *axis.com*

a. DLPU = deep learning processing unit

Environmental responsibility: axis.com/environmental-responsibility

