AXIS TU6004-E Cable

Flexible indoor/outdoor cable for long-distance installations

This robust, flexible AXIS F-series cable is compatible with all AXIS F91 main units and AXIS F21, F41, and F72 sensor units. With a bending radius of 40 mm (1.6 in), it's available in four lengths, up to 30 m (98 ft). To cut and terminate the cable to a custom length, use the AXIS TU6003 Connector Kit FAKRA.

- > Indoor and outdoor rated
- > 40 mm (1.6 in) bending radius
- > IP66-, IP67-, IP6K9K-rated on the SMA and sensor-unit sides
- > 8 m (26 ft) cables are sold in pack of 1 and 4



AXIS TU6004-E Cable

General

Casing
IP66-, IP67- and IP6K9K-rated

Power
Impedance: 50 Ohms

Frequency
0–3 GHz

Connectors
SMA
FAKRA

Operating conditions
-40 °C to 75 °C (-40 °F to 167 °F)
Humidity 10–100% RH (condensing)

Approvals
UL CL2 Sunlight Resistant E335585-T, UN ECE R118

Dimensions
Color: black
Length: 1 m (3 ft), 8 m (26 ft), 20 m (66 ft), and 30 m (98 ft)
ø 5 mm ±0.1 mm (0.2 in)
Maximum length of interconnected cables: 30 m (98 ft)
Bend radius: 40 mm (1.6 in)

Weight
1 m (3 ft): 40 g (0.09 lb)
8 m (26 ft): 300 g (0.66 lb)
20 m (66 ft): 760 g (1.68 lb)
30 m (98 ft): 1140 g (2.51 lb)

Compatible products
AXIS F91 main units, AXIS F21 sensor units, AXIS F41 sensor units, AXIS F72 sensor units

Optional accessories
AXIS TU6003 Connector Kit FAKRA

Warranty
3-year warranty, see *axis.com/warranty*

© 2023 – 2026 Axis Communications AB. AXIS COMMUNICATIONS, AXIS, ARTPEC and VAPIX are registered trademarks of Axis AB in various jurisdictions. All other trademarks are the property of their respective owners. We reserve the right to introduce modifications without notice.