AXIS TU6007-E Cable

Flexible indoor/outdoor cable for compact installations

This robust, flexible AXIS F Series cable is compatible with all AXIS F91 main units and AXIS F21, F41, and F72 sensor units. With a bending radius of 30 mm (1.2 in), it's available in two lengths, up to 8 m (26 ft).

- > Indoor and outdoor rated
- > 30 mm (1.2 in) bending radius
- > IP66- and IP67-rated on the SMA and sensor-unit side
- > 1 m (3 ft), 8 m (26 ft)





AXIS TU6007-E Cable

General

Environment
SMA connector: IP66- and IP67-rated

Power
Impedance: 50 Ohms

Frequency
0–3 GHz

Connectors
SMA
FAKRA

Operating conditions
-40 °C to 75 °C (-40 °F to 167 °F)
Humidity 10-100% RH (condensing)

Approvals
UL CM E164469-F5, UN ECE R118

Dimensions
Color: black
Length: 1 m (3 ft) and 8 m (26 ft)
ø 3 mm ±0.2 mm (0.1 in)
Bend radius: 30 mm (1.2 in)

Weight
1 m (3 ft): 22 g (0.05 lb)
8 m (26 ft): 124 g (0.27 lb)

Compatible products
AXIS F91 main units, AXIS F21 sensor units, AXIS F41 sensor units, AXIS F72 sensor units

Warranty
3-year warranty, see *axis.com/warranty*

© 2023 – 2026 Axis Communications AB. AXIS COMMUNICATIONS, AXIS, ARTPEC and VAPIX are registered trademarks of Axis AB in various jurisdictions. All other trademarks are the property of their respective owners. We reserve the right to introduce modifications without notice.