

AXIS TQ6907-E I/O LED Indicator

Add LED indicators to Axis PTZ cameras

Designed for use with Axis PTZ cameras, this high-durable LED ring can be used to deter, warn, or notify– for example, a green light to signal active recording. Powered and controlled by the camera's I/O ports (if available) or AXIS TU8003 90 W Connectivity Midspan, it offers three customizable RGB color options. These steady lights have a viewable distance of 100 m (328 ft) in pitch darkness. Designed for outdoor pendant installations on ceilings, walls, or poles, this circular accessory is easy to mount.

- > **Circular ring accessory**
- > **For mounting on Axis PTZ cameras**
- > **Three customizable steady RGB colors**
- > **Signal camera-triggered events**
- > **Sold in packs of four**



AXIS TQ6907-E I/O LED Indicator

Light

Illumination LED

Red, green, blue LEDs

Red: >14 lm, green: >55 lm, blue: >10 lm

Approvals

Environment

IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6,
IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-30,
IEC 60068-2-78, IEC/EN 60529 IP66, IEC/EN 62262
IK08

Power

DC input

12 VDC (Powered by device via I/O connector),
max 0.6 W

General

Supported products

Midspan

AXIS TU8003 90 W Connectivity Midspan

Camera

AXIS P5654-E Mk II

AXIS P5655-E

AXIS P5676-LE

AXIS Q6020-E

AXIS Q6086-E

AXIS Q6088-E

AXIS Q6300-E

AXIS Q6325-LE

AXIS Q6355-LE

AXIS Q6358-LE

AXIS Q6411-LE

AXIS Q6411-LE Kit

For a complete list of compatible devices, go to axis.com/products/axis-tq6907-e-io-led-indicator#compatible-products

Casing

IP66- and IK08-rated

Plastic casing

Color: white NCS S 1002-B

Mounting

To be mounted between the bracket and camera

Connectors

I/O: 6-pin 2.5 mm terminal block

Operating conditions

Temperature: -35 °C to 55 °C (-31 °F to 131 °F)

Start-up temperature: -35 °C (-31 °F)

Humidity: 0–70% RH (non-condensing)

Storage conditions

Temperature: -35 °C to 70 °C (-31 °F to 158 °F)

Dimensions

For the overall product dimensions, see the dimension drawing in this datasheet.

Effective Projected Area (EPA): 0.0032 m² (0.034 ft²)

Weight

860 g (1.9 lb)

Box content

LED rings, installation guide, screw gaskets

Warranty

3-year warranty, see axis.com/warranty

Part numbers

Available at axis.com/products/axis-tq6907-e-io-led-indicator#part-numbers

Optional accessories

Mounting

AXIS T91G61 Wall Mount⁽¹⁾, AXIS T91G61 Wall Mount Grey⁽¹⁾, AXIS TQ5301-E Corner Mount

Sustainability

Substance control

PVC free

RoHS in accordance with EU RoHS Directive 2011/65/

EU and 2015/863, and standard EN IEC 63000:2018

REACH in accordance with (EC) No 1907/2006. For SCIP
UUID, see echa.europa.eu

1. Requires additional accessory

Materials

Renewable carbon-based plastic content: 71% (bio-based)

To read more about how we calculate the percentage of renewable carbon-based plastic, go to axis.com/about-axis/sustainability/eco-design

Screened for conflict minerals in accordance with OECD guidelines

To read more about sustainability at Axis, go to axis.com/about-axis/sustainability

Environmental responsibility

axis.com/environmental-responsibility

Axis Communications is a signatory of the UN Global Compact, read more at unglobalcompact.org

