

AXIS Q6135-LE PTZ Network Camera

High-speed PTZ with long-range optimizedIR

AXIS Q6135-LE offers HDTV 1080p with 32x optical zoom. It features OptimizedIR up to 250 m (820 ft) or more depending on the scene and Lightfinder 2.0 for clear, sharp images even in challenging light. Sharpdome technology allows you to see 20° above the horizon with the same sharp image quality as below. It includes orientation aid and autotracking 2 with click and track functionality. Privacy masking with mosaic lets you pixelate whole areas of the scene. It includes enhanced security features such as signed firmware, secure boot and TPM module. Plus, Axis Zipstream with support for H.264 and H.265.

- > **HDTV 1080p with 32x optical zoom**
- > **OptimizedIR (250 m/820 ft range)**
- > **Lightfinder 2.0**
- > **Autotracking 2 and orientationaid**
- > **TPM, FIPS 140-2 level2 certified**



AXIS Q6135-LE PTZ Network Camera

| | | |
|-----------------------------------|--|---|
| Models | AXIS Q6135-LE 50 Hz AXIS Q6135-LE 60 Hz | Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share, and email Notification: email, HTTP, HTTPS, TCP, and SNMP trap PTZ: PTZ preset, guard tour Overlay text, day/night mode WDR mode IR illumination |
| Camera | | |
| Image sensor | 1/2.8" Progressive scan CMOS | |
| Lens | Varifocal, 4.3–137.6 mm, F1.4 – 4.0 Horizontal field of view: 58.3°–2.4° Vertical field of view: 34.9°–1.3° Autofocus, auto-iris | |
| Day and night | Automatically removable infrared-cut filter | |
| Minimum illumination | Color: 0.06 lux at 30 IRE F1.4 B/W: 0.008 lux at 30 IRE F1.4, 0 lux with IR illumination on Color: 0.09 lux at 50 IRE F1.4 B/W: 0.01 lux at 50 IRE F1.4, 0 lux with IR illumination on Color: 0.04* lux at 30 IRE F.4 B/W: 0.004* lux at 30 IRE F.4, 0 lux with IR illumination on * using different shutter speed and gain | |
| Shutter speed | 1/66500 s to 2s | |
| Pan/Tilt/Zoom | Pan: 360° endless, 0.05°–700°/s Tilt: +20 to -90°, 0.05°–500°/s Zoom: 32x optical, 12x digital, total 384x zoom Nadir flip, 256 preset positions, tour recording, guard tour, control queue, on-screen directional indicator, orientation aid PTZ, set new pan 0°, adjustable zoom speed, speed dry | |
| Video | | |
| Video compression | H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG | |
| Resolution | 1920x1080p (HDTV 1080p) to 320x180 | |
| Frame rate | Up to 50/60 fps (50/60 Hz) in 1080p | |
| Video streaming | Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 | |
| Image settings | Compression, saturation, brightness, sharpness, contrast, local contrast, white balance, exposure control, exposure zones, Forensic WDR: Up to 120 dB depending on scene, defogging, day/night shift level, tone mapping, fine tuning of low-light behavior, rotation: 0°, 180°, text and image overlay, image freeze on PTZ, electronic image stabilization (EIS), scene profiles, 32 individual polygon privacy masks | |
| Network | | |
| Security | Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1x (EAP-TLS) ^a network access control, Digest authentication, User access log, Centralized Certificate Management, Brute force delay protection, signed firmware, secure boot, protection of cryptographic keys with FIPS 140-2 certified TPM 2.0 module | |
| Supported protocols | IPv4, IPv6 USGv6, HTTP, HTTPS ^a , HTTP/2, SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCPv4/v6, ARP, SOCKS, SSH, NTPCIP, LLDP, MQTT v3.1.1, Syslog | |
| System integration | | |
| Application Programming Interface | Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF® Profile G, ONVIF® Profile S, and ONVIF® Profile T, specification at onvif.org | |
| Event conditions | Analytics Device status: above operating temperature, above or below operating temperature, below operating temperature, fan failure, IP address removed, network lost, new IP address, shock detected, storage failure, system ready, within operating temperature Edge storage: recording ongoing, storage disruption I/O: manual trigger, virtual input PTZ: PTZ malfunctioning, PTZ movement, PTZ preset position reached, PTZ ready, PTZ autotracking Scheduled and recurring: scheduled event Video: live stream open, day/night mode | |
| Event actions | Record video: SD card and network share Pre- and post-alarm video or image buffering for recording or upload | |
| Data streaming | Event data | |
| Built-in installation aids | Pixel counter, leveling guide | |
| Analytics | | |
| Compute capabilities | Machine learning processing unit (MLPU) | |
| AXIS Object Analytics | Object classes: humans, vehicles Trigger conditions: line crossing, object in area Up to 10 scenarios Metadata visualized with color-coded bounding boxes Polygon include/exclude areas Perspective configuration ONVIF Motion Alarm event | |
| Applications | Included AXIS Object Analytics AXIS Fence Guard, AXIS Motion Guard, AXIS Loitering Guard AXIS Video Motion Detection, Autotracking 2, Active Gatekeeper Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap | |
| General | | |
| Casing | IK08, IK10 housing and mounting ^b , IP66- and NEMA 4X-rated Repaintable metal casing (aluminum), hard coated Polycarbonate (PC) clear dome with Sharpdome technology | |
| Sustainability | PVC free | |
| Memory | 1024 MB RAM, 512 MB Flash | |
| Power | Axis High PoE midspan 1-port: 100–240 V AC, max 74 W Camera consumption: typical 13.5 W (no IR), max 51 W Axis PoE+ midspan 1-port: 100–240 V AC, max 37 W IEEE 802.3at Type 2 Class 4 Camera consumption: typical 13.5 W, max 25 W | |
| Connectors | RJ45 10BASE-T/100BASE-TX PoE RJ45 Push-pull Connector (IP66) | |
| IR illumination | Optimized IR with power-efficient, long life 850 nm IR LEDs With 30 W midspan: Range of reach 190 m (623 ft) or more depending on the scene With 60 W midspan: Range of reach 250 m (820 ft) or more depending on the scene | |
| Storage | Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com | |
| Operating conditions | With 30 W midspan: -30 °C to 50 °C (-22 °F to 122 °F) With 60 W midspan: -50 °C to 50 °C (-58 °F to 122 °F) Maximum temperature according to NEMA TS 2 (2.2.7): 74 °C (165 °F) Arctic Temperature Control: Start-up as low as -40 °C (-40 °F) Humidity 10–100% RH (condensing) | |
| Storage conditions | -40 °C to 70 °C (-40 °F to 158 °F) Humidity 5-95% RH (non-condensing) | |
| Approvals | EMC EN 55032 Class A, EN 55035, EN 55024, EN 50121-4, IEC 62236-4, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), VCCI Class A, RCM AS/NZSCISPR32 Class A KC KN32 Class A, KN35 Safety IEC/EN/UL 62368-1, IEC/EN/UL 60950-22, IEC/EN 62471 risk group 2, IS13252 Environment IEC/EN 62262 IK08, IEC/EN 60529 IP66, NEMA 250, Type 4X, NEMA TS 2 (2.2.7–2.2.9), IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-30, IEC 60068-2-78, ISO4892-2 Network NIST SP500-267 | |

| | |
|----------------------------------|---|
| | For midspan approvals, see: axis.com/products/axis-t8154-60-w-sfp-midspan |
| Dimensions | Height: 241 mm (9.5 in) ø 165 mm (6.4 in) |
| Weight | 3 kg (6.6 lb) |
| Included accessories | IP66-rated RJ45 connector kit, AXIS High PoE 60 W SFP Midspan, installation guide, Windows decoder 1-user licence |
| Optional accessories | AXIS T91/T94 Mounting Accessories, Axis High PoE midspans For more accessories, see axis.com |
| Video management software | AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available on www.axis.com/vms |

| | |
|------------------|---|
| Languages | English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese |
| Warranty | 5-year warranty, see axis.com/warranty |

- a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).*
b. *Mounting not included*

Environmental responsibility:

axis.com/environmental-responsibility