

AXIS A4010-E Reader

Generic touch-free reader

AXIS A4010-E Reader without Keypad is a joint cooperation between Axis and ASSA Abloy designed to perfectly match AXIS A1001 Network Door Controller. The cost-efficient reader has no keypad and its small form factor enables easy placement. Two LED symbols give clearly visible feedback. The reader supports touch-free entry with most entry card formats, and is suitable for both indoor and outdoor installation. IP65 classification makes it ready for harsh environments.

- > **Designed to perfectly match AXIS A1001**
- > **Support for most smart card formats**
- > **2 LED symbols give clearly visible feedback**
- > **Indoor and outdoor ready**
- > **IP65 classified**



AXIS A4010-E Reader

Compatible products AXIS A1001 Network Door Controller, AXIS A1601 Network Door Controller

Indications and user interface

Entry authentication Card, Tag

Read range 30–40 mm with recommended cards and tags

Alarm status indication Symbols for: Access granted, Access denied

General

Casing ABS and halogen free halon plastic

Reader technology Generic 13,56 MHz (MIFARE Classic, MIFARE Plus (Level 1 and 3), MIFARE DESFire EV1, iCLASS® CSN and iCLASS® SEOS™^a)

Communication RS-485 – OSDP

Power 12–24V DC
max 2.8 W
Translates to 240 mA@12V

Operating conditions -30 °C to 70 °C (-34 °F to 158 °F)

Storage conditions -50 °C to 70 °C (-58 °F to 158 °F)

Approvals EN/IEC 61000-6-2, EN/IEC 61000-6-3, EN 55024, EN 50130-4, CFR part 15 Subpart C, AS/NZS 4268, RSS-GEN, RSS-210, EN 50581, EN/IEC 60950-22, ETSI EN 300 330-1, ETSI EN 300 330-2, UL294

Dimensions 85 x 46 x 19 mm (3.35 x 1.8 x 0.75 in)
Cable length: 3 m

Weight 128 g (0.28 lb)

Warranty 3-year warranty, see axis.com/warranty

a. Extra configuration card needed, sold separately.

Environmental responsibility:

axis.com/environmental-responsibility

