

## AXIS A9188-VE Network I/O Relay Module

Intelligent module with supervised inputs

AXIS A9188-VE Network I/O Relay Module comes with AXIS T98A15-VE Surveillance Cabinet making it outdoor-ready, vandal-resistant, and UL294-approved. With its 8 configurable I/Os and relays, the module is optimized for floor access management. Its open platform enables a high level of integration with AXIS A1001 Network Door Controller and other facility systems. It also works standalone. AXIS A9188-VE reacts on inputs, such as signals from PIR motion detectors or switches, to trigger actions. Supplying power to I/O devices, it can extend the functionality of Axis products where additional I/Os or relays are needed.

- > **8 I/Os with supervised inputs and 8 form C relays**
- > **UL294-approved with cabinet AXIS T98A15-VE Surveillance Cabinet**
- > **12 and 24 V DC output/input or PoE+**
- > **Open API, support for VAPIX, ACAP**
- > **Used with AXIS Camera station or third-party software**



# AXIS A9188-VE Network I/O Relay Module

I/O interface		Power	
Digital I/O	8x I/O, configurable as input, supervised input with analog read-out or output (Digital input: 0 to max 40 V DC, possible to supervise between 0-12 V (4 states), Digital output: 0 to max 40 V DC, Open drain, max 100 mA)	Power in:	8-28 V DC, max 26 W or Power over Ethernet IEEE 802.3af Type 1 Class 3 or IEEE 802.3at Type 2 Class 4
Relays	8x Form C relays, NO/NC contacts, max 1 A, 48 V DC, (max 30 V DC outdoors)	Power out:	12 V DC and 24 V DC Max power out shared between 12 V and 24 V outputs: PoE Class 3: 3.6 W PoE Class 4/DC input: 12 W
Network		Connectors	
Security	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1X network access control, digest authentication	Connectors	1x RJ45 10BASE-T/100BASE-TX terminal blocks: 1x DC IN, 2x DC out, 8x Inputs/Outputs, 8x relays, 1x tamper, 1x RS485 (for future use), cable size for connectors: CSA: AWG 28-16, CUL/UL: AWG 30-14
Supported protocols	IPv4, IPv6, HTTP, HTTPS <sup>a</sup> , TLS <sup>a</sup> , QoS layer 3 DiffServ, FTP, SFTP, SMTP, Bonjour, UPnP <sup>TM</sup> , SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCP, ARP, SOCKS	Operating conditions	
System integration		Operating conditions	-30 °C to 55 °C (-22 °F to 131 °F) <sup>b</sup> Humidity 20-85% RH (non-condensing)
Application Programming Interface	Open API for software integration, including VAPIX <sup>®</sup> , specifications at <a href="http://axis.com">axis.com</a>	Approvals	
Events & alarms		Approvals	EN 55022 Class B, EN 50130-4, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, ICES-003 Class B, C-tick AS/NZS CISPR22 Class B, VCCI Class B, IEC/EN/UL 60950-1, UL 294, UL 2043, EN 50581
Tamper detection	Dedicated tamper input for external tamper contact(s)	Dimensions	
Event history	30 000 First In, First Out (FIFO)	Dimensions	361 x 282 x 131 mm (14.2 x 11.1 x 5.2 in)
Event actions	Notification via email, HTTP, HTTPS and TCP, external output port Status LED	Weight	
Event triggers	Tamper detection, network lost, configuration, event logger, hardware, input signal, schedule, system, time, supervised inputs (4 states), relays and outputs, heartbeat lost	Weight	5000 g (11.0 lb)
General		Included accessories	
Sustainability	PVC free	Included accessories	Connector kit, jumper kit, TORX <sup>®</sup> Key TR20, Installation guide
Software	Configuration and basic management through Internet Explorer <sup>®</sup> , Firefox <sup>®</sup> , Chrome <sup>™</sup> , or Safari <sup>®</sup>	Optional accessories	
Memory	256 MB RAM, 256 MB Flash	Optional accessories	AXIS T8133 Midspan 30 W, AXIS T8129 PoE Extender Power supply AXIS T8007 PS24
		Languages	
		Languages	English, French, Italian, German, Spanish
		Warranty	
		Warranty	5-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a>

- a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<http://www.openssl.org/>), and cryptographic software written by Eric Young ([ey@cryptsoft.com](mailto:ey@cryptsoft.com)).
- b. Outdoor installation requires AXIS T98A15-VE Surveillance Cabinet

Environmental responsibility:

[axis.com/environmental-responsibility](http://axis.com/environmental-responsibility)