

AXIS Camera Management

Efficient management of Axis network products

AXIS Camera Management is a powerful application for efficient management of all connected Axis devices, also across multiple sites. The software automatically locates Axis devices on the local network and enables the user to configure network settings and other parameters. Configurations can be copied and restored, or used as a template to quickly configure large amounts of devices. Firmware upgrades and ACAP application installations can be performed as batch operations. AXIS Camera Management has an intuitive user interface. User-defined tags make it easy for example to group cameras by location or list cameras scheduled for firmware upgrade.

- > Fast configuration of new devices
- > Easy backup and restoring of settings
- > Efficient installation of firmware upgrades and applications
- > Support for multi-site management



Technical Specifications - AXIS Camera Management

Compatible products		Camera manageme	
Models	Axis network cameras and encoders including HD, standard resolution, high resolution, Pan Tilt Zoom and thermal cameras with firmware 4.40 or later. Axis physical access control products, Axis network speakers, Axis network switch Note: AXIS Companion Line products can only be used with AXIS Companion video management system.	Firmware upgrade	Upg Aut
		Application management	Sup Inst mu
Camera mana	gement		
Finding new	Discovery of new devices on the network, within the local subnet or on		
devices	remote networks		Act cha
Device tagging	User-defined tags		
		Languages	Eng (Tra (Bra
Unit status	Device status monitoring indicating accessible devices		
Device configuration	Save, copy and configure standard parameters including Action rules, Stream profiles, Device time, Device users and IP settings to several devices, Backup and restore of camera settings	Minimum system requirements	Inte RAI Ope
Device management	Restore to factory default values or restart device	System recom- mendations	For
			Δlv

Camera management		
Firmware upgrade	Upgrade of multiple devices sequentially or in parallel Automatic download of latest available firmware from Axis	
Application management	Support for AXIS Camera Application Platform Installation of Axis-compatible applications including license files to multiple devices	
General		
Logging	Activity log with sort/search functions showing performed actions and changed device status	
Languages	English, French, German, Italian, Arabic, Czech, Chinese (Simplified), Chinese (Traditional), Dutch, Finnish, Japanese, Korean, Persian, Polish, Portuguese (Brazil), Russian, Spanish, Swedish, Thai, Turkish, Vietnamese	
Minimum system requirements	Intel i5 or equivalent AMD RAM: 2 GB (8 GB recommended for larger systems) Operating system: 64-bit operating system	
System recom- mendations	For a list of all supported operating systems, see the release notes available on www.axis.com/techsup Always use the latest service packs. Microsoft NFT runting environment (included in installation package)	

Efficient device management







Multiple site management

Firmware upgrade

Application distribution

