

AXIS Camera Station S1016 Mk II Recorder

Out-of-the box ready workstation for high-definition surveillance

AXIS Camera Station S1016 Recorder is an out-of-the-box ready workstation validated for reliable high-definition surveillance up to 4K. It is preloaded with AXIS Camera Station video management software with universal licenses for 16 channels and other necessary system software. It is preconfigured to minimize installation time. AXIS S1016 has validated hardware components and extendable storage capacity, and includes three-year hardware warranty with on-site replacement service. AXIS Camera Station offers an intuitive user interface and allows users to take full advantage of Axis' wide range of video surveillance cameras and other IP products. It also supports integration of third party IP cameras.

- > **Ease of installation**
- > **Validated with extensive support**
- > **High-definition surveillance up to 4K**
- > **AXIS Camera Station included**
- > **Full compatibility with Axis' products**



AXIS Camera Station S1016 Mk II Recorder

Licenses	16 AXIS Camera Station universal licenses included, can be upgraded up to 32 licenses (sold separately)	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Processor	Intel® i5 4570S, Quad Core, 2.90 GHz Turbo, 6MB	Approvals	EN/IEC/UL 60950-1, FCC part 15, class B, VCCI V-3, VCCI V-4, AS/NZS CISPR 22, class B, ICES-003/NMB-003, KCC KN22 Class B, KN-24, EN 62311, EN 55022, EN 55024, EN/IEC 61000-3-2, EN/IEC 61000-3-3, EN 300 328, EN 301 893, EN 301 489-1, EN 301 489-17
Memory	8GB (2x4GB) 1600 MHz DDR3	Dimensions	360 x 175 x 417 mm (14.17 x 6.89 x 16.42 in)
Storage	8 TB (2x4TB) Enterprise Class HDD, 7200 rpm, SATA 6Gb/s , no RAID. Possible to add 2 additional HDD ^a	Weight	9.5 kg (20.9 lb)
Graphic card	AMD Radeon R5 340X 2 GB 2 monitors supported	Included accessories	Installation guide, Keyboard (International/US), Computer mouse, Power cable
Operating system	Microsoft Windows 10 IoT Enterprise	Optional accessories	AXIS T8310 Video Surveillance Control Board AXIS P8221 I/O Audio Module AXIS A1001 Network Door Controller AXIS Camera Station S9001 Mk II Desktop Terminal AXIS Camera Station S9002 Desktop Terminal
Video streaming	Live view: Up to 25 camera split views or 1 x 4K camera view Playback: 4 x 1080p camera split views or 1 x 4K camera view	Warranty	Axis 3-year warranty, see www.axis.com/warranty
Recording	Qualified for recording up to 32 video channels with a total recording rate up to 256 Mbit per second.	<i>a. For more info www.axis.com/support</i>	
General			
Power	Max 365 W, 100 V AC to 240 V AC		
Connectors	6xUSB 2.0, 4xUSB 3.0, 1xDisplay Port, 1xDual link DVI-I Ethernet LAN 10/100/1000 Mbit, Line-in/out connectors, Computer mouse and keyboard connectors		
Operating conditions	5 °C to 45 °C (41 °F to 113°F)		

AXIS Camera Station

For details about AXIS Camera Station features and functions please see Data Sheet on www.axis.com

Environmental responsibility:
www.axis.com/environmental-responsibility