

AXIS Camera Station S1132 Recorder

Out-of-the box ready server for high-definition surveillance

AXIS Camera Station S1132 Recorder is an out-of-the-box ready rack server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1132 is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 32 channels plus all necessary software. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard disks and power supplies, operating system stored on solid-state drive (SSD), AXIS S1132 provides high-performance and reliability for your system.

- > [Ease of installation](#)
- > [AXIS Camera Station licenses included](#)
- > [Full compatibility with Axis products](#)
- > [3-year hardware warranty with on-site replacement service](#)



AXIS Camera Station S1132 Recorder

Licenses	32 AXIS Camera Station core licenses included, can be upgraded up to 48 licenses (sold separately)	Operating conditions	10 °C to 35 °C (50 °F to 95 °F) Humidity 20–80% RH (non-condensing)
Processor	Intel® Core™ i3	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Memory	8 GB	Approvals	EMC EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), RCM AS/NZS CISPR 32 Class A, VCCI Class A, KC KN 32 Class A, KC KN 35 Safety IEC/EN/UL 60950-1, NOM, BSMI, EAC
Storage	16 TB (4x4 TB) hot swappable Enterprise Class HDD, 7200 rpm 12 TB usable space after RAID Total HDD slots: 4	Dimensions	596 x 484 x 43 mm (23.47 x 19.06 x 1.7 in), 1U chassis
RAID	Factory RAID level: 5 RAID levels: 0, 1, 5, 6, 10	Weight	13.5 kg (29.7 lb)
Operating system	Microsoft® Windows® 10 IoT Enterprise SAC Built-in operating system recovery: yes Operating system drive: 240 GB SSD	Included accessories	Rack rails and power cords
Video streaming	Not intended for local viewing of video. Recommended to use AXIS desktop terminals.	Optional accessories	Axis desktop terminals For more accessories, see axis.com
Recording	Qualified for recording up to 48 video channels with a total recording rate up to 384 Mbit per second.	Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see axis.com/warranty
Power	Up to 2 x 350 W hot-plug redundant power supplies (100 - 240 V AC, 50/60 Hz, 4.8 - 2.4 A)		
Connectors	3x USB 2.0 2x Ethernet (RJ45) 1 GbE 1x VGA 1x Serial port		

Environmental responsibility:

axis.com/environmental-responsibility