

## AXIS Camera Station S2008 Appliance

All-in-one recorder with integrated switch for high-definition surveillance

AXIS Camera Station S2008 is an out-of-the-box ready compact surveillance appliance with an integrated manageable PoE switch. AXIS S2008 is validated for reliable high-definition surveillance up to 4K. It is preloaded with AXIS Camera Station video management software with Universal licenses for 8 channels and other necessary system software. It is preconfigured to minimize installation time. AXIS S2008 has validated hardware components and three-year hardware warranty. AXIS Camera Station offers an intuitive user interface and allows users to take full advantage of Axis' wide range of video surveillance cameras and other IP products. It also supports integration of third-party cameras.

- > **All-in-one solution with integrated PoE switch**
- > **Validated with extensive support**
- > **High-definition surveillance up to 4K**
- > **AXIS Camera Station included**
- > **Full compatibility with Axis' products**



## AXIS Camera Station S2008 Appliance

<b>Licenses</b>	8 AXIS Camera Station Universal licenses included.	<b>Connectors</b>	8x PoE ports RJ45 10/100 Mbps, 2x RJ45/SFP Uplinks 10/100/1000 Mbps, 2x USB 2.0, 2x USB 3.0, 1x VGA, 1x HDMI, 1x eSATA
<b>Processor</b>	Intel i3-4360, 3,7GHz, 4MB Cache, 2C/4T	<b>Operating conditions</b>	0 °C to 40 °C (32 °F to 104 °F)
<b>Memory</b>	UDIMM 8GB (2x4GB) 1600 MHz DDR3	<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F)
<b>Storage</b>	4 TB, (1x4 TB) Surveillance Class HDD 64 MB cache and SATA 6Gb/s.	<b>Approvals</b>	EN/IEC/UL 60950-1, FCC part 15 Class A, VCCI Class A, EN 55022 class A, ICES-3(A)/NMB-3(A), RCM AS/NZS CISPR 22 Class A, EN 55024, EN/IEC 61000-3-2, EN/IEC 61000-3-3
<b>Switch</b>	8 ports integrated, 140 W total power budget, Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 2 up to Class 4	<b>Dimensions</b>	325 x 238 x 44 mm (12.8 x 9.4 x 1.75 in)
<b>Graphic card</b>	Intel HD Graphics 4600	<b>Weight</b>	3.5 kg (7.7 lb)
<b>Operating system</b>	Microsoft Windows 10 IoT Enterprise	<b>Included accessories</b>	Mounting brackets, Installation guide, Power supply
<b>Video streaming</b>	<b>Live view:</b> Capable of 25 camera split views or 1 x 4K camera view. <b>Playback:</b> 4 x 1080p camera split views or 1 x 4K camera view. 2 screens supported.	<b>Optional accessories</b>	AXIS Camera Station S9001 Mk II Desktop Terminal AXIS Camera Station S9002 Desktop Terminal AXIS T8310 Video Surveillance Control Board AXIS P8221 I/O Audio Module AXIS A1001 Network Door Controller
<b>Recording</b>	Qualified for recording with a total recording rate of 128 Mbit per second.	<b>Warranty</b>	Axis 3-year warranty, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>
<b>General</b>			
<b>Power</b>	Max 280 W, 100 V AC to 240 V AC, 50/60 Hz with external power supply. 140 W PoE dedicated		

## AXIS Camera Station

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on [axis.com](http://axis.com)

Environmental responsibility:  
[axis.com/environmental-responsibility](http://axis.com/environmental-responsibility)