

AXIS Companion Eye mini L

Indoor full HD IR network camera

AXIS Companion Eye mini L is a small and discreet, indoor day/night camera with built-in IR illumination for surveillance in total darkness. The mini dome has a compact, flat-faced design that suppresses reflections, and WDR technology delivering high image quality even in scenes with complex light conditions. The camera features Power over Ethernet (PoE) that allows one cable to provide both network connectivity and electrical power. AXIS Companion Eye mini L is supported only by AXIS Companion video management software and mobile app, and requires an AXIS Companion Recorder for system completion.

- > **High video quality in HDTV 1080p and 2 MP resolution**
- > **Built-in IR illumination for surveillance in total darkness**
- > **WDR to handle scenes with complex light conditions**
- > **PoE for network connectivity and electrical power**
- > **Optimized for reduced bandwidth and storage need**



AXIS Companion Recorder is required and sold separately

AXIS Companion Eye mini L

Camera		Connectors	T/100BASE-TX PoE
Image sensor	1/2.8" progressive scan RGB CMOS	IR illumination	Power-efficient, long-life 850 nm IR LED. Range of reach up to 15 m (49 ft) depending on scene
Lens	Horizontal field of view: 103° Vertical field of view: 55° Fixed iris and IR corrected	Storage	AXIS Companion Recorder is required This camera does not support AXIS S3008 Recorder
Day and night	Automatically removable infrared-cut filter	Operating conditions	0 °C to 50 °C (32 °F to 122 °F) Humidity 10–85% RH (non-condensing)
Minimum illumination	0 lux with IR illumination on	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Camera angle adjustment	Pan: +/-177° Tilt: 30° to 90° Rotation: 0°, 90°, 180°, 270° Can be directed in any direction	Approvals	EMC EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, VCCI Class A, ICES-003 Class A, RCM AS/NZS CISPR 32 Class A Safety IEC/EN/UL 62368-1 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP42 Network NIST SP500-267
Video		Dimensions	Height: 58 mm (2 9/32 in) ø 86 mm (3 25/64 in)
Video compression	H.265 (MPEG-H Part 2)	Weight	120 g (0.26 lb)
Resolution	1920x1080 HDTV 1080p and 640x360	Included accessories	Installation guide
Frame rate	Up to 25/30 fps with power line frequency 50/60 Hz	Optional accessories	AXIS T8415 Wireless Installation Tool AXIS T94E01M J-Box/Gang Box Plate AXIS T94E01D Pendant Kit AXIS T91A27 Pole Mount For more accessories, see axis.com
Video streaming	Multiple, individually configurable streams Controllable frame rate	Video management software	AXIS Companion available on axiscompanion.com/vms
Image settings	Color, brightness, sharpness, contrast, white balance, exposure control, rotation: 0°, 90°, 180°, 270°, including Corridor Format, privacy masks	Warranty	Axis 3-year warranty, see axis.com/warranty
Wide dynamic range	WDR	a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).</i>	
Network		Environmental responsibility: axis.com/environmental-responsibility	
Security	Password protection, HTTPS ^a encryption, digest authentication, user access log, brute force delay protection, signed firmware		
Supported protocols	IPv4, IPv6 USGv6, HTTP, HTTPS ^a , SSL/TLS ^a , Bonjour, UPnP®, DNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP		
System integration			
Event triggers	Video motion detection		
General			
Casing	IP42, Plastic PC/ABS Color: white NCS S 1002-B For repainting instructions of casing and impact on warranty, contact your Axis partner.		
Sustainability	PVC free		
Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 1 Typical 2.1 W, max 3.2 W		