

AXIS F1004 Sensor Unit

Super small size and price for discreet surveillance

AXIS F1004 Sensor Unit is small in size and price. For use with an AXIS F Main Unit, AXIS F1004 offers a lower cost, highly discreet sensor unit for indoor surveillance applications. AXIS F1004, which comprises a fixed lens and image sensor, provides a 720p resolution and a 102° horizontal field of view. AXIS F1004 has a detachable 8-m (26 ft.) cable for connecting to a main unit. A flush ceiling/wall mount kit is included. Optional accessories include surface and recessed mounts that enable the sensor unit to be tilted, and a 15-m (49 ft.) cable for connecting AXIS F1004 to a main unit.

- > **Small size and price**
- > **102° horizontal field of view**
- > **HDTV 720p**
- > **Detachable cable for easy and flexible installation**



AXIS F1004 Sensor Unit

Camera		General	
Image sensor	1/4" (effective) progressive scan RGB CMOS	Casing	Zinc and plastic
Lens	Fixed iris 2.1 mm, F2.2 Horizontal angle of view: 102° Vertical angle of view: 56°	Operating conditions	-20 °C to 50 °C (-4 °F to 122 °F) Humidity 10–85% RH (non-condensing)
Resolution	Max 1280x720	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Wide dynamic range	WDR	Approvals	IEC/EN/UL 60950-1, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, EN 55024, EN 61000-6-1, EN 61000-6-2, EN 61000-3-2, EN 61000-3-3, EN 50581, EN 55022 Class B, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 22 Class B, KCC KN22 Class B, KN24
Minimum illumination	Color: 0.4 lux	Dimensions	37.5 mm (1 1/2 in) ø 16 mm (5/8 in)
Shutter time	1/24500 s to 1/6 s	Weight	96 g (0.21 lb)
Frame rate	Max 25/30 fps (50/60 Hz)	Required hardware	AXIS F Main Unit
		Included accessories	Installation Guide Flush mount kit for installation in wall or ceiling
		Optional accessories	AXIS F7315 Cable White 15 m AXIS F8214 Dome Accessory AXIS F8224 Recessed Mount AXIS F8204 Mounting band Mounting bracket for AXIS P1214/P1214-E/P1224-E
		Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty

Environmental responsibility:

www.axis.com/environmental-responsibility