

## AXIS FA1125 Sensor Unit

Extremely discreet indoor surveillance in 1080p

AXIS FA1125 is ideal for extremely discreet indoor surveillance applications in stores and banks, and when integrated in machines. It can be installed in tight places and flush-mounted in a wall, ceiling or metal panel with only a pinhole visible for the lens. For use with an AXIS FA Main Unit, AXIS FA1125 provides a 1080p resolution and a 91° horizontal field of view. AXIS FA1125 uses Forensic WDR (wide dynamic range) that is tuned for motion. The unit comes with a mounting bracket and an 8-m (26 ft.) cable for connection to a main unit.

- > **Flexible, extremely discreet design for indoor use**
- > **Pinhole lens with 1080p resolution**
- > **Wide 91° horizontal field of view**
- > **Forensic WDR**



## AXIS FA1125 Sensor Unit

Camera		General	
<b>Image sensor</b>	1/3" (effective) progressive scan RGB CMOS	<b>Casing</b>	Aluminum Plastic
<b>Lens</b>	Fixed iris, fixed focus, pinhole 3.7 mm, F2.5 Horizontal field of view: 91° Vertical field of view: 45°	<b>Sustainability</b>	PVC free
<b>Resolution</b>	1920x1080 (1080p)	<b>Operating conditions</b>	-20 °C to 50 °C (-4 °F to 122 °F) Humidity 10–85% RH (non-condensing)
<b>Wide dynamic range</b>	Forensic WDR	<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F)
<b>Minimum illumination</b>	Color: 0.25 lux	<b>Approvals</b>	EMC 55032 Class B, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, VCCI Class B, RCM AS/NZS CISPR 32 Class B, ICES-003 Class B, KCC KN32 Class B, KN35 Safety IEC/EN/UL 62368-1 Environment EN 50581, IEC 60529 IP3X, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-78, IEC 60068-2-6, IEC 60068-2-27
<b>Shutter time</b>	1/32500 s to 1/25 s with 50 Hz 1/32500 s to 1/30 s with 60 Hz	<b>Dimensions</b>	28 x 24 x 20 mm (1 1/8 x 15/16 x 13/16 in)
<b>Frame rate</b>	Max 25/30 fps (50/60 Hz)	<b>Weight</b>	12.2 g (0.03 lb)
		<b>Required hardware</b>	AXIS FA Main Unit
		<b>Included accessories</b>	8-m (26 ft) black cable, 1 pcs locking nut, AXIS F82A06 Angled Pinhole Mount Installation Guide
		<b>Optional accessories</b>	AXIS F7315 Cable White 15 m AXIS F8204 Mounting Band AXIS F8211 Pinhole Trim Ring, AXIS F8212 Trim Ring, AXIS F8225 Pinhole Accessory
		<b>Warranty</b>	Axis 3-year warranty and AXIS Extended Warranty option, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>

### Environmental responsibility:

[www.axis.com/environmental-responsibility](http://www.axis.com/environmental-responsibility)