

AXIS M1065-LW Network Camera

Full-featured wireless HDTV 1080p camera with edge storage

AXIS M1065-LW features wireless communication and supports microSD card for edge storage. It has a built-in microphone for recording audio, a mini-speaker that can announce pre-recorded messages and a PIR motion sensor for detecting movement even in the dark. The WDR enabled camera offers 1080p resolution at full frame rate, day and night functionality with a mechanical IR cut filter, and IR illumination. It is easy to install with included wall and corner bracket, and has a 110° horizontal field of view.

- > [Wireless communication and edge storage](#)
- > [Built-in microphone and mini-speaker](#)
- > [PIR motion sensor](#)
- > [Bracket for wall and corner mount](#)
- > [IR illumination](#)



AXIS M1065-LW Network Camera

Camera		Video and audio recording to edge storage, activation of IR-LED, audio clip playback, overlay text Pre- and post-alarm video buffering
Image sensor	1/3" progressive scan RGB CMOS	
Lens	Fixed focal length, 2.8 mm, F2.0 Horizontal field of view: 110° Vertical field of view: 61° M12 mount, fixed iris, IR corrected	Data streaming Event data
Day and night	Automatically removable IR cut filter	Built-in installation aids Pixel counter
Minimum illumination	Color: 0.25 lux at 50 IRE F2.0 B/W: 0.05 lux at 50 IRE F2.0, 0 lux with IR illumination on	General
Shutter time	1/28000 s to 1/5 s with 50 Hz 1/32500 s to 1/5 s with 60 Hz	Casing Polycarbonate, aluminum, recycled plastic Color: White NCS S 1002-B For repainting instructions of skin cover or casing and impact on warranty, contact your Axis partner.
Pan/Tilt/Zoom	Digital PTZ	Sustainability PVC-free, 64% recycled plastic
Video		Mounting ¼"-20 UNC tripod screw thread
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles, Motion JPEG	Memory 512 MB RAM, 256 MB Flash
Resolution	1920x1080 HDTV 1080p to 320x240	Power 4.75–5.25 V DC, typical 2.7 W, max 5.0 W
Frame rate	Up to 25/30 fps (50/60 Hz) in all resolutions	IR illumination IR illumination, LED with adjustable intensity. Range up to 10 m (32 ft)
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264	Connectors Micro USB type B for power only RJ45 10BASE-T/100BASE-TX
Image settings	Compression, color, brightness, sharpness, contrast, white balance, exposure control, day/night shift level, rotation: 0°, 180°, text and image overlay, privacy masks, mirroring of images, WDR	Storage Support for microSD/microSDHC/microSDXC card Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Audio		PIR sensor Passive infrared (PIR) motion sensor. Max range: 6 m (19.7 ft)
Audio streaming	Two-way, half duplex	Operating conditions 0 °C to 40 °C (32 °F to 104 °F) Humidity 10–85% RH (non-condensing)
Audio compression	24bit LPCM, AAC-LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16 kHz Configurable bit rate	Storage conditions -40 °C to 65 °C (-40 °F to 149 °F) Humidity 10–85% RH (non-condensing)
Audio input/output	Built-in microphone (can be disabled), Built-in speaker 82 dB-SPL (at 0.5 m / 20 in)	Approvals EMC EN 55032 Class B, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 32 Class B, KN24, KN35 Wireless EN 300328, EN 301489-1, EN 301489-17, EN 301893, FCC Part 15 Subpart C, FCC Part 15 Subpart E, RSS-247, TELEC Safety IEC/EN/UL 60950-1, IEC/EN 62471 Network NIST SP500-267
Network		Dimensions 106 mm x 60 mm x 37 mm (4.17 x 2.36 x 1.46 in)
Wireless interface	Internal antenna IEEE 802.11a/b/g/n @ 2.4 GHz, @ 5 GHz (channels 36, 40, 44, 48)	Weight 128 g (0.28 lb)
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log WPA/WPA2-PSK, WPA, WPA2 Enterprise, WLAN pairing button (WPS) PBC-compatible, Brute force delay protection, Signed firmware	Included accessories Power supply, Installation Guide, mounting bracket, table top stand, Windows decoder 1-user license
Supported protocols	IPv4, IPv6 USGv6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, LLDP	Optional accessories AXIS T8415 Installation Display T91A10 Mounting Kit AXIS Surveillance microSDXC TM Card 64 GB For more accessories, see axis.com
System integration		Video management software AXIS Companion video management software, AXIS Camera Station, Video management software from Axis' Application Development Partners available on axis.com/vms
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com AXIS Guardian with One-Click Connection ONVIF [®] Profile G, ONVIF [®] Profile S and ONVIF [®] Profile T; specifications at onvif.org	Languages English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Analytics	Included AXIS Video Motion Detection, active tampering alarm Supported Audio detection AXIS Cross Line Detection, AXIS Digital Autotracking Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap	Warranty Axis 3-year warranty and AXIS Extended Warranty option, see axis.com/warranty
Event triggers	Analytics, edge storage events Built-in PIR	
Event actions	File upload: FTP, HTTP, network share and email Notification: email, HTTP, HTTPS and TCP	

a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (openssl.org/), and cryptographic software written by Eric Young (ey@cryptsoft.com).*

Environmental responsibility:

axis.com/environmental-responsibility