

AXIS M1125 Network Camera

Affordable and feature-rich with HDTV 1080p

AXIS M1125 is a day and night camera delivering HDTV 1080p video in up to 25/30 frames per second. The camera is fitted with an IR-corrected, varifocal and easily exchangeable CS-mount lens with DC-iris. AXIS M1125 includes Axis Zipstream technology that significantly reduces bandwidth and storage requirements. WDR - Forensic Capture provides video optimized for forensic purposes in scenes with complex light conditions. AXIS M1125 supports Power over Ethernet to simplify installation, microSD card slot for edge storage, digital input and output ports for external connection, as well as enhanced capacity for analytic applications such as people counting and heat mapping.

- > [HDTV 1080p in up to 25/30 fps](#)
- > [Varifocal CS-mount lens](#)
- > [Day and night camera](#)
- > [WDR - Forensic Capture](#)
- > [Axis Zipstream technology](#)



AXIS M1125 Network Camera

Camera		Casing	Polycarbonate blend Color: White NCS S 1002-B and Axis Black NCS S9000-N
Image sensor	Progressive scan RGB CMOS 1/3"	Mounting	1/4"-20 tripod screw thread Camera stand included
Lens	Varifocal, IR corrected, CS-mount, DC-iris, 3–10.5 mm Horizontal field of view: 91°–32° Vertical field of view: 49°–18°	Sustainability	PVC-free PCB is bromine-free
Day and night	Automatically removable infrared-cut filter	Memory	512 MB RAM, 256 MB Flash
Minimum illumination	Color: 0.25 lux F1.4 B/W: 0.05 lux F1.4	Power	8–28 V DC or Power over Ethernet (PoE) IEEE 802.3af Class 2, max 5.0 W, typical 3.6 W
Shutter time	1/66500 to 1 s	Connectors	RJ45 10BASE-T/100BASE-TX PoE Terminal block for one input and one output (12 V DC output, max. load 15 mA) DC input, terminal block
Video		Storage	Support for microSD/microSDHC/microSDXC card SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Video compression	H.264 Baseline, Main and High profile (MPEG-4 Part 10/AVC) Motion JPEG	Operating conditions	-20 °C to 50 °C (-4 °F to 122 °F) Humidity 10–85% RH (non-condensing)
Resolution	1920x1080 to 160x90	Storage conditions	-20 °C to 50 °C (-4 °F to 122 °F)
Frame rate	Up to 25/30 fps in all resolutions	Approvals	EMC EN 55022 Class A, EN 61000-6-1, EN 61000-3-2, EN 61000-3-3, EN 61000-6-2, EN 55024, EN 50121-4, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 22 Class A, KCC KN22 Class A, KN24 Safety IEC/EN/UL 60950-1, IS 13252 Environment EN 50581, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-30, IEC 60068-2-78, IEC 60721-4-3 Class 3M4 Network NIST SP500-267
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth, VBR/MBR H.264	Dimensions	44 x 70 x 148 mm (1 3/4 x 2 3/4 x 5 13/16 in)
Image settings	WDR – forensic capture: up to 120 dB depending on scene, manual shutter time, compression, color, brightness, sharpness, contrast, white balance, exposure control (including automatic gain control), exposure zones, fine tuning of behavior at low light, rotation: 0°, 90°, 180°, 270° including Corridor Format, aspect ratio correction, text and image overlay, privacy mask, mirroring of images	Weight	Bare bone: 160 g (0.35 lb) With optics: 200 g (0.45 lb)
Pan/Tilt/Zoom	Digital PTZ	Included accessories	AXIS T91A11 Stand White, Installation Guide, Windows® decoder 1-user license
Network		Optional accessories	AXIS T91A04/T91A05 Camera Holders, AXIS T91A50 Telescopic Ceiling Mount, AXIS T92E20 and AXIS T93F Housing Series, Mains adaptor PS-P terminal connector, AXIS T8006 PS12, AXIS T90B Illuminators
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, digest authentication, user access log, brute force delay protection, signed firmware	Video management software	AXIS Camera Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available at axis.com/vms
Supported protocols	IPv4, IPv6 USGv6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
System integration		Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see axis.com/warranty
Application Programming Interface	Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at axis.com AXIS Guardian with One-Click Connection ONVIF® Profile G, ONVIF® Profile S and ONVIF® Profile T. Specification at onvif.org	a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).	
Analytics	Included AXIS Video Motion Detection, active tampering alarm Supported Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap	Environmental responsibility: axis.com/environmental-responsibility	
Event triggers	Analytics, edge storage events, external input		
Event actions	File upload via FTP, HTTP HTTPS, SFTP, network share and email Notification via email, HTTP, HTTPS, TCP Video recording to edge storage, pre- and post-alarm video buffering, PTZ preset, guard tour, send video clip, send SNMP trap, day/night vision mode, WDR mode, status LED indicator, output port		
Data streaming	Event data		
Built-in installation aids	Pixel counter		
General			