

## AXIS M3026-VE Network Camera

Outdoor-ready, day/night fixed dome with HDTV 1080p

AXIS M3026-VE is a light-sensitive fixed dome providing detailed wide-angle views. It has day and night functionality, maintaining high image quality even in low-light conditions. It supports multi-view streaming, enabling different areas of a scene to be cropped from the full view and streamed simultaneously for viewing or recording. It also has support for Axis' Corridor Format for vertically oriented video streams, and for AXIS Camera Application Platform enabling the installation of intelligent video applications such as people counting. The vandal-resistant, outdoor-ready camera has IP66 and NEMA 4X ratings for protection against dust, rain and snow.

- > **Compact, vandal-resistant, outdoor-ready design**
- > **HDTV 1080p/3 MP**
- > **Day/night**
- > **Multi-view streaming**
- > **Power over Ethernet**



# AXIS M3026-VE Network Camera

|   |  |  |
|---|--|--|
| <b>Camera</b>                                 |  | Pre- and post-alarm video buffering<br>Go to PTZ preset, guard tour  |
| <b>Image sensor</b>                           | 1/3.6" (effective) progressive scan RGB CMOS   |  |
| <b>Lens</b>                                   | M12 mount, fixed iris, IR corrected<br>2.0 mm, F2.0<br>Horizontal field of view: 106°<br>Vertical field of view: 78°   | <b>Data streaming</b> Event data   |
| <b>Day and night</b>                          | Automatically removable infrared-cut filter  | <b>Built-in installation aids</b> Pixel counter  |
| <b>Light sensitivity/minimum illumination</b> | Color: 0.3-200000 lux, F2.0, B/W: 0.06 lux, F2.0   | <b>General</b>   |
| <b>Shutter time</b>                           | 1/30500 s to 2 s   | <b>Casing</b> IP66- and NEMA 4X-rated, IK10 impact-resistant aluminum casing with transparent, polycarbonate cover and dehumidifying membrane, Encapsulated electronics, Captive screws (resistorx 10)<br>Color: White NCS S 1002-B<br>For repainting instructions of skin cover or casing and impact on warranty, contact your Axis partner.                                    |
| <b>Camera angle adjustment</b>                | Pan ±175°, Tilt 70°, Rotation ±180°  | <b>Memory</b> 512 MB RAM, 128 MB Flash   |
| <b>Video</b>                                  |  | <b>Power</b> Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 2 max 4.5 W, typical 3.4 W  |
| <b>Video compression</b>                      | H.264 (MPEG-4 Part 10/AVC) Baseline and Main Profile<br>Motion JPEG  | <b>Connectors</b> Shielded male RJ45 10BASE-T/100BASE-TX PoE on a 2 m (6.6 ft) network cable, warranty can be maintained even when cable is cut-for more information, contact your Axis partner<br>Terminal block for 1 alarm input and 1 output   |
| <b>Resolution</b>                             | 2048x1536 (3 MP) to 160x120  | <b>Storage</b> Support for microSD/microSDHC/microSDXC card<br>SD card encryption<br>Support for recording to network-attached storage (NAS)<br>For SD card and NAS recommendations see <a href="http://axis.com">axis.com</a>   |
| <b>Frame rate</b>                             | <b>2 MP (1600x1200) and HDTV 1080p (1920x1080) capture modes:</b><br>25/30 fps with power line frequency 50/60 Hz<br><b>3 MP capture mode:</b><br>16/20 fps with power line frequency 50/60 Hz   | <b>Operating conditions</b> -30 °C to 50 °C (-22 °F to 122 °F)<br>Humidity 10–100% RH (condensing)   |
| <b>Video streaming</b>                        | Multiple, individually configurable streams in H.264 and Motion JPEG<br>Controllable frame rate and bandwidth<br>VBR/MBR H.264   | <b>Storage conditions</b> -40 °C to 65 °C (-40 °F to 149 °F)<br>Humidity 5-95% RH (non-condensing)   |
| <b>Multi-view streaming</b>                   | Up to 8 individually cropped out view areas. When streaming 4 view areas and 1 overview in VGA resolution, the frame rate is 16/20 fps per stream with power line frequency 50/60 Hz (3 MP capture mode)   | <b>Approvals</b> EMC<br>EN 55022 Class B, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 22 Class B, KCC KN22 Class B, KN24<br>Safety<br>IEC/EN/UL 60950-22<br>Environment<br>EN 50581, IEC 60529 IP66, NEMA 250 Type 4X, IEC 62262 IK10  |
| <b>Pan/Tilt/Zoom</b>                          | Digital PTZ, preset positions, guard tour  | <b>Dimensions</b> Ø 132 x 93 mm (Ø 5 3/16 x 3 11/16 in)  |
| <b>Image settings</b>                         | Compression, color, brightness, sharpness, contrast, white balance, exposure control, backlight compensation, WDR – dynamic contrast, text and image overlay, mirroring of images, privacy mask<br>Rotation: 0°, 90°, 180°, 270°, including Corridor Format<br>Exposure zones, fine tuning of low light behavior | <b>Weight</b> 740 g (1.6 lb)   |
| <b>Network</b>                                |  | <b>Included accessories</b> Installation Guide, Windows® decoder 1-user license, Drill hole template, Resistorx L-key, Terminal block connector  |
| <b>Security</b>                               | Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1X <sup>a</sup> network access control, Digest authentication, User access log, Centralized Certificate Management  | <b>Optional accessories</b> AXIS T91 Mount Accessories, AXIS T94F01D Pendant Kit, AXIS T94F01L Recessed Mount Kit, AXIS T94F01M J-Box/Gang Box Plate, AXIS T94F01P Conduit Back Box, AXIS T94F01S Mount Bracket, AXIS T94F02D Pendant Kit with sunshield, Network Cable Coupler IP66, Network Cable Coupler Indoor, Network Cable Coupler Indoor Slim, Skin covers (White/Black) |
| <b>Supported protocols</b>                    | IPv4/v6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP, SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH  | <b>Video management software</b> AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at <a href="http://axis.com/vms">axis.com/vms</a>   |
| <b>System integration</b>                     |  | <b>Languages</b> English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese   |
| <b>Application Programming Interface</b>      | Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at <a href="http://axis.com">axis.com</a><br>AXIS Guardian with One-Click Connection<br>ONVIF Profile S and ONVIF Profile G, specification at <a href="http://onvif.org">onvif.org</a>                  | <b>Warranty</b> Axis 3-year warranty and AXIS Extended Warranty option, see <a href="http://axis.com/warranty">axis.com/warranty</a>   |
| <b>Analytics</b>                              | AXIS Video Motion Detection 4, active tampering alarm<br>Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://axis.com/acap">axis.com/acap</a>  |  |
| <b>Event triggers</b>                         | Analytics, edge storage events, external input   |  |
| <b>Event actions</b>                          | File upload: FTP, SFTP, HTTP, HTTPS, network share and email<br>Notification: email, HTTPS and TCP<br>External output activation<br>Video recording to edge storage  |  |

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<http://www.openssl.org/>), and cryptographic software written by Eric Young ([ey@cryptsoft.com](mailto:ey@cryptsoft.com)).

Environmental responsibility:

[axis.com/environmental-responsibility](http://axis.com/environmental-responsibility)