

AXIS M3044-V

HDTV 720p fixed mini dome

The palm-sized AXIS M3044-V is an affordably priced, vandal- and dust-resistant indoor HDTV 720p fixed mini dome. WDR ensures that details in both the dark and bright areas of a scene are visible. The camera has an integrated RJ45 Ethernet connection and supports Power over Ethernet (PoE). The factory-focused camera can be mounted on walls or ceilings and with its 3-axis camera angle adjustment it can be easily leveled and directed in any direction. Axis Corridor Format enables vertically oriented video streams. AXIS M3044-V supports video analytics such as people counting.

- > [Ultra-compact, vandal and dust-resistant design](#)
- > [HDTV 720p / 1 MP](#)
- > [Axis Zipstream technology for reduced bandwidth and storage](#)
- > [Axis Corridor Format](#)



AXIS M3044-V

Models		Casing	IP42 water- and dust-resistant (to comply with IP42, follow Installation Guide), IK08 impact-resistant, polycarbonate/ABS casing Encapsulated electronics, captive screws (Torx® 10) Color: white NCS S 1002-B For repainting instructions of skin cover or casing and impact on warranty, contact your Axis partner.
Camera		Sustainability	PVC free, 55% recycled plastics
Image sensor	1/3" progressive scan RGB CMOS	Memory	512 MB RAM, 256 MB Flash
Lens	M12 mount, fixed iris, fixed focus 2.8 mm, F2.0 Horizontal field of view: 82° Vertical field of view: 44°	Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 1 Typical 2.5 W, max 2.9 W
Light sensitivity	0.25 lux at 50 IRE F2.0	Connectors	RJ45 10BASE-T/100BASE-TX PoE ^b
Shutter time	1/32500 s to 1/5 s	Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For memory card and NAS recommendations see www.axis.com
Camera angle adjustment	Pan: ±177° Tilt: ±76° Rotation: ±176° Can be directed in any direction and see the wall/ceiling	Operating conditions	0 °C to 45 °C (32 °F to 113 °F) Humidity 15–85% RH (non-condensing)
Video		Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	Approvals	EMC EN 55032 Class B, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A and B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 22 Class B, KCC KN32 Class B, KN35 Safety IEC/EN/UL 60950-1 Environment IEC/EN 60529 IP42, IEC/EN 62262 Class IK08, RoHS, WEEE Network NIST SP500-267
Resolution	1280x720 (720p) to 320x240	Dimensions	Height: 56 mm (2.2 in) ø 101 mm (4.0 in)
Frame rate	25/30 fps with power line frequency 50/60 Hz	Weight	170 g (0.38 lb)
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264	Included accessories	Installation Guide Windows decoder 1-user license Torx® L-key
Pan/Tilt/Zoom	Digital PTZ	Optional accessories	AXIS T94B02D Pendant kit AXIS T94B02L Recessed mount AXIS T94B01P Conduit back box AXIS T94B02M J-Box/Gang box plate View protection Black casing Smoked dome Axis Mounts AXIS Surveillance microSDXC™ Card For more accessories see www.axis.com
Image settings	Compression, color, brightness, sharpness, contrast, white balance, exposure control, WDR, text and image overlay, mirroring of images, privacy mask Rotation: 0°, 90°, 180°, 270°, including Corridor Format	Video management software	AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/vms
Network		Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection	Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty
Supported protocols	IPv4, IPv6 USGv6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTPC, ICMP, DHCP, ARP, SOCKS, SSH, LLDP		
System integration			
Application Programming Interface	Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF® Profile S and ONVIF® Profile G, specification at onvif.org		
Analytics	Included AXIS Video Motion Detection, active tampering alarm Supported AXIS Digital Autotracking, AXIS Fence Guard, AXIS Motion Guard, AXIS Loitering Guard, AXIS People Counter, AXIS Queue Monitor, AXIS Occupancy Estimator, AXIS Direction Detector, AXIS Tailgating Detector, AXIS Random Selector Support for AXIS Camera Application Platform enabling installation of third-party applications, see www.axis.com/acap		
Event triggers	Analytics, edge storage events		
Event actions	File upload: FTP, SFTP, HTTP, HTTPS network share and email Notification: email, HTTP, HTTPS and TCP and SNMP trap Video recording to edge storage Send video clip Pre- and post-alarm video buffering Overlay text		
Data streaming	Event data		
Built-in installation aids	Pixel counter		
General			

- a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<http://www.openssl.org/>), and cryptographic software written by Eric Young (ey@cryptsoft.com).
b. Make sure that the cable has a slim connector plug

Environmental responsibility:

www.axis.com/environmental-responsibility