

AXIS M3045-V Network Camera

HDTV 1080p fixed mini dome with HDMI

AXIS M3045-V is an affordably priced, vandal- and dust-resistant indoor fixed dome. The camera has an integrated RJ45 Ethernet connection and supports Power over Ethernet (PoE). WDR ensures that details in both the dark and bright areas of a scene are visible. HDMI support enables live streaming to an HDTV monitor for e.g. public viewing. The factory-focused camera can be mounted on walls or ceilings and with its 3-axis camera angle adjustment it can be easily leveled and directed in any direction. Axis Corridor Format enables vertically oriented video streams. AXIS M3045-V supports video analytics such as people counting.

- > **Ultra-compact, vandal- and dust-resistant design**
- > **HDTV 1080p / 2 MP**
- > **HDMI support enables streaming to a monitor**
- > **Axis Zipstream technology for reduced bandwidth and storage**
- > **Axis Corridor Format**



AXIS M3045-V Network Camera

Models		Overlay text
Camera		Data streaming Event data
Image sensor	1/3" progressive scan RGB CMOS	Built-in installation aids Pixel counter
Lens	M12 mount, fixed iris, fixed focus 2.8 mm , F2.0 Horizontal field of view: 106° Vertical field of view: 59°	
Light sensitivity	0.25 lux at 50 IRE F2.0	
Shutter speed	1/32500 s to 1/5 s	
Camera angle adjustment	Pan: ±177° Tilt: ±69° Rotation: ±176° Can be adjusted in any direction and see the wall or ceiling.	
Video		General
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	Cybersecurity Signed firmware
Resolution	1920x1080 (1080p) to 320x240	Casing IP42 water- and dust-resistant (to comply with IP42, follow the Installation Guide), IK08 impact-resistant, polycarbonate/ABS casing Encapsulated electronics, captive screws (TORX® 10) Color: white NCS S 1002-B For repainting instructions of skin cover or casing and impact on warranty, contact your Axis partner.
Frame rate	25/30 fps with power line frequency 50/60 Hz	Sustainability PVC-free, 55% recycled plastics
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264 HDMI™	Memory 512 MB RAM, 256 MB Flash
Multi-view streaming	Up to 2 individually cropped out view areas in full frame rate	Power Power over Ethernet (PoE) IEEE 802.3af / 802.3at Type 1 Class 1 Typical 2.6 W , max 3.0 W
Pan/Tilt/Zoom	Digital PTZ	Connectors Shielded RJ45 10BASE-T/100BASE-TX PoE ^b Micro HDMI™ (Type D ^b) Audio and I/O connectivity via AXIS T61 Audio and I/O Interfaces with portcast technology
HDMI output	HDMI 1080p@25/30 fps (50/60 Hz) HDMI 1080i@50/60 fps (50/60 Hz) HDMI 720p@50/60 fps (50/60 Hz) HDMI 720p@25/30 fps (50/60 Hz)	Storage Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For memory card and NAS recommendations see axis.com
Image settings	Compression, color, brightness, sharpness, contrast, white balance, exposure control, WDR, text and image overlay, mirroring of images, privacy mask Rotation: 0°, 90°, 180°, 270°, including Corridor Format	Operating conditions 0° C to 45° C (32° F to 113° F) Humidity 15-85% RH (non-condensing)
Audio		Storage conditions -40° C to 65° C (-40° F to 149° F) Humidity 5-95% RH (non-condensing)
Audio input/output	Two-way audio connectivity via AXIS T61 Audio and I/O Interfaces with portcast technology	Approvals EMC EN 55032 Class B , EN 55024 , EN 61000-6-1 , EN 61000-6-2 , FCC Part 15 Subpart B Class A and B , ICES-003 Class B , VCCI Class B , RCM AS/NZS CISPR 22 Class B , KCC KN32 Class B, KN35 Safety IEC/EN/UL 60950-1 , IS 13252 Environment IEC/EN 60529 IP42 , IEC/EN 62262 Class IK08 Network NIST SP500-267
Network		Dimensions Height: 56 mm (2.2 in) ø 101 mm (4.0 in)
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1x (EAP-TLS) ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection	Weight 170 g (0.38 lb)
Supported protocols	IPv4, IPv6 USGv6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP™ , SNMPv1/v2c/v3 (MIB-II) , DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTP, ICMP, DHCP, ARP, SOCKS, SSH, HDMI™ 1.4b, LLDP, MQTT v3.1.1	Included accessories Installation Guide Windows® decoder 1-user license TORX® L-key
System integration		Optional accessories AXIS T94B02D Pendant kit AXIS T94B02L Recessed mount AXIS T94B01P Conduit back box AXIS T94B02M J-Box/Gang box plate View protection Black casing Smoked dome Axis Mounts AXIS Surveillance microSDXC™ Card For more accessories see axis.com
Application Programming Interface	Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF® Profile G , ONVIF® Profile S , and ONVIF® Profile T ; specification at onvif.org	Video management software AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available at axis.com/vms
Analytics	Included AXIS Video Motion Detection , active tampering alarm Supported AXIS Digital Autotracking, AXIS Fence Guard, AXIS Motion Guard, AXIS Loitering Guard, AXIS People Counter, AXIS Queue Monitor, AXIS Occupancy Estimator, AXIS Direction Detector, AXIS Tailgating Detector, AXIS Random Selector Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap	Languages English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Event triggers	Analytics, edge storage events	Warranty Axis 3-year warranty and AXIS Extended Warranty option, see axis.com/warranty
Event actions	File upload: FTP, SFTP, HTTP, HTTPS network share and email Notification: email, HTTP, HTTPS and TCP and SNMP trap Video recording to edge storage Send video clip Pre- and post-alarm video buffering	

- a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<http://www.openssl.org/>), and cryptographic software written by Eric Young (ey@cryptsoft).
- b. Make sure that the cable has a slim connector plug

Environmental responsibility:

