

## AXIS M3046-V Network Camera

Multi-megapixel fixed mini dome with HDMI and wide view

AXIS M3046-V is an affordably priced dome that provides up to 4 MP video. WDR ensures visible details both in dark and bright areas. HDMI support enables live streaming to a public viewing monitor. AXIS M3046-V provides a wide field of view that can e.g. cover a whole store from a corner, from the product shelves under the camera up to the ceiling. Alternatively, thanks to its digital PTZ capability, the camera can deliver cropped out views, e.g. in HDTV 1080p, with variable field of view. No manual focusing is needed since the camera comes factory-focused.

- > **Ultra-compact, vandal- and dust-resistant design**
- > **Two lens options: 2.4 mm or 1.8 mm**
- > **HDMI support enables streaming to a monitor**
- > **Axis Zipstream technology for reduced bandwidth and storage**
- > **Axis Corridor Format & 3-axis camera angle adjustment**



# AXIS M3046-V Network Camera

<b>Models</b>	AXIS M3046-V 2.4 mm AXIS M3046-V 1.8 mm	Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://axis.com/acap">axis.com/acap</a>
<b>Camera</b>		<b>Event triggers</b>
<b>Image sensor</b>	1/3" progressive scan RGB CMOS	Analytics, edge storage events Virtual inputs through API
<b>Lens</b>	M12 mount, fixed iris, fixed focus <b>2.4 mm:</b> F2.2 Horizontal field of view: 128° Vertical field of view: 72° <b>1.8 mm:</b> F2.4 <b>4:3 aspect ratio:</b> Horizontal field of view: 132°, vertical field of view: 96° <b>16:9 aspect ratio:</b> Horizontal field of view: 152°, vertical field of view: 80°	<b>Event actions</b>
<b>Light sensitivity</b>	<b>2.4 mm:</b> 0.3 lux at 50 IRE F2.2 <b>1.8 mm:</b> 0.35 lux at 50 IRE F2.4	File upload: FTP, SFTP, HTTP, HTTPS network share and email Notification: email, HTTP, HTTPS and TCP and SNMP trap Video recording to edge storage Send video clip Pre- and post-alarm video buffering Overlay text
<b>Shutter time</b>	1/32500 s to 1/5 s	<b>Data streaming</b>
<b>Camera angle adjustment</b>	Pan: ±177° Tilt: ±65° Rotation: ±176° Can be adjusted in any direction and see the wall or ceiling.	Event data
<b>Video</b>		<b>Built-in installation aids</b>
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	Pixel counter
<b>Resolution</b>	<b>2.4 mm:</b> 2688x1520 to 320x240 <b>1.8 mm:</b> 2304x1296 to 640x360 (16:9) or 2016x1512 to 320x240 (4:3)	<b>General</b>
<b>Frame rate</b>	25/30 fps with power line frequency 50/60 Hz	<b>Cybersecurity</b>
<b>Video streaming</b>	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264 HDMI™	Signed firmware
<b>Multi-view streaming</b>	Up to 2 individually cropped out view areas in full frame rate	<b>Casing</b>
<b>Pan/Tilt/Zoom</b>	Digital PTZ	IP42 water- and dust-resistant (to comply with IP42, follow the Installation Guide), IK08 impact-resistant, polycarbonate/ABS casing Encapsulated electronics, captive screws (TORX® 10) Color: white NCS S 1002-B For repainting of casing, remove the transparent dome. Contact your Axis partner for repainting instructions and impact on warranty.
<b>HDMI output</b>	HDMI 1080p@25/30 fps (50/60 Hz) HDMI 1080i@50/60 fps (50/60 Hz) HDMI 720p@50/60 fps (50/60 Hz) HDMI 720p@25/30 fps (50/60 Hz)	<b>Sustainability</b>
<b>Image settings</b>	Compression, color, brightness, sharpness, contrast, white balance, exposure control, WDR, text and image overlay, mirroring of images, privacy mask Rotation: 0°, 90°, 180°, 270°, including Corridor Format	PVC-free, 55% recycled plastics
<b>Audio</b>		<b>Memory</b>
<b>Audio input/output</b>	Two-way audio connectivity via AXIS T61 Audio and I/O Interfaces with portcast technology	512 MB RAM, 256 MB Flash
<b>Network</b>		<b>Power</b>
<b>Security</b>	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1x (EAP-TLS) <sup>a</sup> network access control, digest authentication, user access log, centralized certificate management, brute force delay protection	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 1 Typical 2.8 W, max 3.2 W
<b>Supported protocols</b>	IPv4, IPv6 USGv6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTPC, ICMP, DHCP, ARP, SOCKS, SSH, HDMI™ 1.4b, LLDP	<b>Connectors</b>
<b>System integration</b>		Shielded RJ45 10BASE-T/100BASE-TX PoE <sup>b</sup> HDMI™ Type D <sup>b</sup> Audio and I/O connectivity via AXIS T61 Audio and I/O Interfaces with portcast technology
<b>Application Programming Interface</b>	Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at <a href="http://axis.com">axis.com</a> AXIS Guardian with One-Click Connection ONVIF® Profile G, ONVIF® Profile S, and ONVIF® Profile T; specification at <a href="http://onvif.org">onvif.org</a>	<b>Storage</b>
<b>Analytics</b>	<b>Included</b> AXIS Video Motion Detection, active tampering alarm <b>Supported</b> AXIS Digital Autotracking, AXIS Fence Guard, AXIS Motion Guard, AXIS Loitering Guard, AXIS People Counter, AXIS Queue Monitor, AXIS Occupancy Estimator, AXIS Direction Detector, AXIS Tailgating Detector, AXIS Random Selector	Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For memory card and NAS recommendations see <a href="http://axis.com">axis.com</a>
		<b>Operating conditions</b>
		0 °C to 40 °C (32 °F to 104 °F) Humidity 15–85% RH (non-condensing)
		<b>Storage conditions</b>
		-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
		<b>Approvals</b>
		EMC EN 55032 Class B, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A and B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 22 Class B, KCC KN32 Class B, KN35 Safety IEC/EN/UL 60950-1, IS 13252 Environment IEC/EN 60529 IP42, IEC/EN 62262 Class IK08, RoHS, WEEE Network NIST SP500-267
		<b>Dimensions</b>
		Height: 56 mm (2.2 in) ø 101 mm (4.0 in)
		<b>Weight</b>
		180 g (0.40 lb)
		<b>Included accessories</b>
		Installation Guide Windows® decoder 1-user license TORX® L-key
		<b>Optional accessories</b>
		AXIS T94B02D Pendant kit AXIS T94B02L Recessed mount AXIS T94B01P Conduit back box AXIS T94B02M J-Box/Gang box plate View protection Black casing Smoked dome Axis Mounts AXIS Surveillance microSDXC™ Card For more accessories see <a href="http://axis.com">axis.com</a>
		<b>Video management software</b>
		AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available at <a href="http://axis.com/vms">axis.com/vms</a>

<b>Languages</b>	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
<b>Warranty</b>	Axis 3-year warranty and AXIS Extended Warranty option, see <a href="http://axis.com/warranty">axis.com/warranty</a>

a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<http://www.openssl.org/>), and cryptographic software written by Eric Young ([ey@cryptsoft](mailto:ey@cryptsoft)).*

b. *Make sure that the cable has a slim connector plug*

Environmental responsibility:

[axis.com/environmental-responsibility](http://axis.com/environmental-responsibility)