

## AXIS M3104-L Network Camera

Discreet HDTV 720p video surveillance with built-in IR illumination

AXIS M3104-L is an affordable, discreet fixed mini dome with a flat-faced design that suppresses reflections. Using WDR technology and IR illumination, it provides compact HDTV surveillance even in challenging light conditions or total darkness. The smart design allows for easy repainting, or using the optional black accessory casing to blend the camera into its environment. Axis Zipstream technology reduces bandwidth and storage requirements. A variety of accessories are available for flexible and easy installation.

- > [Built-in IR illumination](#)
- > [HDTV 720p video](#)
- > [WDR – Forensic Capture](#)
- > [Axis Zipstream technology](#)
- > [Smart design for easy, flexible installation](#)



# AXIS M3104-L Network Camera

|  |  |   |  |
|--|--|---|--|
| <b>Camera</b>                            |  | <b>Data streaming</b>   | Event data   |
| <b>Image sensor</b>                      | 1/2.8" progressive scan RGB CMOS   | <b>Built-in installation aids</b>   | Pixel counter  |
| <b>Lens</b>                              | M12 mount, Fixed iris, Fixed focus<br>2.8 mm, F2.0<br>Horizontal field of view: 80°<br>Vertical field of view: 45°   | <b>General</b>  |  |
| <b>Day and night</b>                     | Automatically removable infrared-cut filter  | <b>Casing</b>   | IP42 water and dust resistant (to comply with IP42, follow instructions in Installation Guide), ASA polymer casing<br>Encapsulated electronics, Captive screws (Torx 10)<br>Color: White NCS S 1002-B<br>For repainting instructions and impact on warranty, contact your Axis partner   |
| <b>Minimum illumination</b>              | Color: 0.2 lux at 50 IRE, F2.0<br>B/W: 0.04 lux at 50 IRE, F2.0<br>0 lux with IR illumination on   | <b>Sustainability</b>   | PVC free   |
| <b>Shutter speed</b>                     | 1/66500 s to 2 s   | <b>Memory</b>   | 512 MB RAM, 256 MB Flash   |
| <b>Camera angle adjustment</b>           | Pan: ±180°<br>Tilt: 0° to 60° (0° = lens directed at a right angle to camera base)<br>Rotation: ±95°<br>Can be directed in any direction and see the wall/ceiling  | <b>Power</b>  | Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 2<br>Typical: 4.2 W, Max.: 6.2 W   |
| <b>Video</b>                             |  | <b>Connectors</b>   | RJ45 10BASE-T/100BASE-TX PoE   |
| <b>Video compression</b>                 | H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles<br>Motion JPEG   | <b>IR illumination</b>  | Power-efficient, long-life 850 nm IR LED. Range of reach 15 m (50 ft) or more depending on the scene   |
| <b>Resolution</b>                        | 1280x720 to 176x120  | <b>Storage</b>  | Support for microSD/microSDHC/microSDXC card<br>Support for SD card encryption<br>Support for recording to network-attached storage (NAS)<br>For SD card and NAS recommendations see <a href="http://axis.com">axis.com</a>  |
| <b>Frame rate</b>                        | Up to 25/30 fps with power line frequency 50/60 Hz   | <b>Operating conditions</b>   | 0 °C to 50 °C (32 °F to 122 °F)<br>Humidity 10–85% RH (non-condensing)   |
| <b>Video streaming</b>                   | Multiple, individually configurable streams in H.264 and Motion JPEG<br>Axis Zipstream technology in H.264<br>Controllable frame rate and bandwidth<br>VBR/ABR/MBR H.264   | <b>Storage conditions</b>   | -40 °C to 65 °C (-40 °F to 149 °F)<br>Humidity 5–95% RH (non-condensing)   |
| <b>Image settings</b>                    | Compression, Color, Brightness, Sharpness, Contrast, Local contrast, White balance, Exposure control, WDR – Forensic Capture: up to 115 dB depending on scene. Rotation: 0°, 90°, 180°, 270° including Corridor Format, Text and image overlay, Privacy masks, Mirroring of images   | <b>Approvals</b>  | EMC<br>EN 55022 Class B, EN 55024, IEC 62471, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 22 Class B, KCC KN32 Class B, KN35<br>Environment<br>IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-78, IEC 60068-2-14, IEC 60068-2-6, IEC 60068-2-27, IEC/EN 60529 IP42, IEC 60721-3-4 Class 3M3<br>Safety<br>IEC/EN/UL 62368-1, IS 13252<br>Network<br>NIST SP500-267 |
| <b>Pan/Tilt/Zoom</b>                     | Digital PTZ  | <b>Dimensions</b>   | Height: 85 mm (3.3 in)<br>ø 100 mm (3.9 in)  |
| <b>Network</b>                           |  | <b>Weight</b>   | 360 g (0.78 lb)  |
| <b>Security</b>                          | Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1x (EAP-TLS) <sup>a</sup> network access control, Digest authentication, User access log, Centralized Certificate Management, brute force delay protection, signed firmware   | <b>Included accessories</b>   | Installation Guide, Windows decoder 1-user license, Torx® L-key  |
| <b>Supported protocols</b>               | IPv4, IPv6 USGv6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, LLDP, MQTT v3.1.1  | <b>Optional accessories</b>   | AXIS T94B02D Pendant kit<br>AXIS T94B01P Conduit Back Box<br>AXIS T94B02M J-Box/Gang Box Plate<br>AXIS M31-L Casing, Black<br>Axis Mounts<br>AXIS Surveillance microSDXC™ Card<br>For more accessories, see <a href="http://axis.com">axis.com</a>   |
| <b>System integration</b>                |  | <b>Video management software</b>  | AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on <a href="http://axis.com/vms">axis.com/vms</a>   |
| <b>Application Programming Interface</b> | Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at <a href="http://axis.com">axis.com</a><br>AXIS Video Hosting System (AVHS) with One-Click Connection<br>ONVIF® Profile G, ONVIF® Profile S, and ONVIF® Profile T, specification at <a href="http://onvif.org">onvif.org</a>  | <b>Languages</b>  | English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese  |
| <b>Analytics</b>                         | <b>Included</b><br>AXIS Video Motion Detection, active tampering alarm<br><b>Supported</b><br>AXIS Digital Autotracking, AXIS Fence Guard, AXIS Motion Guard, AXIS Loitering Guard, AXIS People Counter, AXIS Queue Monitor, AXIS Occupancy Estimator, AXIS Direction Detector, AXIS Tailgating Detector, AXIS Random Selector<br>Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://axis.com/acap">axis.com/acap</a> | <b>Warranty</b>   | Axis 3-year warranty and AXIS Extended Warranty option, see <a href="http://axis.com/warranty">axis.com/warranty</a>   |
| <b>Event triggers</b>                    | Analytics, Edge storage events, Virtual inputs through API   | a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. ( <a href="http://www.openssl.org">www.openssl.org</a> ), and cryptographic software written by Eric Young ( <a href="mailto:ey@cryptsoft.com">ey@cryptsoft.com</a> ). |  |
| <b>Event actions</b>                     | File upload: FTP, SFTP, HTTP, HTTPS, network share, email<br>Notification: email, HTTP, HTTPS, TCP, SNMP trap<br>Video recording to edge storage<br>Send video clip<br>Pre- and post-alarm video buffering<br>Overlay text<br>Day/night mode, overlay text, IR illumination, WDR mode  | Environmental responsibility:<br><a href="http://axis.com/environmental-responsibility">axis.com/environmental-responsibility</a>   |  |