

AXIS P1368-E Network Camera

Outdoor-ready 4K surveillance with i-CS lens

The 4K Ultra HD resolution at 25/30 fps ensures excellent video quality. The innovative outdoor-ready camera P1368-E is built for all weather conditions, with a quick and easy installation in mind. Built-in camera rails enable easier changing of lenses and with a simple roll of the sensor, the format shifts to Axis Corridor Format. Equipped with i-CS lens, the camera enables remote zoom and focus. It also supports standard CS-mount lenses. In complex lighting Forensic WDR together with Lightfinder will discover all details. Axis Zipstream technology saves bandwidth and storage while maintaining video quality.

- > **Temperature range: -40 °C to 55 °C (-40 °F to 131 °F)**
- > **IK10-, IP66- and NEMA 4X-ratings**
- > **Equipped with i-CS lens**
- > **Lightfinder and Forensic WDR**
- > **Zipstream**



AXIS P1368-E Network Camera

Camera		
Image sensor	1/2.5" progressive scan RGB CMOS	
Lens	IR corrected, i-CS lens Varifocal 2.8–8.5 mm, F1.2 With IK10 protection in the front window Horizontal field of view: 72°–45° Vertical field of view: 40°–25° Without IK10 protection in the front window Horizontal field of view: 83°–45° Vertical field of view: 45°–25°	Notification: email, HTTP, HTTPS and TCP External output activation Video recording to edge storage, Play audio clip Pre- and post-alarm video buffering PTZ preset, Guard tour, Overlay text Day/Night switching, Status LED activation Send SNMP trap
Day and night	Automatically removable infrared-cut filter	
Minimum illumination	Color: 0.16 lux B/W: 0.03 lux, at 50 IRE F1.3	
Shutter speed	1/55500 s to 2 s	
Video		
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG Controllable frame rate and bandwidth	Data streaming Event data
Resolution	3840x2160 (8 MP) to 160x90	Built-in installation aids Pixel counter Remote focus and zoom with supplied i-CS lens, remote back focus and focus assistant with other lenses
Frame rate	25/30 fps (50/60 Hz) in all resolutions	
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/ABR/MBR H.264	General
Multi-view streaming	Up to 8 individually cropped out view areas	Casing IP66-, IP67- and NEMA 4X-rated, IK10 impact-resistant polymer enclosure Color: White NCS S 1002-B
Image settings	Saturation, contrast, brightness, sharpness, Forensic WDR: Up to 120 dB depending on scene, white balance, day/night threshold, exposure mode, exposure zones, compression, orientation: 0°, 90°, 180°, 270° including Corridor Format, mirroring of images, dynamic text and image overlay, privacy masks	Sustainability PVC free
Pan/Tilt/Zoom	Digital PTZ Uploadable PTZ driver (Pelco D pre-installed)	Memory 1 GB RAM, 512 MB Flash
Audio		Power Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3, max 9.5 W, typical 6.4 W
Audio streaming	Two-way, full duplex	Connectors RJ45 10BASE-T/100BASE-TX PoE I/O: 4-pin 2.5 mm terminal block for two configurable inputs/outputs (12 V DC output, max. load 50mA) RS485/RS422, 2 pcs, 2 pos, full duplex, terminal block 3.5 mm mic/line in, 3.5 mm line out i-CS connector (compatible with P-Iris and DC-iris)
Audio encoding	AAC LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz, LPCM 8/16/32/48 kHz Configurable bit rate	Storage Support for microSD/microSDHC/microSDXC card Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Audio input/output	External microphone input or line input, line output Automatic gain control	Operating conditions -40 °C to 55 °C (-40 °F to 131 °F) Maximum temperature (intermittent): 60 °C (140 °F) Humidity 10–100% RH (condensing)
Network		Storage conditions -40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X (EAP-TLS) ^a network access control, digest authentication, user access log, brute force delay protection, signed firmware	Approvals EMC EN 55032 Class A, EN 50121-4, IEC 62236-4, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KCC KN32 Class A, KN35 Safety IEC/EN/UL 62368-1, IEC/EN/UL 60950-22, IS 13252 Environment IEC/EN 60529 IP66, NEMA 250 Type 4X, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 62262 IK10, IEC/EN 60529 IP67 Network NIST SP500-267
Supported protocols	IPv4, IPv6 USGv6, HTTP, HTTPS ^a , HTTP/2, SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP SM , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, SRTP, TCP, UDP, IGMP, RTCP, ICMP, DHCPv4/v6, ARP, SOCKS, SSH, LLDP, MQTT v3.1.1, Syslog	Dimensions 382 x 155 x 120 mm (15 x 6.1 x 4.7 in)
System integration		Weight 2.2 kg (4.9 lb)
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform, specifications at axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF [®] Profile G, ONVIF [®] Profile S and ONVIF [®] Profile T, specification at onvif.org	Included accessories Installation Guide, Windows [®] decoder 1-user license, wall mount bracket, sunshield, connector kit IK10 tool
Analytics	Included AXIS Video Motion Detection, active tampering alarm, audio detection Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap	Optional accessories Axis mounts, Axis lenses, Axis midspans For more accessories, see axis.com
Event triggers	Analytics, open casing, edge storage events, external input, audio level, time scheduled	Video management software AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available at axis.com/vms
Event actions	File upload: FTP, SFTP, HTTP, HTTPS, network share and email	Languages English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
		Warranty Axis 3-year warranty and AXIS Extended Warranty option, see axis.com/warranty

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (openssl.org/), and cryptographic software written by Eric Young (ey@cryptsoft.com).

Environmental responsibility:

axis.com/environmental-responsibility