

AXIS P3228-LVE Network Camera

Streamlined outdoor-ready 4K fixed dome for any light conditions

AXIS P3228-LVE is a streamlined, outdoor-ready 4K fixed dome that features a varifocal lens with remote zoom and focus, which facilitates installation and eliminates the need for hands-on fine tuning. Equipped with Forensic WDR to handle scenes with strong variations in light, Lightfinder technology, as well as built-in IR illumination with OptimizedIR, this versatile camera provides exceptional video quality in any light conditions. It supports Axis Zipstream technology that significantly reduces bandwidth and storage requirements. AXIS P3228-LVE is vandal-resistant with IK10 rating.

- > **4K video in full frame rate**
- > **Outdoor ready and IK10 rated**
- > **Forensic WDR, Lightfinder and OptimizedIR**
- > **Remote zoom and focus**
- > **Zipstream for reduced bandwidth and storage needs**



AXIS P3228-LVE Network Camera

Camera		Casing	IP66- and NEMA 4X-rated, IK10 impact-resistant casing with hard-coated dome and dehumidifying membrane Encapsulated electronics and captive screws Color: white NCS S 1002-B For repainting instructions of skin cover or casing and impact on warranty, contact your Axis partner.
Image sensor	Progressive scan RGB CMOS 1/2.5"	Mounting	Mounting bracket with holes for junction boxes (double-gang, single-gang, and 4" octagon) and for wall or ceiling mount ¼"-20 UNC tripod screw thread
Lens	Varifocal, 3.5–10 mm, F1.7 Horizontal field of view: 100°–38° Vertical field of view: 51°–22° Remote zoom and focus, P-Iris control, IR corrected	Sustainability	PVC free
Day and night	Automatically removable infrared-cut filter	Memory	1 GB RAM, 512 MB Flash
Minimum illumination	Color: 0.19 lux at 50 IRE, F1.7 B/W: 0.04 lux at 50 IRE, F1.7, 0 lux with IR illumination on	Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3, max 11.5 W, typical 8.6 W
Shutter time	1/62500 s to 2 s	Connectors	RJ45 10BASE-T/100BASE-TX PoE
Camera angle adjustment	Pan ±180°, tilt -40 to +75°, rotation ±95°	IR illumination	OptimizedIR with power-efficient, long-life 850 nm IR LEDs. Range of reach 30 m (100 ft) or more depending on the scene
Video		Storage	Support for microSD/microSDHC/microSDXC card SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	Operating conditions	-40 °C to 50 °C (-40 °F to 122 °F) Start-up: -30 °C to 50 °C (-22 °F to 122 °F) Maximum temperature (intermittent): 55 °C (131 °F) Humidity 10 to 100% RH (condensing)
Resolution	3840x2160 to 160x90	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Frame rate	25/30 fps with power line frequency 50/60 Hz	Approvals	EMC EN 55032 Class B, EN 50121-4, IEC 62236-4, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A and B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 22 Class B, KCC KN32 Class B, KN35 Safety IEC/EN/UL 60950-1, IEC/EN/UL 60950-22, IEC/EN 62471, IS 13252 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14 IEC 60068-2-6 (vibration), IEC 60068-2-27 (shock), IEC 60068-2-30, IEC 60068-2-78, IEC/EN 60529 IP66, NEMA 250 Type 4X, IEC/EN 62262 IK10 Network NIST SP500-267
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264	Dimensions	Height: 104 mm (4 1/16 in) ø 149 mm (5 7/8 in)
Multi-view streaming	8 individually cropped out view areas.	Weight	750 g (1.7 lb) including weathershield
Pan/Tilt/Zoom	Digital PTZ, Preset positions	Included accessories	Installation guide, Windows decoder 1-user license, mounting bracket, cable gasket, Resistorx®T20 L-key, drill template, connector guard, weather shield
Image settings	Compression, Color, Brightness, Sharpness, Contrast, Local contrast, White balance, Exposure control (including automatic gain control), Exposure zones, Fine tuning of behavior at low light, Forensic WDR: up to 120 dB depending on scene, Text and image overlay, Mirroring of images, Privacy masks Rotation: 0°, 90°, 180°, 270°, including Corridor Format	Optional accessories	AXIS T6101 Audio and I/O Interface AXIS T6112 Audio and I/O Interface AXIS ACI Conduit Bracket A AXIS ACI Conduit Adapters AXIS T94M01L Recessed Mount Kit AXIS T94T01D Pendant Kit including weather shield AXIS Mounts AXIS P32-VE Smoked Dome A
Network		Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available on axis.com/vms
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Supported protocols	IPv4, IPv6 USGv6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, LLDP	Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see axis.com/warranty
System integration		a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).</i>	
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com AXIS Video Hosting System (AVHS) with One-Click Connection AXIS Guardian with One-Click Connection ONVIF [®] Profile G, ONVIF [®] Profile S, and ONVIF [®] Profile T specification at onvif.org	Environmental responsibility: www.axis.com/environmental-responsibility	
Analytics	Included AXIS Video Motion Detection, active tampering alarm Supported AXIS Digital Autotracking, AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard, AXIS Perimeter Defender, AXIS Demographic Identifier Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap		
Event triggers	Analytics, edge storage events, virtual inputs through API		
Event actions	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap Overlay text, IR illumination on/off		
Data streaming	Event data		
Built-in installation aids	Remote zoom, remote focus, pixel counter		
General			