

AXIS P3367-V Network Camera

5-megapixel, light-sensitive with remote focus and zoom

AXIS P3367-V is a fixed dome network camera that offers superb video performance in HDTV 1080p/5 MP resolution. It complies with the SMPTE 274M standard and can cover a large area with exceptional detail and light sensitivity. Wide dynamic range and day/night functionality provides high image quality even in low-light conditions. With multi-view streaming, the full view and up to 8 individually cropped out view areas can be streamed simultaneously. P-Iris control provides optimal depth of field, resolution, image contrast and clarity. Remote zoom and focus eliminate the need for hands-on fine tuning. AXIS P3367-V has support for digital pan/tilt/zoom, two-way audio, audio detection and input/output ports for external devices.

- > [HDTV 1080p/5 MP](#)
- > [P-Iris control](#)
- > [Remote zoom and focus](#)
- > [I/O ports and two-way audio](#)
- > [IK10 vandal-resistance](#)



AXIS P3367-V Network Camera

Camera		AXIS Digital Autotracking, AXIS Cross Line Detection Support for AXIS Camera Application Platform enabling installation of third-party applications, see www.axis.com/acap
Image sensor	Progressive scan RGB CMOS 1/3.2"	Event triggers
Lens	3-9 mm, F1.2 Horizontal field of view: 84°-30° Vertical field of view: 63°-22° Varifocal, Remote focus and zoom, P-Iris control, IR corrected	Event actions
Day and night	Automatically removable infrared-cut filter	File upload: FTP, SFTP, HTTP, HTTPS, network share and email Notification: email, HTTP, HTTPS and TCP Video recording to edge storage Pre- and post-alarm video buffering External output activation, Audio recording to edge storage, Play audio clip Preset positions, Guard tour
Minimum illumination	Color: 0.2 lux, F1.2, B/W: 0.04 lux, F1.2	Data streaming
Shutter time	1/28000 s to 2 s	Event data
Camera angle adjustment	Pan 360°, Tilt 160°, Rotation 340°	Built-in installation aids
Video		Remote zoom, Remote focus, Pixel counter
Video compression	H.264 Baseline and Main Profile (MPEG-4 Part 10/AVC), Motion JPEG	General
Resolution	2592x1944 (5 MP) to 160x90	Casing
Frame rate	2 MP 4:3 (1600x1200) and HDTV 1080p (1920x1080) capture modes: 30 fps in all resolutions, 3 MP capture mode: 20 fps in all resolutions, 5 MP capture mode: 12 fps in all resolutions	Polycarbonate transparent dome, aluminum inner camera module with encapsulated electronics IK10 impact-resistant casing with aluminum base Color: White NCS S 1002-B. For repainting instructions and impact on warranty, contact your Axis partner.
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG, Controllable frame rate and bandwidth, VBR/MBR H.264	Mounting
Multi-view streaming	Up to 8 individually cropped out view areas When streaming 4 view areas and 1 overview in VGA resolution, the frame rate is 12 fps per stream (5 MP capture mode) or 20 fps per stream (3 MP capture mode)	¼"-20 UNC tripod screw thread
Pan/Tilt/Zoom	Digital PTZ Preset positions, Guard tour	Memory
Image settings	Compression, Color, Brightness, Sharpness, Contrast, White balance, Exposure control, Exposure zones, Fine tuning of behavior at low light, Text and image overlay, Mirroring of images, Privacy mask Rotation 0°, 90°, 180°, 270°, including Corridor Format Wide Dynamic Range - Dynamic Contrast	512 MB RAM, 128 MB Flash
Audio		Power
Audio streaming	Two-way audio	Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 2 Max 6.2 W
Audio compression	AAC LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Configurable bit rate	Connectors
Audio input/output	External microphone input or line input, Line output, Built-in microphone (can be disabled)	RJ45 10BASE-T/100BASE-TX PoE Terminal block for 1 alarm input and 1 output, 3.5 mm mic/line in, 3.5 mm line out
Network		Storage
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log	Support for SD/SDHC/SDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	Operating conditions
System integration		0 °C to 50 °C (32 °F to 122 °F) Humidity 10-85% RH (non-condensing)
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform, specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-click Connection ONVIF [®] Profile S and ONVIF [®] Profile G, specification at www.onvif.org	Storage conditions
Analytics	Included AXIS Video Motion Detection, active tampering alarm, audio detection Supported	-40 °C to 65 °C (-40 °F to 149 °F)
		Approvals
		EN 55022 Class B, EN 61000-6-1, EN 61000-6-2, EN 55024, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 22 Class B, KCC KN22 Class B, KN24, EN 50581, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-64, IEC 60068-2-78 IEC/EN/UL 60950-1 IEC 62262 IK10
		Weight
		730 g (1.6 lb)
		Dimensions
		Ø148 x 104 mm (Ø5 13/16 x 4 1/16 in)
		Included accessories
		Installation Guide, Windows decoder 1-user license, Resistorx ^R T20 L-key, Drill hole template Connector kit, Smoked dome
		Video management software
		AXIS Camera Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/support/downloads
		Languages
		English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
		Warranty
		Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty
		a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (http://www.openssl.org/), and cryptographic software written by Eric Young (ey@cryptsoft.com).</i>
		Environmental responsibility: www.axis.com/environmental-responsibility