

AXIS P3367-VE Network Camera

5-megapixel, light-sensitive with remote focus and zoom

AXIS P3367-VE is a fixed dome network camera that offers superb video performance in HDTV 1080p/5 MP resolution. It complies with the SMPTE 274M standard and can cover a large area with exceptional detail and light sensitivity. Wide dynamic range and day/night functionality provides high image quality even in low-light conditions. With multi-view streaming, the full view and up to 8 individually cropped out view areas can be streamed simultaneously. AXIS P3367-VE has support for digital pan/tilt/zoom, two-way audio, audio detection and input/output ports for external devices. With its weather-proof and vandal-resistant casing, it is perfectly adapted for harsh environments.

- > **HDTV 1080p/5 MP**
- > **P-Iris control**
- > **Remote zoom and focus**
- > **I/O ports and two-way audio**
- > **Outdoor-ready and IK10 vandal-resistance**



AXIS P3367-VE Network Camera

| | | | |
|--|--|--|--|
| Camera | | Event triggers | Analytics, edge storage events, external input |
| Image sensor | Progressive scan RGB CMOS 1/3.2" | Event actions | File upload: FTP, FTPS, HTTP, HTTPS, network share and email Notification: email, HTTP, HTTPS and TCP Video recording to edge storage Pre- and post-alarm video buffering External output activation, audio recording to edge storage, play audio clip Preset positions, guard tour |
| Lens | 3–9 mm, F1.2 Horizontal field of view: 84°–30° Vertical field of view: 63°–22° Varifocal, Remote focus and zoom, P-Iris control, IR corrected | Data streaming | Event data |
| Day and night | Automatically removable infrared-cut filter | Built-in installation aids | Remote zoom, remote focus, pixel counter |
| Minimum illumination | Color: 0.2 lux, F1.2, B/W: 0.04 lux, F1.2 | General | |
| Shutter time | 1/28000 s to 2 s | Casing | Polycarbonate transparent dome, aluminum inner camera module with encapsulated electronics IP66- and NEMA 4X-rated, IK10 impact-resistant casing with aluminum base and dehumidifying membrane Color: White NCS S 1002-B. For repainting instructions and impact on warranty, contact your Axis partner. |
| Camera angle adjustment | Pan 360°, Tilt 160°, Rotation 340° | Sustainability | PVC free |
| Video | | Mounting | Mounting bracket with junction box holes (double-gang, single-gang, 4" octagon and 4" square) ¼"-20 UNC tripod screw thread |
| Video compression | H.264 Baseline and Main Profile (MPEG-4 Part 10/AVC) Motion JPEG | Memory | 512 MB RAM, 128 MB Flash |
| Resolution | 2592x1944 (5 MP) to 160x90 | Power | Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 3 Max 12.1 W |
| Frame rate | 2 MP 4:3 (1600x1200) and HDTV 1080p (1920x1080) capture modes: 30 fps in all resolutions, 3 MP capture mode: 20 fps in all resolutions, 5 MP capture mode: 12 fps in all resolutions | Connectors | RJ45 10BASE-T/100BASE-TX PoE Terminal block for 1 alarm input and 1 output, 3.5 mm mic/line in, 3.5 mm line out |
| Video streaming | Multiple, individually configurable streams in H.264 and Motion JPEG Controllable frame rate and bandwidth VBR/MBR H.264 | Storage | Support for SD/SDHC/SDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com |
| Multi-view streaming | Up to 8 individually cropped out view areas When streaming 4 view areas and 1 overview in VGA resolution, the frame rate is 12 fps per stream (5 MP capture mode) or 20 fps per stream (3 MP capture mode) | Operating conditions | -40 °C to 55 °C (-40 °F to 131 °F) Humidity 10–100% RH (condensing) |
| Pan/Tilt/Zoom | Digital PTZ Preset positions, guard tour | Storage conditions | -40 °C to 65 °C (-40 °F to 149 °F) |
| Image settings | Compression, color, brightness, sharpness, contrast, white balance, exposure control, exposure zones, fine tuning of behavior at low light, text and image overlay, mirroring of images, privacy mask Rotation 0°, 90°, 180°, 270°, including Corridor Format Wide Dynamic Range – dynamic contrast | Approvals | EN 55022 Class B, EN 61000-6-1, EN 61000-6-2, EN 55024, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 22 Class B, KCC KN22 Class B, KN24, EN 50581, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-64, IEC 60068-2-78 EN 50121-4, IEC 62236-4, IEC/EN/UL 60950-22, IEC 62262 IK10, IEC/EN 60529 IP66, NEMA 250 Type 4X IS 13252 |
| Audio | | Weight | 1.7 kg (3.7 lb), with weathershield |
| Audio streaming | Two-way audio | Dimensions | Ø178 x 117 mm (Ø7 x 4 5/8 in) |
| Audio compression | AAC LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz Configurable bit rate | Included accessories | Installation Guide, Windows® decoder 1-user license, Resistorx® L-key, drill hole template Connector kit, mounting bracket, smoked dome, weather shield, 5 m (16 ft) network cable with pre-mounted gasket |
| Audio input/output | External microphone input or line input, Line output | Video management software | AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on axis.com/vms |
| Network | | Languages | English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese |
| Security | Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, digest authentication, user access log | Warranty | Axis 3-year warranty and AXIS Extended Warranty option, see axis.com/warranty |
| Supported protocols | IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, SFTP, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH | a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (http://www.openssl.org/), and cryptographic software written by Eric Young (ey@cryptsoft.com).</i> | |
| System integration | | Environmental responsibility: axis.com/environmental-responsibility | |
| Application Programming Interface | Open API for software integration, including VAPIX® and AXIS Camera Application Platform, specifications at axis.com AXIS Guardian with One-Click Connection ONVIF® Profile S and ONVIF® Profile G, specification at www.onvif.org | | |
| Analytics | Included AXIS Video Motion Detection, active tampering alarm, audio detection Supported AXIS Cross Line Detection, AXIS Perimeter Defender AXIS Digital Autotracking Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap | | |