

# AXIS P5655-E PTZ Network Camera

## HDTV 1080p PTZ with 32x zoom and focus recall

AXIS P5655-E PTZ Network Camera is a cost-effective, high performance PTZ with HDTV 1080p and 32x optical zoom. It features Forensic WDR for clarity even when there's both dark and light areas in the scene. And, Lightfinder 2.0 to capture low-light images with more saturated colors and sharper images of moving objects. It offers electronic image stabilization and enhanced security features including signed firmware and secure boot. With IP66, NEMA 4X and IK10 ratings it's resistant to both harsh weather conditions and impacts. Plus, you get two-way audio, I/O ports and extended capabilities for advanced analytics.

- > [HDTV 1080p with 32x optical zoom](#)
- > [Forensic WDR and Lightfinder 2.0](#)
- > [Signed firmware and secure boot](#)
- > [Focus recall and EIS](#)
- > [Zipstream with support for H.264 and H.265](#)



# AXIS P5655-E PTZ Network Camera

<b>Camera</b>	
<b>Image sensor</b>	1/2.8" progressive scan RGB CMOS
<b>Lens</b>	Varifocal, 4.3–137.6 mm, F1.4 – 4.0 Horizontal field of view: 58.3°– 2.4° Vertical field of view: 35.5°– 1.4° Including EIS, barrel and pincushion distortion correction Autofocus and auto-iris
<b>Day and night</b>	Automatically removable infrared-cut filter
<b>Minimum illumination</b>	Color: 0.1 lux at 30 IRE F1.4 B/W: 0.01 lux at 30 IRE F1.4
<b>Shutter speed</b>	1/66500 s to 2 s
<b>Pan/Tilt/Zoom</b>	Pan: 360° endless, 0.1°– 350°/s Tilt: 180°, 0.1°– 350°/s Zoom: 32x optical, 12x digital, Total 384x zoom 256 preset positions, nadir flip, limited guard tour, control queue, on-screen directional indicator, set new pan 0°, focus window, focus recall
<b>System on chip (SoC)</b>	
<b>Model</b>	ARTPEC-7
<b>Memory</b>	1024 MB RAM, 512 MB Flash
<b>Compute capabilities</b>	Machine learning processing unit (MLPU)
<b>Video</b>	
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG
<b>Resolution</b>	1920x1080 HDTV 1080p to 320x180
<b>Frame rate</b>	Up to 60/50 fps (60/50 Hz) in all resolutions
<b>Video streaming</b>	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Controllable frame rate and bandwidth Axis Zipstream technology in H.264 and H.265 VBR/ABR/MBR H.264/H.265
<b>Image settings</b>	Compression, saturation, brightness, sharpness, contrast, local contrast, white balance, exposure control, exposure zones, Forensic WDR: Up to 120 dB depending on scene, defogging, day/night shift level, tone mapping, fine tuning of low-light behavior, rotation: 0°, 180°, text and image overlay, image freeze on PTZ, electronic image stabilization, scene profiles, 20 individual polygon privacy masks
<b>Audio</b>	
<b>Audio streaming</b>	Two-way, full duplex
<b>Audio encoding</b>	24bit LPCM, AAC-LC 8/16/32/44.1/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz Configurable bit rate
<b>Audio input/output</b>	External microphone input or line input, line output (Requires Axis 10-pin Push-pull System Connector or Axis Multicable C I/O Audio Power 1 m/5 m, not included), automatic gain control
<b>Network</b>	
<b>Security</b>	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1X (EAP-TLS) <sup>a</sup> network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot
<b>Supported protocols</b>	IPv4, IPv6 USGv6, HTTP, HTTP/2, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP <sup>®</sup> , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SOCKS, SSH, NTCIP, LLDP, CDP, MQTT v3.1.1, Syslog
<b>System integration</b>	
<b>Application Programming Interface</b>	Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="http://axis.com">axis.com</a> One-click cloud connection ONVIF <sup>®</sup> Profile G, ONVIF <sup>®</sup> Profile S, and ONVIF <sup>®</sup> Profile T, specification at <a href="http://onvif.org">onvif.org</a>
<b>Event conditions</b>	Audio: Audio detection Device status: Above operating temperature, Above or below operating temperature, Below operating temperature, Fan failure, IP address removed, Network lost, New IP address, Shock detected, Storage failure, System ready, Within operating temperature, Edge storage, Recording ongoing, Storage disruption I/O: Digital input, Manual trigger, Virtual input PTZ: PTZ malfunctioning, PTZ movement: Camera 1, PTZ preset position reached: Camera 1, PTZ ready Scheduled and recurring: Scheduled event Video: Day-night mode, Live stream open
<b>Event actions</b>	Play audio clips, day-night mode, go to preset position, guard tour, I/O, upload of images or video clips via FTP, SFTP, HTTP, HTTPS, network share and email, notification to email, HTTP, HTTPS, TCP and SNMP trap, overlay text, prioritized text, record video to SD card and network share, WDR mode
<b>Data streaming</b>	Event data
<b>Built-in installation aids</b>	Pixel counter
<b>Analytics</b>	
<b>AXIS Object Analytics</b>	Object classes: humans, vehicles Trigger conditions: line crossing, object in area Up to 10 scenarios Metadata visualized with color-coded bounding boxes Polygon include/exclude areas Perspective configuration ONVIF Motion Alarm event
<b>Applications</b>	Included AXIS Object Analytics AXIS Video Motion Detection, audio detection, advanced gatekeeper, autotracker 2 Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://axis.com/acap">axis.com/acap</a>
<b>General</b>	
<b>Casing</b>	IP66-, NEMA 4X- and IK10-rated Aluminum casing, polycarbonate (PC) dome Color: white NCS S 1002-B, repaintable skin cover For repainting instructions of casing and impact on warranty, contact your Axis partner.
<b>Sustainability</b>	PVC free
<b>Power</b>	Axis PoE+ midspan 1-port: 100–240 V AC, max 37 W IEEE 802.3at, Type 2 Class 4 Camera consumption: typical 10.5 W, max 19 W Multiconnector: 20–28 V DC, typical 10 W, max 18 W 20–24 V AC, typical 15.5 V A, max 26 V A (PoE+ midspan or power supply not included)
<b>Connectors</b>	RJ45 10BASE-T/100BASE-TX PoE RJ45 push-pull connector (IP66) included I/O connector for DC or AC input, 4 configurable alarm Inputs/outputs: mic in/line in, line out (Axis 10-pin push-pull system connector or Axis multicable C I/O audio power 1 m/5 m, (not included))
<b>Storage</b>	Support for SD/SDHC/SDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Recording to network-attached storage (NAS) For SD card and NAS recommendations see <a href="http://axis.com">axis.com</a>
<b>Operating conditions</b>	–30 °C to 50 °C (–22 °F to 122 °F) Maximum intermittent temperature 55 °C Humidity 10–100% RH (condensing)
<b>Storage conditions</b>	–40 °C to 65 °C (–40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
<b>Approvals</b>	EMC EN 55032 Class A, EN 50121–4, IEC 62236–4, EN 61000–3–2, EN 61000–3–3, EN 55024, EN 61000–6–1, EN 61000–6–2, FCC Part 15 Subpart B Class A, ICES–003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KC KN32 Class A, KC KN35 Safety IEC/EN/UL 62368–1, IEC/EN/UL 60950–22, IS 13252 Environment IEC 60068–2–1, IEC 60068–2–2, IEC 60068–2–6, IEC 60068–2–14,

	IEC 60068-2-27, IEC 60068-2-30, EC 60068-2-78, IEC/EN 60529 IP66, IEC/EN 62262, IK10, NEMA 250 Type 4X <b>Network</b> NIST SP500-267, IPv6 USGv6	For more accessories, see <a href="http://axis.com">axis.com</a>
<b>Dimensions</b>	Height: 217 mm (8.54 in) ø 188 mm (7.4 in)	<b>Video management software</b> AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at <a href="http://axis.com/vms">axis.com/vms</a>
<b>Weight</b>	2.5 kg (5.5 lb)	<b>Languages</b> English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
<b>Included accessories</b>	RJ45 Push-pull Connector (IP66), hard ceiling mount, spring pipe adaptor, U-profile pipe adaptor, installation guide, Windows® decoder 1-user license	<b>Warranty</b> 5-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a>
<b>Optional accessories</b>	AXIS T91B mounts, AXIS T94A02L recessed mount, outdoor RJ45 cable with premounted connector, AXIS T8133 Midspan 30 W 1-port, repaintable skin covers, smoked dome, Axis 10-pin push-pull system connector, Axis multicable C I/O audio power 1 m/5 m	a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).</i>

Environmental responsibility:

[axis.com/environmental-responsibility](http://axis.com/environmental-responsibility)