

## AXIS Q1647-LE

5 MP video with 1/2" sensor and OptimizedIR

With AXIS Q1647-LE Network Camera it's easier than ever to capture everything. High resolution at full frame rate, i-CS lens and 1/2" sensor ensure outstanding details and sharp images. Even in challenging or low light scenes, Forensic WDR and Lightfinder ensure that details will be unveiled. The robust aluminum housing resists extreme temperatures, and comes with built-in IR LED illumination for surveillance in complete darkness. AXIS Q1647-LE enables proactive surveillance with pre-installed AXIS Guard Suite and orientation aid for quick orientation with multiple monitors. Zip-stream optimizes the video stream to maintain high video quality while saving bandwidth and storage.

- > **5 MP resolution at 25/30 fps**
- > **1/2" sensor**
- > **Forensic WDR and Lightfinder**
- > **Electronic image stabilization (EIS)**
- > **AXIS Motion Guard, AXIS Fence Guard and AXIS Loitering Guard**



# AXIS Q1647-LE

Camera	
<b>Image sensor</b>	1/2" progressive scan RGB CMOS
<b>Lens</b>	Varifocal, IR corrected, CS-mount 3.9–10.0 mm, F1.5 5.3 MP (16:9): Horizontal field of view: 92°–44° Vertical field of view: 50°–24° 4 MP (16:9): Horizontal field of view: 95°–38° Vertical field of view: 52°–21° 5 MP (4:3): Horizontal field of view: 81°–37° Vertical field of view: 60°–27° i-CS lens
<b>Day and night</b>	Automatically removable infrared-cut filter
<b>Minimum illumination</b>	5 MP 25/30 fps with WDR and Lightfinder: Color: 0.12 lux at 50 IRE, F1.5; B/W: 0.02 lux at 50 IRE, F1.5, 0 lux with IR illumination on 4 MP 50/60 fps: Color: 0.24 lux at 50 IRE, F1.5, B/W: 0.04 lux at 50 IRE, F1.5, 0 lux with IR illumination on
<b>Shutter time</b>	1/100000 to 2 s
<b>Pan/Tilt/Zoom</b>	Digital PTZ, uploadable PTZ driver (Pelco D pre-installed)
Video	
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC), Main, Baseline and High Profile Motion JPEG
<b>Resolution</b>	3072x1728 to 320x180
<b>Frame rate</b>	5 MP with WDR: 25/30 fps with power line frequency 50/60 Hz 4 MP without WDR: 50/60 fps with power line frequency 50/60 Hz
<b>Video streaming</b>	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264
<b>Image settings</b>	Saturation, contrast, brightness, sharpness, Forensic WDR – 120 dB, white balance, day/night threshold, exposure mode, exposure zones, compression, orientation: auto, 0°, 90°, 180°, 270°, mirroring of images, dynamic text overlay, image overlay, privacy masks, defogging, noise reduction, electronic image stabilization, barrel distortion correction, orientation aid, fine tuning of behavior at low light Scene profiles: forensic, vivid, traffic overview
Audio	
<b>Audio streaming</b>	Two-way
<b>Audio compression</b>	AAc-LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz Configurable bit rate
<b>Audio input/output</b>	External balanced/unbalanced microphone or line input, line output 24 bit AD/DA-conversion
Network	
<b>Security</b>	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1X <sup>a</sup> network access control, Digest authentication, User access log, Centralized Certificate Management, Brute force delay protection.
<b>Supported protocols</b>	IPv4, IPv6 USGv6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP <sup>TM</sup> , SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, SRTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, LLDP, CDP.
System integration	
<b>Application Programming Interface</b>	Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="http://axis.com">axis.com</a> AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile G, ONVIF Profile S and ONVIF Profile T, specifications at <a href="http://onvif.org">onvif.org</a>
<b>Analytics</b>	Included AXIS Video Motion Detection, AXIS Fence Guard, AXIS Motion Guard, AXIS Loitering Guard, active tampering alarm, audio detection

<b>Supported</b>	AXIS Digital Autotracking, AXIS Perimeter Defender Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://axis.com/acap">axis.com/acap</a>
<b>Event triggers</b>	Analytics, external input, edge storage events Detectors: live stream accessed, video motion detection, audio detection, shock detection Hardware: network, temperature Input Signal: manual trigger, virtual inputs PTZ: error, moving, preset reached, ready Storage: disruption, recording System: system ready Time: recurrence, use schedule
<b>Event actions</b>	File upload: FTP, SFTP, HTTP, HTTPS, network share and email, send video clip Notification: email, HTTP, HTTPS and TCP Overlay text, Send SNMP Trap Video and audio recording to edge storage Pre- and post-alarm video buffering External output activation, day/night vision mode, play audio clip, status LED, WDR mode, Defog mode, PTZ control
<b>Data streaming</b>	Event data
<b>Built-in installation aids</b>	i-CS: Remote zoom and focus Other lens: Remote back focus Traffic wizard, pixel counter, levelling assistant, autorotation
General	
<b>Casing</b>	IP66-, IP67-, NEMA 4X- and IK10-rated Metal (Aluminium) Color front: Black – NCS S 9000-N Color chassis: White – NCS S 1002-B
<b>Sustainability</b>	PVC free
<b>Memory</b>	1 GB RAM, 512 MB Flash
<b>Power</b>	Power over Ethernet (PoE) IEEE 802.3at Type 2 Class 4 Typical 12.3 W, max 25.5 W
<b>Connectors</b>	Shielded RJ45 10BASE-T/100BASE-TX PoE I/O: 6-pin 2.5 mm terminal block for four configurable inputs/outputs (12 V DC output, max load 50 mA) RS485/RS422, 2 pcs, 2 pos, full duplex, terminal block 3.5 mm mic/line in, 3.5 mm line out i-CS connector (compatible with P-Iris and DC-iris)
<b>IR illumination</b>	Optimized IR with power-efficient, long-life 850 nm IR LEDs Range of reach 30 m (98 ft) or more depending on the scene
<b>Storage</b>	Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see <a href="http://axis.com">axis.com</a>
<b>Operating conditions</b>	Arctic temperature control: Start-up at -40 °C to 60 °C (-40 °F to 140 °F) Humidity 10–100% RH (condensing)
<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F)
<b>Approvals</b>	EMC EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 50121-4, IEC 62236-4, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A Safety IEC/EN/UL 60950-22, IEC/EN/UL 62368-1 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP66/67, IEC/EN 62262 IK10, NEMA 250 Type 4X Network/NIST SP500-267 Other IEC 62471
<b>Dimensions</b>	178 x 206 x 494 mm (7 x 8.11 x 19.45 in)
<b>Weight</b>	6350 g (13.2 lb)

<b>Included accessories</b>	AXIS T94Q01A Wall Mount, AXIS T92G20 Outdoor Housing, connector kit, resistor <sup>x</sup> T20 tool, installation guide, Windows decoder 1-user license	<b>Languages</b>	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
<b>Optional accessories</b>	AXIS T90B Illuminators, Axis network cable couplers, AXIS T8129 PoE Extender, AXIS T8415 Wireless Installation Tool, Axis midspans For more accessories, see <a href="http://axis.com">axis.com</a>	<b>Warranty</b>	Axis 3-year warranty and AXIS Extended Warranty option, see <a href="http://axis.com/warranty">axis.com/warranty</a>
<b>Video management software</b>	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at <a href="http://axis.com/vms">axis.com/vms</a>		a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<a href="http://openssl.org">openssl.org</a>), and cryptographic software written by Eric Young (<a href="mailto:eyay@cryptsoft.com">eyay@cryptsoft.com</a>).</i>
		<b>Environmental responsibility:</b>	<a href="http://www.axis.com/environmental-responsibility">www.axis.com/environmental-responsibility</a>