

AXIS Q3527-LVE

5 MP dome with enhanced security features

AXIS Q3527-LVE Network Camera is a vandal-resistant fixed dome for harsh environments with enhanced security features. Signed firmware and secure boot ensure the integrity and authenticity of the camera's firmware, while a TPM provides secure storage of its certificates and cryptographic keys. Based on AXIS Q3517-LVE, the top-quality image sensor and advanced technologies such as Lightfinder and Forensic WDR ensures that AXIS Q3527-LVE delivers outstanding video quality in any light condition, even when the camera is subject to vibrations. AXIS Q3527-LVE also offers redundancy between PoE and DC power. Video analytics, supervised inputs, and digital outputs further support the surveillance task.

- > [TPM, FIPS 140-2 level 2 certified](#)
- > [Signed firmware](#)
- > [Secure boot](#)
- > [OptimizedIR and Zipstream](#)
- > [AXIS Guard Suite analytics](#)



AXIS Q3527-LVE

Camera	
Image sensor	Progressive scan RGB CMOS 1/1.8"
Lens	Varifocal, 4.3–8.6 mm, F1.5 Horizontal field of view: 96° – 50° Vertical field of view: 53° – 29° Remote focus and zoom, P-Iris control, IR-corrected
Day and night	Automatically removable infrared-cut filter
Minimum illumination	5MP 25/30 fps with WDR and Lightfinder: Color: 0.12 lux at 50 IRE, F1.5; B/W: 0.02 lux at 50 IRE, F1.5, 0 lux with IR illumination on 4MP 50/60 fps: Color: 0.24 lux at 50 IRE, F1.5, B/W; 0.04 lux at 50 IRE, F1.5, 0 lux with IR illumination on
Shutter time	1/71 500 s to 2 s
Camera angle adjustment	Pan: 360° Tilt: ±80° Rotation: ±175°
Video	
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG
Resolution	3072x1728 to 160x120
Frame rate	5MP with WDR: 25/30 fps with power line frequency 50/60 Hz 4MP without WDR: 50/60 fps with power line frequency 50/60 Hz
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/ABR/MBR H.264
Multi-view streaming	8 individually cropped-out view areas
Pan/Tilt/Zoom	Digital PTZ, Optical zoom, Preset positions
Image settings	Scene profiles, compression, color, brightness, sharpness, contrast, local contrast, white balance, day/night threshold, exposure control (including automatic gain control), defogging, exposure zones, fine tuning of behavior at different light levels, Forensic WDR: Up to 120 dB depending on scene, electronic image stabilization, barrel distortion correction, dynamic text and image overlay, privacy masks, mirroring of images, straighten image, rotation: 0°, 90°, 180°, 270°, auto, including corridor format
Audio	
Audio streaming	Full-duplex
Audio compression	24-bit LPCM 48 kHz, AAC LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8kHz, Opus 8/16/48 kHz Configurable bitrate
Audio input/output	Input for external microphone or line-level device Line output
Network	
Security	Password protection, IP address filtering, IEEE 802.1X (EAP-TLS) network access control ^a , HTTPS ^a encryption, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot, protection of cryptographic keys with FIPS 140-2 certified TPM 2.0 module
Supported protocols	IPv4, IPv6 USGv6, HTTP, HTTPS, SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, LLDP
System integration	
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com AXIS Guardian with One-Click Connection ONVIF Profile G, ONVIF Profile S and ONVIF Profile T, specification at onvif.org
Analytics	Included AXIS Video Motion Detection, AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard, active tampering alarm, audio detection

Supported	AXIS Perimeter Defender Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap
Event triggers	Analytics, supervised external inputs, virtual inputs through API, edge storage events, shock detection
Event actions	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap Overlay text, external output activation, play audio clip, zoom preset
Data streaming	Event data
Built-in installation aids	Remote zoom, remote focus, pixel counter, leveling assistant, autorotation, straighten image, traffic wizard
General	
Casing	IP66-, IP67-, IP6K9K- and NEMA 4X-rated, IK10+ (50 joules) impact-resistant casing with polycarbonate hard-coated dome, aluminum base and dehumidifying membrane Encapsulated electronics, captive screws Color: White NCS S 1002-B For repainting instructions of casing or skin cover and impact on warranty, contact your Axis partner.
Mounting	Mounting bracket with holes for junction boxes (double-gang, single-gang, 4" square, and 4" octagon) and for ceiling and wall mounting ¾" (M25) conduit side entry
Sustainability	PVC-free
Memory	1 GB RAM, 512 MB Flash
Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3, typical 6.5 W, max 12.9 W 8–28 V DC, typical 6.9 W, max 14.5 W Power redundancy
Connectors	RJ45 10BASE-T/100BASE-TX PoE, terminal block for two configurable supervised inputs / digital outputs (12 V DC output, max load 50 mA), 3.5 mm mic/line in, 3.5 mm line out, terminal block for DC input
IR illumination	OptimizedIR with power-efficient, long-life 850 nm IR LEDs Range 40 m (130 ft) or more, depending on the scene
Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Operating conditions	-50 °C to 60 °C (-58 °F to 140 °F) Start-up: -40 °C to 60 °C (-40 °F to 140 °F) Humidity 10–100% RH (condensing)
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
Approvals	EMC EN 55032 Class A, EN 50121-4, IEC 62236-4, EN 55024, IEC/EN 61000-6-1, IEC/EN 61000-6-2, FCC Part 15, Subpart B, Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 22 Class A, KCC KN32 Class A, KN35 Safety IEC/EN/UL 62368-1, IEC/EN/UL 60950-22, IEC/EN 62471, IS 13252 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78 NEMA 250 Type 4X, IEC/EN 62262 IK10+ (50J), ISO 20653 IP6K9K IEC/EN 60529 IP66/67 Network NIST SP500-267
Dimensions	Height: 182 mm including weathershield ø 183 mm
Weight	2.0 kg (4.4 lb) including weathershield

Included accessories	Installation Guide, Windows decoder 1-user license, drill hole template, cable gaskets, I/O and DC connectors, connector guard, weathershield, Axis U-shape conduit adapter, Resistorx® T20 L-key, mounting bracket	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Optional accessories	AXIS Q35 Smoked Dome A, AXIS Dome Intrusion Switch B, AXIS Multicable B I/O Audio Power AXIS Q35-VE Skin Cover A Black, AXIS ACI Conduit Adapter 3/4" NPS, AXIS T94M01D Pendant Kit including weathershield, AXIS T94M02L Recessed Mount, AXIS T8351 Microphone, Axis Mounts Et Cabinets For more accessories, see axis.com	Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see axis.com/warranty
Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available at axis.com/vms		a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).</i>

Environmental responsibility:

axis.com/environmental-responsibility