

AXIS Q6054 Mk II PTZ Network Camera

Indoor PTZ with 30x zoom and focus recall and Lightfinder

AXIS Q6054 Mk II is a top-of-the-line, indoor PTZ camera, offering fast and precise pan/tilt performance for wide area coverage and detailed surveillance at great distances. The focus recall feature offers instant focus in predefined areas. The camera comes with Axis Lightfinder technology to ensure color images even in low-light conditions. Axis Zipstream technology reduces bandwidth and storage requirements. AXIS Q6054 Mk II offers shock detection, video motion detection, Active Gatekeeper, and electronic image stabilization that gives smoother video in environments with vibrations. It supports two-way audio, audio detection, I/O ports, and 24 V AC/DC power.

- > [Lightfinder](#)
- > [HDTV 720p and 30x optical zoom](#)
- > [Focus recall](#)
- > [Zipstream](#)
- > [IP52-rated protection against dust and dripping water](#)



AXIS Q6054 Mk II PTZ Network Camera

Models	AXIS Q6054 Mk II 60 Hz AXIS Q6054 Mk II 50 Hz	Hardware: fan, network, temperature PTZ: autotracking, error, moving, preset reached, ready Storage: disruption, recording System: system ready Time: recurrence, use schedule Input signal: manual trigger, virtual input, digital input
Camera		
Image sensor	1/3" progressive scan RGB CMOS	
Lens	4.4–132 mm, F1.4–4.6 Horizontal field of view: 58.1°–2.4° Vertical field of view: 33.8°–1.3° Autofocus, auto-iris	
Day and night	Automatically removable infrared-cut filter	
Minimum illumination	Color: 0.15 lux at 30 IRE F1.4 B/W: 0.03 lux at 30 IRE F1.4 Color: 0.2 lux at 50 IRE F1.4 B/W: 0.04 lux at 50 IRE F1.4	
Shutter time	1/30000 s to 1/0.75 s with 50 Hz 1/30000 s to 1 s with 60 Hz	
Pan/Tilt/Zoom	Pan: 360° endless, 0.05°–450°/s Tilt: 180°, 0.05°–450°/s 30x optical zoom and 12x digital zoom, total 360x zoom E-flip, 256 preset positions, tour recording (max 10, max duration 16 minutes each), guard tour (max 100), control queue, on-screen directional indicator, adjustable zoom speed	
Video		
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	
Resolution	HDTV 720p 1280x720 to 320x180	
Frame rate	Up to 50/60 fps (50/60 Hz) in all resolutions	
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264	
Image settings	Manual shutter time, compression, color, brightness, sharpness, white balance, exposure control, exposure zones, fine tuning of behavior at low light, rotation: 0°, 180°, text and image overlay, 32 individual 3D privacy masks, image freeze on PTZ, automatic defog, backlight compensation, scene profiles, focus recall Electronic Image Stabilization (EIS) Wide Dynamic Range (WDR): Up to 110 dB depending on scene	
Audio		
Audio streaming	Two-way: full duplex, half duplex, simplex	
Audio compression	AAC-LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz Configurable bit rate	
Audio input/output	Requires multicable (sold separately) for external microphone or line input, and line output	
Network		
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log, Centralized Certificate Management, Brute force delay protection	
Supported protocols	IPv4, IPv6 USGv6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, NTCIP	
System integration		
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF [®] Profile S and ONVIF [®] Profile G, specification at www.onvif.org	
Analytics	Included AXIS Video Motion Detection, audio detection, AXIS Fence Guard, AXIS Motion Guard Supported Support for AXIS Camera Application Platform enabling installation of third-party applications, see www.axis.com/acap	
Event triggers	Detectors: live stream accessed, video motion detection, shock detection, audio detection	
Event actions	Day/night mode, overlay text, video recording to edge storage, pre- and post-alarm video buffering, send SNMP trap PTZ: PTZ preset, start/stop guard tour File upload via FTP, SFTP, HTTP, HTTPS network share and email Notification via email, HTTP, HTTPS and TCP External output activation, audio recording to edge storage, play audio clip	
Data streaming	Event data	
Built-in installation aids	Pixel counter	
General		
Casing	IP52-rated Metal casing (aluminum), Acrylic (PMMA) clear dome	
Sustainability	PVC free	
Memory	512 MB RAM, 256 MB Flash	
Power	Axis PoE+ midspan 1-port: 100–240 V AC, max 37 W IEEE 802.3at Type 2 Class 4 Camera consumption: typical 13 W, max 19 W Multiconnector: 20–28 V DC, typical 11 W, max 16 W 20–24 V AC, typical 17 VA, max 22 VA	
Connectors	RJ45 10BASE-T/100BASE-TX PoE, multiconnector (cable sold separately) for AC/DC power, 4 configurable alarm inputs/outputs, mic in, line mono input, line mono output to active speaker	
Storage	Support for SD/SDHC/SDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com	
Operating conditions	0 °C to 50 °C (32 °F to 122 °F) Humidity 10–85% RH (non-condensing)	
Storage conditions	–40 °C to 65 °C (–40 °F to 149 °F)	
Approvals	EMC EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, EN 55024, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 22 Class A, KCC KN32 Class A, KN35 Safety IEC/EN/UL 60950-1 Environment IEC/EN 60529 IP52, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78 Network NIST SP500-267 Midspan: EN 60950-1, GS, UL, cUL, CE, FCC, VCCI, CB, KCC, UL-AR	
Weight	Camera: 2.6 kg (5.7 lb); with drop-ceiling mount: 3.2 kg (7.1 lb)	
Dimensions	Hard-ceiling: Ø198 x 240 mm (Ø7 13/16 x 9 7/16 in) Drop-ceiling: Ø248 x 243 mm (Ø9 3/4 x 9 9/16 in)	
Included accessories	Axis PoE+ midspan 1-port, Recessed mount for hard and drop ceilings, Smoked dome cover Installation Guide, Windows decoder 1-user license	
Optional accessories	AXIS P55/Q60 Multi-connector cable, 5 m AXIS T91 Mounting Accessories, AXIS T8415 Wireless Installation Tool, AXIS T90 Illuminators, AXIS T8310 Video Surveillance Control Board, multi-user decoder license pack	
Video management software	AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/vms	
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese	
Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty	

- a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).*

Environmental responsibility:

axis.com/environmental-responsibility