

## AXIS S1032 Mk II Recorder

Out-of-the box ready server for high-definition surveillance

AXIS Camera Station S1032 Recorder is an out-of-the-box ready rack server validated for reliable high-definition surveillance up to 4K. It is preloaded with AXIS Camera Station video management software with universal licenses for 32 channels and other necessary system software. It is preconfigured to minimize installation time. AXIS S1032 has validated hardware components, redundant hard disks and power supplies and includes three-year hardware warranty with on-site replacement service. AXIS Camera Station offers an intuitive user interface and allows users to take full advantage of Axis' wide range of video surveillance cameras and other IP products. It also supports integration of third party IP cameras.

- > **Ease of installation**
- > **Validated with extensive support**
- > **High-definition surveillance up to 4K**
- > **AXIS Camera Station included**
- > **Full compatibility with Axis' products**



## AXIS S1032 Mk II Recorder

<b>Licenses</b>	32 AXIS Camera Station universal licenses included, can be upgraded up to 48 licenses (sold separately)	<b>Operating conditions</b>	5 °C to 40 °C (41 °F to 104°F)
<b>Processor</b>	Intel® Xeon® E3-1220 v5, 3.0GHz, 8MB Cache, 4C/4T, turbo (80W)	<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F)
<b>Memory</b>	UDIMM 2133 MT/s, ECC, 2x4GB (8192MB)	<b>Approvals</b>	EN/IEC/UL 60950-1, FCC part 15, class A, VCCI class A, EN 55022, class A, ICES-003/NMB-003 Class A, KCC KN22 Class A, KN-24, EN 55024, EN/IEC 61000-3-2, EN/IEC 61000-3-3
<b>Storage</b>	16 TB (4x4 TB) Enterprise Class HDD (12 TB usable space after RAID), 7200 rpm, SATA 6Gb/s, RAID 5 RAID Controller: PERC H730, 1GB NV Cache	<b>Dimensions</b>	43 x 483 x 610 mm (1.69 x 19 x 24 in), 1U Chassi
<b>Operating system</b>	Microsoft Windows 10 IoT Enterprise	<b>Weight</b>	14 kg (31 lb)
<b>Video streaming</b>	Not intended for local viewing of video. Recommended to use AXIS S9001 or AXIS S9002.	<b>Included accessories</b>	Installation guide, Power cords for rack mounting
<b>Recording</b>	Qualified for recording up to 48 video channels with a total recording rate up to 384 Mbit per second.	<b>Optional accessories</b>	AXIS T8310 Video Surveillance Control Board AXIS P8221 I/O Audio Module AXIS A1001 Network Door Controller AXIS Camera Station S9001 MkII Desktop Terminal AXIS Camera Station S9002 Desktop Terminal
<b>General</b>		<b>Warranty</b>	Axis 3-year warranty, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>
<b>Power</b>	Max 350 W, 100 V AC to 240 V AC		
<b>Connectors</b>	1xUSB 2.0, 2xUSB 3.0, 2xVGA, Serial port (DB9), 2xEthernet (RJ45), 2xPower inlet		

## AXIS Camera Station

For details about AXIS Camera Station features and functions please see Data Sheet on [www.axis.com](http://www.axis.com)

Environmental responsibility:  
[www.axis.com/environmental-responsibility](http://www.axis.com/environmental-responsibility)