

# AXIS S9001 Mk II Desktop Terminal

## Effective surveillance for server installations

AXIS Camera Station S9001 is a compact and an easy-to-install desktop terminal for high-definition surveillance. The terminal is preloaded with an AXIS Camera Station client and all necessary software and it is preconfigured to minimize installation time. AXIS S9001 complements AXIS S1032 or AXIS S1048 rack servers to create a high performing surveillance workstation. The terminal has validated hardware components, such as graphic card and CPUs. The product includes three-year hardware warranty with on-site replacement service. AXIS S9001 supports two monitors for system overview. A keyboard and computer mouse are included.

- > **Ease of installation**
- > **AXIS Camera Station client included**
- > **Validated hardware**
- > **High-definition surveillance up to 4K**
- > **Extensive support**



## AXIS S9001 Mk II Desktop Terminal

<b>Processor</b>	Intel® i5 4570S, Quad Core, 2.90 GHz Turbo, 6MB	<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F)
<b>Memory</b>	8GB (2x4GB) 1600 MHz DDR3	<b>Approvals</b>	EN/IEC/UL 60950-1, FCC part 15, class B, VCCI V-3, VCCI V-4, AS/NZS CISPR 22, class B, ICES-003/NMB-003, KCC KN22 Class B, KN-24, EN 62311, EN 55022, EN 55024, EN/IEC 61000-3-2, EN/IEC 61000-3-3, EN 300 328, EN 301 893, EN 301 489-1, EN 301 489-17
<b>Storage</b>	500 GB, 7200 rpm HDD with 64 MB cache and SATA 6Gb/s interface Not intended for local storage of video. Recommended to use AXIS S1032 or AXIS S1048.	<b>Dimensions</b>	290 x 93 x 312 mm (11.4 x 3.66 x 12.28 in)
<b>Graphic card</b>	AMD Radeon R5 340X 2 GB 2 monitors supported	<b>Weight</b>	5.3 kg (17.6 lb)
<b>Operating system</b>	Microsoft Windows 10 IoT Enterprise	<b>Included accessories</b>	Installation guide, Keyboard (International/US), Computer mouse, Power cable
<b>Video streaming</b>	<b>Live view:</b> Up to 25 camera split views or 1 x 4K camera view <b>Playback:</b> 4 x 1080p camera split views or 1 x 4K camera view	<b>Optional accessories</b>	AXIS T8310 Video Surveillance Control Board AXIS P8221 I/O Audio Module AXIS A1001 Network Door Controller
<b>General</b>		<b>Warranty</b>	Axis 3-year warranty, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>
<b>Power</b>	Max 315 W, 100 V AC to 240 V AC		
<b>Connectors</b>	6xUSB 2.0, 4xUSB 3.0, 1xDisplay Port, 1xDual link DVI-I Ethernet LAN 10/100/1000 Mbit, Line-in/out connectors, Computer mouse and keyboard connectors		
<b>Operating conditions</b>	5 °C to 45 °C (41 °F to 113°F)		

## AXIS Camera Station

For details about AXIS Camera Station features and functions please see Data Sheet on [www.axis.com](http://www.axis.com)

Environmental responsibility:  
[www.axis.com/environmental-responsibility](http://www.axis.com/environmental-responsibility)