

AXIS S9002 Desktop Terminal

Effective 4K surveillance for server installations

AXIS Camera Station S9002 is an easy-to-install desktop terminal for high-definition surveillance with support for three simultaneous 4K streams. The terminal is preloaded with an AXIS Camera Station client and all necessary software and it is preconfigured to minimize installation time. AXIS S9002 complements AXIS S1032 or AXIS S1048 rack servers to create a high-end surveillance workstation. The terminal has validated hardware components, such as graphic card and CPUs. The product includes three-year hardware warranty with on-site replacement service. AXIS S9002 supports four monitors for optimal system overview. A keyboard and computer mouse are included.

- > **Ease of installation**
- > **AXIS Camera Station client included**
- > **Validated high performing hardware**
- > **High-definition surveillance up to three 4K streams**
- > **Extensive support**



AXIS S9002 Desktop Terminal

Processor	Intel® i5 4570S, Quad Core, 2.90 GHz Turbo, 6MB	Operating conditions	5 °C to 45 °C (41 °F to 113°F)
Memory	DDR5 RDIMM PC4-2133MHz 2x4GB (8192MB), Dual Rank, x8 Data Width	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Storage	500 GB, 7200 rpm HDD with 64 MB cache and SATA 6Gb/s interface Not intended for local storage of video. Recommended to use AXIS S1032 or AXIS S1048.	Approvals	EN/IEC/UL 60950-1, FCC part 15, class B, VCCI V-3, VCCI V-4, AS/NZS CISPR 22, class B, ICES-003/NMB-003, KCC KN22 Class B, KN-24, EN 62311, EN 55022, EN 55024, EN/IEC 61000-3-2, EN/IEC 61000-3-3, EN 300 328, EN 301 893, EN 301 489-1, EN 301 489-17
Graphic card	Nvidia Quadro K1200 4GB GDDR5 4 monitors supported	Dimensions	360 x 175 x 417 mm (14.17 x 6.89 x 16.42 in)
Operating system	Microsoft Windows 10 IoT Enterprise	Weight	8.0 kg (17.6 lb)
Video streaming	Live view: Up to 25 camera split view or 3 x 4K camera view Playback: 9 x 1080p camera split views or 3 x 4K camera views	Included accessories	Installation guide, Keyboard (International/US), Computer mouse, Power cable, 4x mini Display Port to Display Port adapter
General			
Power	Max 365 W, 100 V AC to 240 V AC	Optional accessories	AXIS T8310 Video Surveillance Control Board AXIS P8221 I/O Audio Module AXIS A1001 Network Door Controller
Connectors	6xUSB 2.0, 4xUSB 3.0, 4xMini Display Port, 1xVGA, 1xDual link DVI-I Ethernet LAN 10/100/1000 Mbit, Line-in/out connectors, Computer mouse and keyboard connectors	Warranty	Axis 3-year warranty, see www.axis.com/warranty

AXIS Camera Station

For details about AXIS Camera Station features and functions please see Data Sheet on www.axis.com

Environmental responsibility:
www.axis.com/environmental-responsibility