

## AXIS Surveillance microSDXC™ Card 64 GB

Reliable edge storage for video surveillance.

AXIS Surveillance microSDXC™ Card 64 GB is a high performing edge storage solution optimized for video surveillance applications. Edge storage, supported in most Axis network video products, allows for flexible storage solutions. Useful in 1-4 channel systems, it offers de-centralized video recording and eliminates the need of an onsite server, DVR or NVR. It also offers redundancy for failover recording should connection with a central server be lost. In applications with bandwidth limitations, live video can be viewed in low resolution, while HDTV quality images are recorded locally on the card. AXIS Surveillance microSDXC™ Card 64 GB is delivered with a SD™ card adapter and supported by Axis 3-year warranty.

- > [Optimized for surveillance cameras](#)
- > [Compatible with Axis products with edge storage](#)
- > [Axis 3-year warranty](#)



## AXIS Surveillance microSDXC™ Card 64 GB

SD card		Approvals
<b>Form factor</b>	microSDXC™ with SD™ card adapter <sup>a</sup>	EN 55022 Class B, EN 55024, FCC Part 15 Subpart B Class B, ICES-003 Class B, C-tick AS/NZS CISPR 22 Class B
<b>Casing</b>	The microSDXC™ card and SD™ card adapter are delivered in a jewel case	<b>Compatibility</b> Compatible with all microSD, microSDHC, microSDXC and supporting host devices with SD, SDHC, SDXC
<b>Color</b>	White	<b>Warranty</b> Axis 3-year warranty, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>
<b>Capacity</b>	64 GB	a. <i>SanDisk is a trademark of SanDisk Corporation, registered in the United States and other countries. microSDXC and SD marks and logos are trademarks of SD-3C, LLC.</i>
<b>Class</b>	Class 10	More information is available at <a href="http://www.axis.com">www.axis.com</a>
<b>Transfer speed read/write</b>	20 MB/s read/write	
<b>Card dimensions</b>	microSDXC™ card: 15 mm x 11 mm x 1.0 mm (0.59 in x 0.43 in x 0.04 in) SD™ adapter: 24 mm x 32 mm x 2.1 mm (0.94 in x 1.26 in x 0.08 in)	
<b>Operating conditions</b>	-25 °C to 85 °C (-13 °F to 185 °F)	
<b>Storage conditions</b>	-40 °C to 85 °C (-40 °F to 185 °F)	