

# AXIS T8342 Door/Window Sensor

## Wireless door/window sensor

AXIS T8342 Door/Window Sensor enables the triggering of events such as notification messages, illumination, and much more, when the door or window is opened. By communicating wirelessly with AXIS M5065 PTZ Network Camera or connected Z-Wave Plus<sup>®</sup> controllers, the door/window sensor can be used in small security solutions with less cabling. The wireless I/O connectivity also enables flexible installation as the sensor can easily be mounted on a door, window, or cabinet according to your needs.

- > **Wireless I/O connectivity**
- > **Z-Wave Plus<sup>®</sup> compatibility**
- > **S2 security compliant**
- > **Battery included**



## AXIS T8342 Door/Window Sensor

<b>Supported products</b>	AXIS M5065 PTZ Network Camera Compatible with other Z-Wave Plus® control devices	<b>Storage conditions</b>	-20 °C to 60 °C (-4 °F to 140 °F)
<b>Network</b>		<b>Approvals</b>	EMC FCC Part 15 Subpart C, ICES-003 Class B, VCCI Class B
<b>Supported protocols</b>	Z-Wave Plus®. For more information on the supported command classes, see the product's User Manual	<b>Dimensions</b>	Sensor: 31 x 15 x 70 mm (1.22 x 0.59 x 2.76 in) Magnet: 11 x 15 x 70 mm (0.43 x 0.59 x 2.76 in)
<b>General</b>		<b>Weight</b>	38 g (0.08 lbs)
<b>Casing</b>	Plastic Color: white	<b>Included accessories</b>	Installation guide, mounting kit, 2 x CR2450 3.0 V Lithium battery
<b>Sustainability</b>	PVC free	<b>Warranty</b>	Axis 3-year warranty, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>
<b>Power</b>	2 x CR2450 3.0 V Lithium battery Battery life: 1 year	<b>Environmental responsibility:</b> <a href="http://www.axis.com/environmental-responsibility">www.axis.com/environmental-responsibility</a>	
<b>Distance</b>	Transmitting range up to 100 meters (328 ft)		
<b>Frequency</b>	908.42 MHz (US), 922.5 MHz (JP)		
<b>Operating conditions</b>	-10 °C to 40 °C (14 °F to 104 °F)		