

AXIS T8343 Alert Button

Wireless alert button

AXIS T8343 Alert Button is a push button which relays events such as notification messages, illumination, and much more. By communicating wirelessly with AXIS M5065 PTZ Network Camera or connected Z-Wave Plus[®] controllers, the alert button can be used in small security solutions with less cabling. The wireless I/O connectivity also enables flexible installation as the relay can easily be moved and adapted to your needs.

- > **Wireless I/O connectivity**
- > **Z-Wave Plus[®] compatibility**
- > **S2 security compliant**
- > **Battery included**



AXIS T8343 Alert Button

| | | | |
|-----------------------------|--|-----------------------------|--|
| Supported products | AXIS M5065 PTZ Network Camera Compatible with other Z-Wave Plus® control devices | Approvals | EMC FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, EN 301 489-1 V2.1.1, EN 301 489-13 V2.1.1 |
| Network | | Radio | EN 300 220-2 v3.1.1, EN 300 220-2 V3.1.1 |
| Supported protocols | Z-Wave Plus®. For more information on the supported command classes, see the product's User Manual | Safety | EN 62368-1:2014 |
| General | | Dimensions | 80 x 80 x 18 mm (3.15 x 3.15 x 0.71 in) |
| Casing | Plastic Color: white | Weight | 76 g (0.16 lbs) |
| Power | 2 x AAA 1.5 V Alkaline battery Battery life: 1 year ^a | Included accessories | Installation guide, mounting kit, 2 x AAA 1.5 V Alkaline battery |
| Distance | Transmitting range up to 100 meters (328 ft) | Warranty | 3-year warranty, see axis.com/warranty |
| Frequency | 908.42 MHz (US), 922.5 MHz (JP), 868.42 MHz (EU) | | |
| Operating conditions | -10 °C to 40 °C (14 °F to 104 °F) | | |
| Storage conditions | -20 °C to 60 °C (-4 °F to 140 °F) | | |

a. Measured at 1 trigger per day.

Environmental responsibility:

axis.com/environmental-responsibility