

## AXIS T91G61 Wall Mount

### Quick connection and room for more

Designed for PTZ and multi-sensor cameras, AXIS T91G61 Wall Mount accommodates and safely protects accessories inside the mount. Quickly and easily, connect power and data via pre-mounted Ethernet cable with IP66 RJ45 connector. Thanks to its impact-resistant and outdoor proven material, the mount suits all environments, both indoors and outdoors. AXIS T91G61 has the same hole pattern as the standard Axis PTZ wall mount and for retrofit, a pattern that matches Pelco's PTZ camera mount to enable an easy switch - no additional drilling is required. It can be mounted on poles and corners with the help of optional accessories.

- > **Room for connectivity devices, midspans (not included) and service loop**
- > **Protection against impacts, water, dust and corrosion**
- > **Pre-mounted IP66 RJ45 connector**
- > **Re-use existing holes**



## AXIS T91G61 Wall Mount

General		Included accessories
<b>Supported products</b>	AXIS Q3709-PVE AXIS Q6000-E Series AXIS P56 Series AXIS Q60 Series AXIS Q61 Series	Installation guide Ethernet cable with IP66 RJ45 connector (with gasket) Foam gaskets and silicone strap (pre-mounted) Connector plug angle C13
<b>Casing</b>	Powder coated aluminum casing Color: white NCS S 1002-B	<b>Optional accessories</b>
<b>Dimensions</b>	185 x 214 x 404 mm (7.28 x 8.43 x 15.9 in)	AXIS T81B22 DC 30 W Midspan 1-port <sup>a</sup> AXIS T8133 30 W Midspan <sup>a</sup> AXIS T8134 60 W Midspan <sup>a</sup> AXIS T8154 60 W SFP Midspan <sup>a</sup> AXIS T8642 PoE+ over Coax Device AXIS T91A57 Pole Mount AXIS T91A64 Corner Mount AXIS ACI Conduit Adapters Network cable coupler indoor slim For more accessories, see <a href="http://www.axis.com">www.axis.com</a>
<b>Weight</b>	3.5 kg (7.7 lb)	<b>Warranty</b>
<b>Maximum load</b>	30 kg (66 lb)	Axis 3-year warranty, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>
<b>Cable routing</b>	Back: cable hole Bottom: 3/4" Conduit entrance x2	a. <i>Midspan not included</i>
<b>Environment</b>	Indoor Outdoor	Environmental responsibility: <a href="http://axis.com/environmental-responsibility">axis.com/environmental-responsibility</a>
<b>Approvals</b>	<b>Safety</b> IEC/EN/UL 60950-1, IEC/EN/UL 60950-22 <b>Environment</b> IEC/EN 60529 IP66, IEC 62262 IK10, IEC 60068-2-6 (Sinus), IEC 60068-2-27 (Shock), NEMA 250 Type 4X, UL 50E, MIL-STD 810G 509.5, RoHS	