

AXIS T94Q01A and AXIS T94R01P Mounts

Wall mount and conduit back box for Axis housings



- > Impact resistant
- > Protection against water, dust and corrosion
- > Compatible with Axis Housings
- > Ease of installation

AXIS T94Q01A Wall Mount is a robust and flexible mount compatible with Axis Fixed Housings. AXIS T94R01P Conduit Back Box increases mounting possibilities and enables the use of cable protection products.

When using the back box together with the wall mount, the Ethernet cable can be routed through or along the wall (from the left or right). The side-hole in AXIS T94R01P is compatible with 3/4" conduits, M25 cable protection products and the Axis Conduit Interface (ACI) adapter range.

Made of powder-coated aluminum, AXIS T94Q01A Wall Mount is corrosion resistant according to NEMA 4X rat-

ing. Supporting IK10 rating, the wall mount offers protection against impact and vandal acts.

AXIS T94R01P Conduit Back Box can also be used to cover a single gang junction box.

The wall mount is included with AXIS T93F Housing Series and available as accessory for other fixed housings.



Technical Specifications – AXIS T94Q01A/T94R01P

	AXIS T94Q01A Wall Mount	AXIS T94R01P Conduit Back Box
Mount support/ Compatible with	AXIS T94R01P Conduit back Box, VT corner mount WCWA, AXIS T98A16-VE Surveillance Cabinet, AXIS T91A47 Pole Mount, AXIS T92E Series, AXIS T93E05, AXIS T93F Series, AXIS P13-E, AXIS Q16-E, AXIS Q1755-E, AXIS Q1910-E/Q1921-E/Q1922-E	AXIS T94Q01A Wall Mount, VT Wall bracket Internal Cable WBOVA1, AXIS T92E Series, AXIS T93E05, AXIS T93F Series, AXIS P13-E, AXIS Q16-E, AXIS Q1755-E, AXIS Q1910-E/Q1921-E/Q1922-E
Maximum load	7 kg (15.4 lb)	8 kg (17.6 lb)
Angle	Tilt: +25° to - 65° Pan: +100° to -100°	
Cable routing	Internal	Back: Cable hole Side: Conduit hole M25 (3/4 in)
Environment	Indoor/Outdoor	Indoor/Outdoor
Material	Powder coated, Chromate aluminum Color: White NCS S 1002-B Stainless steel screws (captiv)	Powder coated, Chromate aluminum Color: White NCS S 1002-B Stainless steel screws
Compliance	RoHS, REACH, CE	RoHS, REACH, CE
Approvals	IEC/EN/UL 60950-1, IEC/EN/UL 60950-22, EN 50581, IEC 62262 IK10, NEMA 250 Type 4X* *Corrosion protected only	IEC/EN/UL 60950-1, IEC/EN/UL 60950-22, EN 50581, IEC 62262 IK10, NEMA 250 Type 4X* *Corrosion protected only
Weight	650 g (1.4 lb)	550 g (1.2 lb)
Included accessories	Installation Guide	Installation Guide
Required accessories	Torx 30 Bit (required)	Torx 30 Bit (required)
Warranty	Axis 3-year warranty, see www.axis.com/warranty	Axis 3-year warranty, see www.axis.com/warranty

Optional accessories

AXIS T94Q01A

1. AXIS T94R01P
Conduit Back Box

2. AXIS T98A16-VE
Surveillance
Cabinet

3. AXIS T91A47
Pole Mount

4. VT Corner Mount
WCWA

AXIS T94R01P

5. Axis Conduit
Interface (ACI)



Dimensions

1. AXIS T94Q01A

2. AXIS T94R01P

