

## AXIS T96B05 Outdoor Housing

AXIS T96B05 Outdoor Housing enables mounting of AXIS P39 Series network cameras outside of vehicles and rolling stock, such as buses, trams and emergency vehicles. The enclosure is PVC-free, and made of impact-resistant polymer and aluminum base plate. AXIS T96B05 complies with strict regulatory demands of the transportation industry.

- > Enclosure for mounting onboard cameras outside vehicles and rolling stock
- > Compliant to IP66/IP67, IP6K9K, NEMA 250 Type 4X and IK09
- > Operating temperature -40 °C to 60 °C (-40 °F to 140 °F)



## AXIS T96B05 Outdoor Housing

<b>Supported products</b>	AXIS P3904-R Mk II Network Camera and AXIS P3905-R Mk II Network Camera with 3.6 mm, 6 mm and 8 mm lenses	<b>EMC</b> EN 55032 Class A, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, EN 50121-4, EN 50121-3-2, IEC 62236-4, ECE R10 rev.05 (E approval), EN 50498
<b>Lens</b>	<b>Maximum horizontal field of view<sup>a</sup></b> 87° with 3.6 mm M12 lens 52° with 6 mm M12 lens 40° with 8 mm M12 lens	<b>Safety</b> IEC/EN 62368-1, IEC/EN 60950-22 (CB certificate), EN 45545
<b>Camera angle adjustment</b>	<b>With 3.6 mm M12 lens</b> Pan: 0° Tilt: 0° <b>With 6 mm M12 lens</b> Pan: ±20° Tilt: 0°–15° Rotation: ±175° <b>With 8 mm M12 lens</b> Pan: ±30° Tilt: 0°–15° Rotation: ±175°	<b>Environment</b> IEC/EN 61373 Category 1 Class B, IEC 60529 IP66/IP67, NEMA 250 Type 4X, IEC/EN 62262 IK09, ISO 20653 IP6K9K, EN 50155:2017 Class OT2/ST2 (EN 50155:2007 Class TX), IEC 60721-3-5 Class 5M3 (vibration and shock), IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-27, IEC 60068-2-64, IEC 60068-2-78
<b>General</b>		<b>Dimensions</b>
<b>Casing</b>	IP66/IP67, IP6K9K, NEMA 4X-rated, IK09 impact resistant aluminum and polymer enclosure Color: white NCS S 1002-B	Height: 56 mm (2 1/4 in) ø 150 mm (5 7/8 in)
<b>Sustainability</b>	PVC free	<b>Weight</b>
<b>Operating conditions</b>	-40 °C to 60 °C (-40 °F to 140 °F) Humidity: 10–100% RH (condensing)	540 g (1.2 lb) with AXIS P39 Series network camera
<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F)	<b>Included accessories</b>
<b>Approvals</b>	These approvals apply together with supported AXIS P39 Series network cameras	Installation guide, drill template Top cover tool Allen key Lens tool kit
		<b>Warranty</b>
		Axis 3-year warranty, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>

a. Lenses for AXIS P39 Series network cameras

**Environmental responsibility:**  
[www.axis.com/environmental-responsibility](http://www.axis.com/environmental-responsibility)